

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support

Obsolescence Management

PCAP

Embedded Systems

Human Machine Interface

Touch Solutions

Software

Quality Management

Open Frame Monitors

LCD Controller

Research & Development

Firmware

EMC tests

on-site service

Optical Bonding

In-house Manufacturing

Cover glass

System solutions

OEM Solutions

Custom Display

Production Custom designs Installation

Mechanical design




Features

- Portrait, 4.0 inch WVGA
- High outdoor readability with low backlight power.
- Wide viewing angle LCD module.

Under Development



Dimensions



Specifications

RoHS

Items	Specifications	Units	Notes
Display Size	10.08 (4.0)	cm (inch)	15.98
Display Format	480 X RGB X 800 Stripe	--	
Dot Pitch	36.00(H) X 108.00(V)	μ m	
Outline Dimensions	57.20(H) X 95.83 X 1.50(D)	mm	1.55(D):Polarizer~S CASE C
Weight	(20)	g	
Number of Colors	16.77 million	--	
Brightness	TYP (400 at 10mA , 730 at 20mA)	cd/m ²	
Viewing Angle(U/D/L/R)	80/80/80/80	deg.	CR $\geq$ 10
Input Signal Type	MIPI	--	Note1
Power Supplies	VDD 3.3, VCCIO 1.8 (Without B/L)	V	
Operating Temperature	-20 ~ +70	°C	
Storage Temperature	-30 ~ +80	°C	
Backlight	LED Backlight (7LED)	--	
Remarks	Color gamut(NTSC) : 35%(Target spec.)		

Note1 LCD-Driver has the following restriction.

Generic short / Long Write Cmd is not supported. It is only DCS Short / Long Write Cmd is supported.

※ Specifications are subject to change without notice.

August 1, 2011

ORTUS TECHNOLOGY CO.,LTD.

Sales Dept. Industrial Application

2-8-7, Asahigaoka, Hino-shi, Tokyo 191-0065, Japan

TEL +81-42-514-0630 FAX +81-42-514-0880

<http://www.ortustech.co.jp>

All Rights Reserved. Copyright (C) ORTUS TECHNOLOGY CO., LTD.

Contact