

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support

Obsolescence Management

PCAP

Embedded Systems

Human Machine Interface

Touch Solutions

Software

Quality Management

Open Frame Monitors

LCD Controller

Research & Development

Firmware

EMC tests

on-site service

Optical Bonding

In-house Manufacturing

Cover glass

System solutions

OEM Solutions

Custom Display

Production
Custom designs
Installation

Mechanical design



Product Specifications

Customer	Standard
Description	1.54" E-PAPER DISPLAY
Model Name	ET015EP03-J
Date	2023 / 08 / 08
Revision	1.0

	Design Engineering		
	Approval	Check	Design



CONTENTS

1. Over View-----	3
2. Features-----	3
3. Mechanical Specifications-----	3
4. Mechanical Drawing of EPD module -----	4
5. Input /Output Pin Assignment -----	5
6. Electrical Characteristics -----	6
6.1 Absolute Maximum Rating-----	6
6.2 Panel DC Characteristics-----	7
6.3 Panel AC Characteristics-----	8
7. Command Table -----	10
8. Optical Specifications -----	35
9. Typical Application Circuit -----	35
10. Reliability test-----	36
11. Handling, Safety and Environment Requirements -----	37
12. Matched Development Kit-----	38
13. Typical Operating Sequence -----	39
13.1 Normal Operation Flow-----	39
14. Inspection method and condition-----	40
14.1 Inspection conditio -----	40
14.2 Display area -----	40
14.3 General inspection standards for product -----	41
15. Precautions -----	42



1. Over View

ET015EP03-J is a reflective electrophoretic technology display module on an active matrix TFT substrate. The panel is capable of displaying black, white, yellow and red images depending on the associated lookup table used. The circuitry on the panel includes an integrated gate and source driver, timing controller, oscillator, DC-DC boost circuit, and memory to store the frame buffer and lookup tables, and additional circuitry to control VCOM and BORDER settings.

2. Features


- Highlight Red and Yellow color
- High contrast
- High reflectance
- Ultra wide viewing angle
- Ultra low power consumption
- Pure reflective mode
- Bi-stable display
- Antiglare hard-coated front-surface
- Low current deep sleep mode
- On chip display RAM
- Waveform stored in On-chip OTP
- Serial peripheral interface available
- On-chip oscillator
- On-chip booster and regulator control for generating VCOM, Gate and Source driving voltage
- I²C signal master interface to read external temperature sensor
- Available in COG package

3. Mechanical Specifications

Parameter	Specifications	Unit	Remark
Screen Size	1.54	Inch	
Display Resolution	152 (H)×152(V)	Pixel	Dpi:140
Active Area	27.512×27.512	mm	
Pixel Pitch	0.181×0.181	mm	
Pixel Configuration	Rectangle		
Outline Dimension	31.8(H)×37.32(V) ×1.0(D)	mm	
Weight	2.18 ± 0.5	g	



4. Mechanical Drawing of EPD module



5. Input /Output Pin Assignment

No.	Name	I/O	Description	Remark
1	NC		Do not connect with other NC pins	Keep Open
2	GDR	O	This pin is N-MOS gate control.	
3	RESE	P	Current sense input for control loop.	
4	NC	NC	Do not connect with other NC pins	Keep Open
5	VSPL	P	Positive source voltage	
6	TSCL	O	I ² C clock for external temperature sensor (I ² C interface need external pull high resistance.) Must pull high or low if not used.	
7	TSDA	I/O	I ² C data for external temperature sensor (I ² C interface need external pull high resistance.) Must pull high or low if not used.(Default low)	
8	BS	I	Input interface setting.	
9	BUSY_N	O	This pin indicates the driver status.	
10	RST_N	I	Global reset pin. Low reset. (normal pull high)	
11	DC	I	Serial communication Command/Data input	
12	CSB	I	Serial communication chip select.	
13	SCL	I	Serial communication clock input.	
14	SDA	I/O	Serial communication data input.	
15	VDDIO	P	IO voltage supply	
16	VDD	P	Digital/Analog power.	
17	VSS	P	Ground	
18	VDD_15V	P	1.5V voltage input & output	
19	VMTP	P	MTP program power (10.1V)	
20	VSP	P	Positive source voltage	
21	VGP	P	Positive gate voltage	
22	VSN	P	Negative Source driving voltage	
23	VGN	P	Negative gate voltage	
24	VCOM	O	VCOM driving voltage	

Note: I: Input, O: Output, P: Power, D: Dummy, S: Shorted line, M: Mark, PI: Power input, PO: Power output, I/O: Input / Output. PS: Power Setting, C: Capacitor pin.



6. Electrical Characteristics

6.1 Absolute Maximum Rating

Parameter	Symbol	Rating	Unit
Logic supply voltage	VDD, AVDD,VDDIO, VDD1,VPP	-0.3 to +6.0	V
Logic Input voltage	VI	-0.3 to VDDIO+0.3	V
Operating Temp range	TOPR	0 to +40	°C
Storage Temp range	TSTG	-25 to +70	°C
Optimal Storage Humidity	HSTGo	55±10	%RH


Note: Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposing device to the absolute maximum ratings in a long period of time may degrade the device and affect its reliability.



6.2 Panel DC Characteristics

Parameter	Symbol	Conditions	Applicable pin	Min.	Typ.	Max	Units
Single ground	V _{SS}	-		-	0	-	V
Logic supply voltage	V _{IO}	-	VIO	2.3	3.3	3.6	V
Core logic voltage	V _{DD}		VDD	2.3	3.3	3.6	V
High level input voltage	V _{IH}	-	-	0.7V _{IO}	-	V _{IO}	V
Low level input voltage	V _{IL}	-	-	GND	-	0.3V _{DD}	V
High level output voltage	V _{OH}	I _{OH} = 400uA	-	V _{IO} -0.4	-	-	V
Low level output voltage	V _{OL}	I _{OL} = -400uA	-	GND	-	GND +0.4	V
Typical power	P _{TYP}	V _{CI} =3.3V	-	-	8.25	-	mW
Deep sleep mode	P _{STPY}	V _{CI} =3.3V	-	-	0.003	-	mW
Typical operating current	I _{opr_VCI}	V _{CI} =3.3V	-	-	2.5	-	mA
Image update time	-	25 °C	-	-	26	-	sec
Stand-by current	I _{st_VDD}		-	-	1	5	uA

Notes: 1. The typical power is measured with following transition from horizontal 4 scale pattern to vertical 4 scale pattern.



2. The deep sleep power is the consumed power when the panel controller is in deep sleep mode.

3. The listed electrical/optical characteristics are only guaranteed under the controller & waveform provided by YOURITECH.

4. Electrical measurement: Multimeter



6.3 AC Characteristics


6.3.1 MCU Interface Selection

The 3-wire/4-wire serial port as communication interface for all the function and command setting.


3-wire/4-wire engine act as a "slave mode" for all the time, and will not issue any command to the 3-wire/4-wire bus itself.

Under read mode, 3-wire/4-wire engine will return the data during "Data phase". The returned data should be latched at the rising edge of SCL by external controller. Data in the "Hi-Z phase" will be ignored by 3-wire/4-wire engine during write operation, and should be ignored during read operation also. During read operation, external controller should float SDA pin under "Hi-Z phase" and "Data phase".


6.3.2 MCU Serial Interface (4-wire SPI)




4 pin serial interface characteristics(write mode)




4 pin serial interface characteristics(read mode)




6.3.3 MCU Serial Interface (3-wire SPI)



3 pin serial interface characteristics (write mode)



3 pin serial interface characteristics (read mode)



7. Command Table

Address	command	Bit										
		R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
R00H	Panel setting (PSR)	W	0	0	0	0	0	0	0	0	0	00H
		W	1	RES[1]	RES[0]	PST_MODE	-	UD	SHL	SHD_N	RST_N	0Fh
		W	1	LUT_EN	-	FOPT	VCMZ	TS_AUTO	TIEG	NORG	VC_LUTZ	09h
R01H	Power setting (PWR)	W	0	0	0	0	0	0	0	0	1	01H
		W	1	-	-	-	-	V_MODE	VSC_EN	VDS_EN	VDG_EN	07h
		W	1	-	-	-	-	-	-	VGPN [1]	VGPN [0]	00h
		W	1	-	VSPL_0[6]	VSPL_0[5]	VSPL_0[4]	VSPL_0[3]	VSPL_0[2]	VSPL_0[1]	VSPL_0[0]	00h
		W	1	-	VSP_1[6]	VSP_1 [5]	VSP_1 [4]	VSP_1 [3]	VSP_1 [2]	VSP_1 [1]	VSP_1 [0]	00h
		W	1	-	VSN_1[6]	VSN_1[5]	VSN_1[4]	VSN_1[3]	VSN_1[2]	VSN_1[1]	VSN_1[0]	00h
		W	1	-	VSPL_1[6]	VSPL_1[5]	VSPL_1[4]	VSPL_1[3]	VSPL_1[2]	VSPL_1[1]	VSPL_1[0]	00h
R02H	Power OFF(POF)	W	0	0	0	0	0	0	0	1	0	02H
		W	1	-	-	-	-	-	-	-	EDSE	00h
R03H	Power off Sequence Setting(PFS)	W	0	0	0	0	0	0	0	1	1	03H
		W	1	-	-	T_VDPG_OFF[1:0]	-	-	-	T_VDS_OFF[1:0]	-	00h
		W	1	-	-	VGP_LEN[3:0]	-	-	-	VGP_EXT[3:0]	-	54
		W	1	-	-	XON_DLY	-	-	-	XON_LEN	-	44
R04H	Power ON (PON)	W	0	0	0	0	0	0	1	0	0	04H
R06H	Booster Soft Start (BTST)	W	0	0	0	0	0	0	1	1	0	06H
		W	1	-	-	-	-	PHB_SFT[1:0]	-	PHA_SFT[1:0]	-	00h
		W	1	-	-	-	-	PHA_ON[5:0]	-	-	-	02h
		W	1	-	-	-	-	PHA_OFF[5:0]	-	-	-	07h
		W	1	-	-	-	-	PHB_ON[5:0]	-	-	-	02h
		W	1	-	-	-	-	PHB_OFF[5:0]	-	-	-	07h
		W	1	-	-	-	-	PHC_ON[5:0]	-	-	-	02h
		W	1	-	-	-	-	PHC_OFF[5:0]	-	-	-	07h
R07H	Deep Sleep(DSLP)	W	0	0	0	0	0	0	1	1	1	07H
		W	1	1	0	1	0	0	1	0	1	A5h
R10H	Data Start transmission (DTM)	W	0	0	0	0	1	0	0	0	0	10H
		W	1	#	#	#	#	#	#	#	#	00H
R11H	Data Stop (DSP)	W	0	0	0	0	1	0	0	0	1	11H
		R	1	Data_flag	-	-	-	-	-	-	-	--
R12H	Display Refresh (DRF)	W	0	0	0	0	1	0	0	1	0	12H
		W	1	-	-	-	-	-	-	-	AC/DC VCOM	00H
R17H	Auto sequence (AUTO)	W	0	0	0	0	1	0	1	1	1	17H
		W	1	Code[7]	Code[6]	Code[5]	Code[4]	Code[3]	Code[2]	Code[1]	Code[0]	A5h
R30H	PLL control (PLL)	W	0	0	0	1	1	0	0	0	0	30H
		W	1	-	-	-	-	Dyna	-	FR[2:0]	-	02h
R40H	Temperature Sensor Command (TSC)	W	0	0	1	0	0	0	0	0	0	40H
		R	1	D10/TS[7]	D9/TS[7]	D8/TS[6]	D7/TS[5]	D6/TS[4]	D5/TS[3]	D4/TS[2]	D3/TS[1]	--
		R	1	D2/ TS[9]	D1/TS[8]	D0	-	-	-	-	-	--
R41H	Temperature Sensor Calibration (TSE)	W	0	0	1	0	0	0	0	0	1	41H
		W	1	TSE	-	-	TO[4]	TO[3]	TO[2]	TO[1]	TO[0]	00h
R42H	Temperature Sensor Write (TSW)	W	0	0	1	0	0	0	0	1	0	42H
		W	1	WATTR[7]	WATTR[6]	WATTR[5]	WATTR[4]	WATTR[3]	WATTR[2]	WATTR[1]	WATTR[0]	00h
		W	1	WMSB[7]	WMSB[6]	WMSB[5]	WMSB[4]	WMSB[3]	WMSB[2]	WMSB[1]	WMSB[0]	00h
		W	1	WLSB[7]	WLSB[6]	WLSB[5]	WLSB[4]	WLSB[3]	WLSB[2]	WLSB[1]	WLSB[0]	00h
R43H	Temperature Sensor	W	0	0	1	0	0	0	0	1	1	43H



	Read (TSR)	R	1	RMSB[7]	RMSB[6]	RMSB[5]	RMSB[4]	RMSB[3]	RMSB[2]	RMSB[1]	RMSB[0]	--
		R	1	RLSB[7]	RLSB[6]	RLSB[5]	RLSB[4]	RLSB[3]	RLSB[2]	RLSB[1]	RLSB[0]	--
R50H	VCOM and DATA interval setting (CDI)	W	0	0	1	0	1	0	0	0	0	50H
		W	1	VBD[2]	VBD[1]	VBD[0]	DDX	CDI[3]	CDI[2]	CDI[1]	CDI[0]	97h
R51H	Lower Power Detection (LPD)	W	0	0	1	0	1	0	0	0	1	51H
		R	1	-	-	-	-	-	-	-	LPD	--
		W	0	0	1	1	0	0	0	0	1	61H
R61H	Resolution setting(TRES)	W	1	-	-	-	-	-	-	HRES(9)	HRES(8)	00h
		W	1	HRES(7)	HRES(6)	HRES(5)	HRES(4)	HRES(3)	HRES(2)	0	0	00h
		W	1	-	-	-	-	-	-	VRES(8)	VRES(0)	00h
		W	1	VRES(7)	VRES(6)	VRES(5)	VRES(4)	VRES(3)	VRES(2)	VRES(1)	VRES(0)	00h
R65H	Gate/Source Start Setting(GSST)	W	0	0	1	1	0	0	1	0	1	65H
		W	1	-	-	-	-	-	-	S_start(9)	S_start(8)	00h
		W	1	S_start(7)	S_start(6)	S_start(5)	S_start(4)	S_start(3)	S_start(2)	0	0	00h
		W	1	-	-	-	-	-	-	G_start(9)	G_start(8)	00h
		W	1	G_start(7)	G_start(6)	G_start(5)	G_start(4)	G_start(3)	G_start(2)	G_start(1)	G_start(0)	00h
R70H	REVISION (REV)	W	0	0	1	1	1	0	0	0	0	70H
		R	1	0	0	0	0	0	0	1	1	03h
		R	1	0	0	0	0	0	0	1	0	02h
		R	1	0	0	0	0	0	0	0	1	01h
R80H	Auto Measure Vcom (AMV)	W	0	1	0	0	0	0	0	0	0	80 H
		W	1	P[1]	P[0]	AMVT[1]	AMVT[0]	XON	AMVS	AMV	AMVE	00h
R81H	Vcom Value (VV)	W	0	1	0	0	0	0	0	0	1	81H
		R	1	-	VV[6]	VV[5]	VV[4]	VV[3]	VV[2]	VV[1]	VV[0]	--
R82H	Vcom_DC Setting register(VDCS)	W	0	1	0	0	0	0	0	1	0	82H
		W	1	MTP_VCM	VDCS[6]	VDCS[5]	VDCS[4]	VDCS[3]	VDCS[2]	VDCS[1]	VDCS[0]	00h
R83H	Partial Window (PTLW)	W	0	1	0	0	0	0	0	1	1	83H
		W	1	-	-	-	-	-	-	HRST(9)	HRST(8)	00h
		W	1	HRST(7)	HRST(6)	HRST(5)	HRST(4)	HRST(3)	HRST(2)	0	0	00h
		W	1	-	-	-	-	-	-	HRED(9)	HRED(8)	00h
		W	1	HRED(7)	HRED(6)	HRED(5)	HRED(4)	HRED(3)	HRED(2)	0	0	00h
		W	1	-	-	-	-	-	-	VRST(9)	VRST(8)	00h
		W	1	VRST(7)	VRST(6)	VRST(5)	VRST(4)	VRST(3)	VRST(2)	VRST(1)	VRST(0)	00h
		W	1	-	-	-	-	-	-	VRST(9)	VRST(8)	00h
		W	1	VRST(7)	VRST(6)	VRST(5)	VRST(4)	VRST(3)	VRST(2)	VRST(1)	VRST(0)	00h
		W	1	-	-	-	-	-	-	-	PMOD	00h
R90H	Program mode(PGM)	W	0	1	0	0	1	0	0	0	0	90H
R91H	Active Program(APG)	W	0	1	0	0	1	0	0	0	1	91H
R92H	Read MTP data (RMTP)	W	0	1	0	0	1	0	0	1	0	92H
		R	1	#	#	#	#	#	#	#	#	-
R9EH	REVISION2 (REV2)	W	0	1	0	0	1	1	1	1	0	9EH
		R	1	0	0	0	0	0	0	0	1	01h
R9FH	Read MTP Reserved Bytes(RMRB)	W	0	1	0	0	1	1	1	1	1	9FH
		R	1	#	#	#	#	#	#	#	#	-
RE3H	Power saving(PWS)	W	0	1	1	1	0	0	0	1	1	E3H
		W	1	VCOM_W [3]	VCOM_W [2]	VCOM_W [1]	VCOM_W [0]	SD_W[3]	SD_W[2]	SD_W[2]	SD_W[0]	00h
RE4H	LVD voltage Select(LVSEL)	W	0	1	1	1	0	0	1	0	0	E4H
		W	1	-	-	-	-	-	-	LVD_SEL [1]	LVD_SEL [0]	03h

R00H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
PSR	W	0	0	0	0	0	0	0	0	0	00H
1 st Parameter	W	1	RES[1]	RES[0]	PST_MODE	-	UD	SHL	SHD_N	RST_N	0Fh
2 nd Parameter	W	1	LUT_EN	-	FOPT	VCMZ	TS_AUTO	TIEG	NORG	VC_LUTZ	09h

NOTE: "-" Don't care, can be set to VDD or GND level



Description	-The command defines as :		
	1 st parameter		
	Bit	Name	Description
	0	RST_N	RST_N function 1: no effect. (default) 0: Booster OFF, Register data are set to their default values, and Source/Boder/Vcom: floating
	1	SHD_N	SHD_N function 0 : Booster OFF, register data are kept, and Source/Boder/Vcom are kept 0V or floating. 1 : Booster on. (default)
	2	SHL	SHL function 0: Shift left; First data=Sn→Sn-1 →...→S2→Last data=S1. 1: Shift right: First data=S1→S2 →...→Sn-1→Last data=Sn. (default)
	3	UD	UD function 0:Scan down; First line=Gn→Gn-1 →...→G2→Last line=G1. 1:Scan up; First line=G1→G2 →...→Gn-1→Last line=Gn. (default)
	5	PST_MODE	Power switch operation mode 0:Power switching time in the period of frame scanning.(default) 1:Power switching time in the external period before frame scanning.
	7-6	RES[1,0]	Resolution setting 00: Display resolution is 176x296 (default) 01: Display resolution is 128x296 10: Display resolution is 128x250 11: Display resolution is 112x204
	2 nd parameter		
	Bit	Name	Description
	0	VC_LUTZ	VCOM status function 0 : No effect 1 : After refreshing display,the output of VCOM is set to floating automatically (default)
	1	NORG	VCOM status function 0 : No effect (default) 1 : After refreshing display, VCOM is tied to GND before power off
	2	TIEG	VGN power off status function 0 : No effect (default) 1 : Power off, VGN will be tied to GND
	3	TS_AUTO	Temperature sensing will be activated automatically one time 0 : Before enabling booster, Temperature Sensor will be activated automatically one time. 1 : When RST_N low to high, Temperature Sensor will be activated automatically one time. (default)
	4	VCMZ	VCOM status function 0 : No effect (default) 1 : VCOM is always floating
	5	FOPT	FOPT function 0: Scan 1 frame after waveform finished(default) 1: No scan after waveform finished and switch the source channel output to Hiz.
	7	LUT_EN	LUT selection setting 0 : Using LUT from MTP(default) 1 : Using LUT from register



Priority of VCOM setting: VCMZ > NORG > FOPT > VC_LUTZ

FOPT setting is part of refreshing display.
FOPT: Power off floating.

Notes:

1. Non-select gate line keep at VGN for DSP/DRF and AMV
2. Dummy source line follow LUTC for DSP/DRF
3. When SHD_N become low, DCDC will turn off. Register and SRAM data will keep until VDD turn off. SD output and VCOM will base on previous condition. It may have two condition: 0V or floating.
4. When RST_N become low, driver will reset. All register will reset to default value. All of the driver's functions will disable. Source/Gate/Border/VCOM will be released to floating

R01H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
PWR	W	0	0	0	0	0	0	0	0	1	01h
1 st Parameter	W	1	-	-	-	-	V_MODE	VSC_EN	VDS_EN	VDG_EN	07h
2 nd Parameter	W	1	-	-	-	-	-	-	VGPN [1]	VGPN [0]	00h
3 rd Parameter	W	1	-	VSPL_0 [6:0]							00h
4 th Parameter	W	1	-	VSP_1 [6:0]							00h
5 th Parameter	W	1	-	VSN_1 [6:0]							00h
6 th Parameter	W	1	-	VSPL_1 [6:0]							00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as :	
	1 st Parameter:	
	Bit	Name
	0	VDG_EN
	1	VDS_EN
	2	VSC_EN
	3	V_MODE
	Description	
	Gate power selection. 0 : External gate power from VGP/VGN pins. 1 : Internal DCDC function for generate VGP/VGN. (default)	
	Source power selection. 0 : External source power from VSP/VSN pins. 1 : Internal regulator function for generate VSP/VSN (default)	
	Source LV power selection. 0 : External source power from VSPL pins. 1 : Internal regulator function for generate VSPL (default)	
	Source Power switching mode. 0: Mode0(default) 1: Mode1	
	2nd Parameter:	
	Bit	Name
	1-0	VGPN
	Description	
	VGPN Voltage Level. 00: VGP=20 v, VGN=-20v (default) 01: VGP=17 v, VGN=-17v 10: VGP=15 v, VGN=-15v 11: VGP=10 v, VGN=-10v	



3rd & 4th & 6th Parameter: Internal VSP_1/VSPL_0/ VSPL_1 power selection

Bit	Name	Description					
6-0	VSP_1 & VSPL_0 & VSPL_1	Internal VSP & VSPL power selection.					
		bit[6:0]	Voltage(V)	bit [6:0]	Voltage(V)	bit [6:0]	Voltage(V)
		0000000	00h	3	0101001	29h	7.1
		0000001	01h	3.1	0101010	2Ah	7.2
		0000010	02h	3.2	0101011	2Bh	7.3
		0000011	03h	3.3	0101100	2Ch	7.4
		0000100	04h	3.4	0101101	2Dh	7.5
		0000101	05h	3.5	0101110	2Eh	7.6
		0000110	06h	3.6	0101111	2Fh	7.7
		0000111	07h	3.7	0110000	30h	7.8
		0001000	08h	3.8	0110001	31h	7.9
		0001001	09h	3.9	0110010	32h	8
		0001010	0Ah	4	0110011	33h	8.1
		0001011	0Bh	4.1	0110100	34h	8.2
		0001100	0Ch	4.2	0110101	35h	8.3
		0001101	0Dh	4.3	0110110	36h	8.4
		0001110	0Eh	4.4	0110111	37h	8.5
		0001111	0Fh	4.5	0111000	38h	8.6
		0010000	10h	4.6	0111001	39h	8.7
		0010001	11h	4.7	0111010	3Ah	8.8
		0010010	12h	4.8	0111011	3Bh	8.9
		0010011	13h	4.9	0111100	3Ch	9
		0010100	14h	5	0111101	3Dh	9.1
		0010101	15h	5.1	0111110	3Eh	9.2
		0010110	16h	5.2	0111111	3Fh	9.3
		0010111	17h	5.3	1000000	40h	9.4
		0011000	18h	5.4	1000001	41h	9.5
		0011001	19h	5.5	1000010	42h	9.6
		0011010	1Ah	5.6	1000011	43h	9.7
		0011011	1Bh	5.7	1000100	44h	9.8
		0011100	1Ch	5.8	1000101	45h	9.9
		0011101	1Dh	5.9	1000110	46h	10
		0011110	1Eh	6	1000111	47h	10.1
		0011111	1Fh	6.1	1001000	48h	10.2
		0100000	20h	6.2	1001001	49h	10.3
		0100001	21h	6.3	1001010	4Ah	10.4
		0100010	22h	6.4	1001011	4Bh	10.5
		0100011	23h	6.5	1001100	4Ch	10.6
		0100100	24h	6.6	1001101	4Dh	10.7
		0100101	25h	6.7	1001110	4Eh	10.8
		0100110	26h	6.8	1001111	4Fh	10.9
		0100111	27h	6.9	1010000	50h	11
		0101000	28h	7	1010001	51h	11.1
		other					15



5th Parameter: Internal VSN_1 power selection

Bit	Name	Description								
6-0	VSN_1	Internal VSN power selection.								
		bit[6:0]		Voltage(V)	bit [6:0]		Voltage(V)	bit [6:0]		Voltage(V)
		0000000	00h	-3	0101001	29h	-7.1	1010010	52h	-11.2
		0000001	01h	-3.1	0101010	2Ah	-7.2	1010011	53h	-11.3
		0000010	02h	-3.2	0101011	2Bh	-7.3	1010100	54h	-11.4
		0000011	03h	-3.3	0101100	2Ch	-7.4	1010101	55h	-11.5
		0000100	04h	-3.4	0101101	2Dh	-7.5	1010110	56h	-11.6
		0000101	05h	-3.5	0101110	2Eh	-7.6	1010111	57h	-11.7
		0000110	06h	-3.6	0101111	2Fh	-7.7	1011000	58h	-11.8
		0000111	07h	-3.7	0110000	30h	-7.8	1011001	59h	-11.9
		0001000	08h	-3.8	0110001	31h	-7.9	1011010	5Ah	-12
		0001001	09h	-3.9	0110010	32h	-8	1011011	5Bh	-12.1
		0001010	0Ah	-4	0110011	33h	-8.1	1011100	5Ch	-12.2
		0001011	0Bh	-4.1	0110100	34h	-8.2	1011101	5Dh	-12.3
		0001100	0Ch	-4.2	0110101	35h	-8.3	1011110	5Eh	-12.4
		0001101	0Dh	-4.3	0110110	36h	-8.4	1011111	5Fh	-12.5
		0001110	0Eh	-4.4	0110111	37h	-8.5	1100000	60h	-12.6
		0001111	0Fh	-4.5	0111000	38h	-8.6	1100001	61h	-12.7
		0010000	10h	-4.6	0111001	39h	-8.7	1100010	62h	-12.8
		0010001	11h	-4.7	0111010	3Ah	-8.8	1100011	63h	-12.9
		0010010	12h	-4.8	0111011	3Bh	-8.9	1100100	64h	-13
		0010011	13h	-4.9	0111100	3Ch	-9	1100101	65h	-13.1
		0010100	14h	-5	0111101	3Dh	-9.1	1100110	66h	-13.2
		0010101	15h	-5.1	0111110	3Eh	-9.2	1100111	67h	-13.3
		0010110	16h	-5.2	0111111	3Fh	-9.3	1101000	68h	-13.4
		0010111	17h	-5.3	1000000	40h	-9.4	1101001	69h	-13.5
		0011000	18h	-5.4	1000001	41h	-9.5	1101010	6Ah	-13.6
		0011001	19h	-5.5	1000010	42h	-9.6	1101011	6Bh	-13.7
		0011010	1Ah	-5.6	1000011	43h	-9.7	1101100	6Ch	-13.8
		0011011	1Bh	-5.7	1000100	44h	-9.8	1101101	6Dh	-13.9
		0011100	1Ch	-5.8	1000101	45h	-9.9	1101110	6Eh	-14
		0011101	1Dh	-5.9	1000110	46h	-10	1101111	6Fh	-14.1
		0011110	1Eh	-6	1000111	47h	-10.1	1110000	70h	-14.2
0011111	1Fh	-6.1	1001000	48h	-10.2	1110001	71h	-14.3		
0100000	20h	-6.2	1001001	49h	-10.3	1110010	72h	-14.4		
0100001	21h	-6.3	1001010	4Ah	-10.4	1110011	73h	-14.5		
0100010	22h	-6.4	1001011	4Bh	-10.5	1110100	74h	-14.6		
0100011	23h	-6.5	1001100	4Ch	-10.6	1110101	75h	-14.7		
0100100	24h	-6.6	1001101	4Dh	-10.7	1110110	76h	-14.8		
0100101	25h	-6.7	1001110	4Eh	-10.8	1110111	77h	-14.9		
0100110	26h	-6.8	1001111	4Fh	-10.9	1111000	78h	-15		
0100111	27h	-6.9	1010000	50h	-11	other		-15		
0101000	28h	-7	1010001	51h	-7.1					



5th Parameter: Internal VSN_1 power selection

Bit	Name	Description					
6-0	VSN_1	Internal VSN power selection.					
		bit[6:0]	Voltage(V)	bit [6:0]	Voltage(V)	bit [6:0]	Voltage(V)
		0000000	00h	-3	0101001	29h	-7.1
		0000001	01h	-3.1	0101010	2Ah	-7.2
		0000010	02h	-3.2	0101011	2Bh	-7.3
		0000011	03h	-3.3	0101100	2Ch	-7.4
		0000100	04h	-3.4	0101101	2Dh	-7.5
		0000101	05h	-3.5	0101110	2Eh	-7.6
		0000110	06h	-3.6	0101111	2Fh	-7.7
		0000111	07h	-3.7	0110000	30h	-7.8
		0001000	08h	-3.8	0110001	31h	-7.9
		0001001	09h	-3.9	0110010	32h	-8
		0001010	0Ah	-4	0110011	33h	-8.1
		0001011	0Bh	-4.1	0110100	34h	-8.2
		0001100	0Ch	-4.2	0110101	35h	-8.3
		0001101	0Dh	-4.3	0110110	36h	-8.4
		0001110	0Eh	-4.4	0110111	37h	-8.5
		0001111	0Fh	-4.5	0111000	38h	-8.6
		0010000	10h	-4.6	0111001	39h	-8.7
		0010001	11h	-4.7	0111010	3Ah	-8.8
		0010010	12h	-4.8	0111011	3Bh	-8.9
		0010011	13h	-4.9	0111100	3Ch	-9
		0010100	14h	-5	0111101	3Dh	-9.1
		0010101	15h	-5.1	0111110	3Eh	-9.2
		0010110	16h	-5.2	0111111	3Fh	-9.3
		0010111	17h	-5.3	1000000	40h	-9.4
		0011000	18h	-5.4	1000001	41h	-9.5
		0011001	19h	-5.5	1000010	42h	-9.6
		0011010	1Ah	-5.6	1000011	43h	-9.7
		0011011	1Bh	-5.7	1000100	44h	-9.8
		0011100	1Ch	-5.8	1000101	45h	-9.9
		0011101	1Dh	-5.9	1000110	46h	-10
		0011110	1Eh	-6	1000111	47h	-10.1
		0011111	1Fh	-6.1	1001000	48h	-10.2
		0100000	20h	-6.2	1001001	49h	-10.3
		0100001	21h	-6.3	1001010	4Ah	-10.4
		0100010	22h	-6.4	1001011	4Bh	-10.5
		0100011	23h	-6.5	1001100	4Ch	-10.6
		0100100	24h	-6.6	1001101	4Dh	-10.7
		0100101	25h	-6.7	1001110	4Eh	-10.8
		0100110	26h	-6.8	1001111	4Fh	-10.9
		0100111	27h	-6.9	1010000	50h	-11
		0101000	28h	-7	1010001	51h	-7.1
		other					-15



Notes:

1. VSP_0/VSN_0 voltage output is ± 15 V fixed value.
2. When switching Mode0 or Mode1, the voltage output is:
 Mode0: VSP_0(+15) / VSN_0 (-15) / VSPL_0 (+3~+15)
 Mode1: VSP_1(+3 ~ +15) / VSN_1(-3 ~ -15) / VSPL_1(+3 ~ +15)

	Mode0	Mode1
VSP	VSP_0(+15)	VSP_1(+3~+15)
VSN	VSN_0(-15)	VSN_1(-3~-15)
VSPL	VSPL_0(+3~+15)	VSPL_1(+3~+15)

3. If gate voltage is set to ± 15 v, ± 10 v, IC will auto correct source voltage as follows

- I. VGP- VSP_0 / VSPL_0 / VSP_1 / VSPL_1 ≥ 2 v
- II. VGN- VSN_0 / VSN_1 ≥ -2 v

For example:

	symbol	Voltage setting	Real Voltage
Voltage	VGP	10v	+10v
	VGN	10v	-10v
	VSP_0	+15v	+8v
	VSN_0	-15v	-8v
	VSP_1	+5v	+5v
	VSN_1	-5v	-5v
	VSPL	+15v	+8v
	VCOMH	+15v+(-2v)	+8v +(-2v)
	VCOML	-15v+(-2v)	-8v +(-2v)
	VCOMDC	-2v	-2v

4. Voltage setting limit: VSP_0 $\geq$ VSPL_0 , VSP_1 $\geq$ VSPL_1

Restriction

R02H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
POF	W	0	0	0	0	0	0	0	1	0	02H
1 st Parameter	W	0	-	-	-	-	-	-	-	EDSE	00

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as : ● After power off command, driver will power off base on power off sequence. ● After power off command, BUSY_N signal will drop from high to low. When finish the power off sequence, BUSY_N signal will rise from low to high. ● Power off command will turn off charge pump, T-con, source driver, gate driver, VCOM, temperature sensor, but register and SRAM data will keep until VDD off. ● SD output and VCOM will base on previous condition. It may have two conditions: 0v or floating. 1st parameter <table><tr><th>Bit</th><th>Name</th><th>Description</th></tr><tr><td>0</td><td>EDSE</td><td>EPD Discharge Trigger 0 : Disable EPD discharge (default) 1 : Enable EPD discharge</td></tr></table>			Bit	Name	Description	0	EDSE	EPD Discharge Trigger 0 : Disable EPD discharge (default) 1 : Enable EPD discharge
Bit	Name	Description							
0	EDSE	EPD Discharge Trigger 0 : Disable EPD discharge (default) 1 : Enable EPD discharge							
Restriction	This command only active when BUSY_N = "1".								

R03H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
PFS	W	0	0	0	0	0	0	0	1	1	03H
1 st Parameter	W	1	-		T_VDPG_OFF [1:0]		-		T_VDS_OFF [1:0]		00h
2 nd Parameter	W	1	VGP_LEN[3:0]				VGP_EXT[3:0]				54h
3 rd Parameter	W	1	XON_DLY[3:0]				XON_LEN[3:0]				44h

NOTE: "-" Don't care, can be set to VDD or GND level



Description	-The command defines as :	
	1 st Parameter:	
	Bit	Name
	1-0	T_VDS_OFF
	5-4	T_VDPG_OFF
		Description
		Power off sequence of VSP /VSN 00: 20 ms (default) 01: 40 ms 10: 60 ms 11: 80 ms
		Power off sequence of VGP and VGN 00: 20 ms (default) 01: 40 ms 10: 60 ms 11: 80 ms
	2 nd Parameter	
	Bit	Name
	1-0	VGP_EXT
	7-4	VGP_LEN
		Description
		VGP extension time 0000: 0 ms 0001: 500 ms 0010: 1000 ms 0011: 1500 ms 0100: 2000 ms (default) 0101: 2500 ms 0110: 3000 ms 0111: 3500 ms 1000: 4000 ms 1001: 4500 ms 1010: 5000 ms 1011: 5500 ms 1100: 6000 ms 1101: 6500 ms
		When power off, the length of time VGP stay 10V 0000: 0 ms 0001: 500 ms 0010: 1000 ms 0011: 1500 ms 0100: 2000 ms 0101: 2500 ms (default) 0110: 3000 ms 0111: 3500 ms 1000: 4000 ms 1001: 4500 ms 1010: 5000 ms 1011: 5500 ms 1100: 6000 ms 1101: 6500 ms
		1100: 6000 ms 1101: 6500 ms
	3 rd Parameter:	
	Bit	Name
	3-0	XON_LEN
		Description
		XON enable time 0000: 0 ms 0001: 500 ms 0010: 1000 ms 0011: 1500 ms 0100: 2000 ms (default) 0101: 2500 ms 0110: 3000 ms 0111: 3500 ms 1000: 4000 ms 1001: 4500 ms 1010: 5000 ms 1011: 5500 ms 1100: 6000 ms



Description	Bit[5:0]	Description	Bit[5:0]	Description	Bit[5:0]	Description
Minimum OFF time setting of PHA_OFF & PHB_OFF & PHC_OFF	000000	Period1	010110	Period23	101100	Period45
	000001	Period2	010111	Period24	101101	Period46
	000010	Period3	011000	Period25	101110	Period47
	000011	Period4	011001	Period26	101111	Period48
	000100	Period5	011010	Period27	110000	Period49
	000101	Period6	011011	Period28	110001	Period50
	000110	Period7	011100	Period29	110010	Period51
	000111	Period8	011101	Period30	110011	Period52
	001000	Period9	011110	Period31	110100	Period53
	001001	Period10	011111	Period32	110101	Period54
	001010	Period11	100000	Period33	110110	Period55
	001011	Period12	100001	Period34	110111	Period56
	001100	Period13	100010	Period35	111000	Period57
	001101	Period14	100011	Period36	111001	Period58
	001110	Period15	100100	Period37	111010	Period59
	001111	Period16	100101	Period38	111011	Period60
	010000	Period17	100110	Period39	111100	Period61
	010001	Period18	100111	Period40	111101	Period62
	010010	Period19	101000	Period41	111110	Period63
	010011	Period20	101001	Period42	111111	Period64
	010100	Period21	101010	Period43		
	010101	Period22	101011	Period44		
Restriction						

R07H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
DSLP	W	0	0	0	0	0	0	1	1	1	07H
1 st Parameter	W	1	1	0	1	0	0	1	0	1	A5h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	The command define as follows: After this command is transmitted, the chip would enter the deep-sleep mode to save power. The deep sleep mode would return to standby by hardware reset. The only one parameter is a check code, the command would be excited if check code = 0xA5.
Restriction	This command only active when BUSY_N = "1".

R10H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
DTM	W	0	0	0	0	1	0	0	0	0	10H
2 bit mode	W	1									
1 st Parameter	W	1	Pixel1	Pixel2	Pixel3	Pixel4					00h
:	W	1	:	:	:	:	:	:	:	:	00h
M th Parameter	W	1	Pixel(n-3)	Pixel(n-2)	Pixel(n-1)	Pixel(n)					00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	The command define as follows: The register is indicates that user start to transmit data, then write to SRAM. While data transmission complete, user must send command 12H. Then chip will start to send data/VCOM for panel.				
	Pixel [1~n][1:0]: 2-bit/pixel				
	Image Data	DDX=1(default)		DDX=0	
	Pixel[1:0]	Gray level select	IP output LUT select	Gray level select	IP output LUT select
	00b	Gray0	ogray00	Gray3	ogray03
	01b	Gray1	ogray01	Gray2	ogray02
	10b	Gray2	ogray02	Gray1	ogray01
	11b	Gray3	ogray03	Gray0	ogray00



	Data mapping example: When DDX=1, Pixel[1:0]=01 -> Gray level select=Gray1, follow LUT data output from IP output port "ogray01". When DDX=0, Pixel[1:0]=11 -> Gray level select=Gray0, follow LUT data output from IP output port "ogray00".
Restriction	

R11H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
DSP	W	0	0	0	0	1	0	0	0	1	11H
1 st Parameter	R	1	Data_flag	-	-	-	-	-	-	-	-

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as : ■While finished the data transmitting, user must send this command to driver and read Data_flag information. 1st Parameter: <table><tr><th>Bit</th><th>Name</th><th>Description</th></tr><tr><td>7</td><td>Data_flag</td><td>0: Driver didn't receive all the data. 1: Driver has already received all of the one frame data.</td></tr></table> After "Data Start" (10h) or "Data Stop" (11h) commands and when data_flag=1, BUSY_N signal will become "0" and the refreshing of panel starts.	Bit	Name	Description	7	Data_flag	0: Driver didn't receive all the data. 1: Driver has already received all of the one frame data.
Bit	Name	Description					
7	Data_flag	0: Driver didn't receive all the data. 1: Driver has already received all of the one frame data.					
Restriction	This command only actives when BUSY N = "1".						

R12H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
DRF	W	0	0	0	0	1	0	0	1	0	12H
1 st Parameter	W	1	-	-	-	-	-	-	-	AC/DC VCOM	00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as : While users send this command, driver will refresh display (data/VCOM) base on SRAM data and LUT. AC/DC VCOM: 0: AC VCOM, VCOM will follow LUTC when updating image. (default) 1: DC VCOM, VCOM will always be VCOMDC when updating image After display refresh command, BUSY_N signal will become "0"
Restriction	This command only actives when BUSY_N = "1"



R17H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
Auto Sequence	W	0	0	0	0	1	0	1	1	1	17H
1 st Parameter	W	1	Code[7]	Code[6]	Code[5]	Code[4]	Code[3]	Code[2]	Code[1]	Code[0]	A5h

Description	The command can enable the internal sequence to execute several commands continuously. The successive execution can minimize idle time to avoid unnecessary power consumption and reduce the complexity of host's control procedure. The sequence contains several operations, including PON, DRF, POF, DSLP. AUTO (0x17) + Code(0xA5) = (PON→DRF→POF) AUTO (0x17) + Code(0xA7) = (PON→DRF→POF→DSLP)
Restriction	This command only actives when BUSY_N = "1".

R30H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
PLL	W	0	0	0	1	1	0	0	0	0	30H
1 st Parameter	W	1	-	-	-	-	Dyna	FR[2]	FR[1]	FR[0]	02h

NOTE: "-" Don't care, can be set to VDD or GND level



Description	-The command defines as: The command controls the PLL clock frequency. The PLL structure must support the following frame rates: <table border="1"> <tr> <th>bit3</th><th>Dynamic frame rate</th></tr> <tr> <td>0</td><td>Disable(default)</td></tr> <tr> <td>1</td><td>Enable</td></tr> </table> <table border="1"> <tr> <th>FR[2:0]</th><th>Frame rate</th></tr> <tr> <td>000</td><td>12.5 Hz</td></tr> <tr> <td>001</td><td>25 Hz</td></tr> <tr> <td>010</td><td>50 Hz(default)</td></tr> <tr> <td>011</td><td>65 Hz</td></tr> <tr> <td>100</td><td>75 Hz</td></tr> <tr> <td>101</td><td>85 Hz</td></tr> <tr> <td>110</td><td>100 Hz</td></tr> <tr> <td>111</td><td>120 Hz</td></tr> </table>	bit3	Dynamic frame rate	0	Disable(default)	1	Enable	FR[2:0]	Frame rate	000	12.5 Hz	001	25 Hz	010	50 Hz(default)	011	65 Hz	100	75 Hz	101	85 Hz	110	100 Hz	111	120 Hz
bit3	Dynamic frame rate																								
0	Disable(default)																								
1	Enable																								
FR[2:0]	Frame rate																								
000	12.5 Hz																								
001	25 Hz																								
010	50 Hz(default)																								
011	65 Hz																								
100	75 Hz																								
101	85 Hz																								
110	100 Hz																								
111	120 Hz																								
remark	-Horizontal  -Vertical 																								
Restriction																									

R40H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
TSC	W	0	0	1	0	0	0	0	0	0	40H
1 st Parameter	R	1	D10/TS[7]	D9/TS[6]	D8/TS[5]	D7/TS[4]	D6/TS[3]	D5/TS[2]	D4/TS[1]	D3/TS[0]	-
2 nd Parameter	R	1	D2/TS[9]	D1/TS[8]	D0	-	-	-	-	-	-

NOTE: "-" Don't care, can be set to VDD or GND level

Description

-The command define as follows:

This command indicates the temperature value.

If R41H(TSE) bit7 set to 0, this command reads internal temperature sensor value.

If R41H(TSE) bit7 set to 1, this command reads external (LM75) temperature sensor value

TS[7:0]/D[10:3]	T (°C)	TS[7:0]/D[10:3]	T (°C)	TS[7:0]/D[10:3]	T (°C)
11100111	-25	00000000	0	00011001	25
11101000	-24	00000001	1	00011010	26
11101001	-23	00000010	2	00011011	27
11101010	-22	00000011	3	00011100	28
11101011	-21	00000100	4	00011101	29
11101100	-20	00000101	5	00011110	30
11101101	-19	00000110	6	00011111	31
11101110	-18	00000111	7	00100000	32
11101111	-17	00001000	8	00100001	33
11110000	-16	00001001	9	00100010	34



11110001	-15	00001010	10	00100011	35
11110010	-14	00001011	11	00100100	36
11110011	-13	00001100	12	00100101	37
11110100	-12	00001101	13	00100110	38
11110101	-11	00001110	14	00100111	39
11110110	-10	00001111	15	00101000	40
11110111	-9	00010000	16	00101001	41
11111000	-8	00010001	17	00101010	42
11111001	-7	00010010	18	00101011	43
11111010	-6	00010011	19	00101100	44
11111011	-5	00010100	20	00101101	45
11111100	-4	00010101	21	00101110	46
11111101	-3	00010110	22	00101111	47
11111110	-2	00010111	23	00110000	48
11111111	-1	00011000	24	00110001	49

TS[9:8]	T (°C)
00	+0
01	+0.25
10	+0.5
11	+0.75

Restriction	This command only actives when BUSY_N = "1".
-------------	--

R41H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
TSE	W	0	0	1	0	0	0	0	0	1	41H
1 st Parameter	W	1	TSE	-	-	TO[4]	TO[3]	TO[2]	TO[1]	TO[0]	00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description

-The command defines as:

This command indicates the driver IC temperature sensor enable and calibration function.

Reserve one temperature offset TO[3:0] for calibration

1. TO[3]: mean '+' or '-', while 0 is '+' ; 1 is '-'

2. TO[2:0]: mean temperature offset value

Bit	Name	Description
3-0	TO[3:0]	Temperature level: 0000: +0°C (default) 0001: +0.5°C 0010: +1°C 0011: +1.5°C 0100: +2°C 0101: +2.5°C 0110: +3°C 0111: +3.5°C 1000: -4°C 1001: -3.5°C 1010: -3°C 1011: -2.5°C 1100: -2°C 1101: -1.5°C 1110: -1°C 1111: -0.5°C
4	TO[4]	0: +0.0°C (default) 1: +0.25°C
7	TSE	Internal temperature sensor enable 0: Internal temperature sensor enable.(default) 1: Internal temperature sensor disable, using external temperature sensor.

Restriction

This command only actives after R04H(PON)

R42H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
TSW	W	0	0	1	0	0	0	0	1	0	42H
1 st Parameter	W	1	WATTR[7]	WATTR[6]	WATTR[5]	WATTR[4]	WATTR[3]	WATTR[2]	WATTR[1]	WATTR[0]	00h
2 nd Parameter	W	1	WMSB[7]	WMSB[6]	WMSB[5]	WMSB[4]	WMSB[3]	WMSB[2]	WMSB[1]	WMSB[0]	00h
3 rd Parameter	W	1	WLSB[7]	WLSB[6]	WLSB[5]	WLSB[4]	WLSB[3]	WLSB[2]	WLSB[1]	WLSB[0]	00h

NOTE: "-" Don't care, can be set to VDD or GND level



Description	-The command defines as: This command writes the temperature. 1st Parameter: <table><tr><th>Bit</th><th>Name</th><th>Description</th></tr><tr><td>2-0</td><td>WATTR[2:0]</td><td>Pointer setting</td></tr><tr><td>5-3</td><td>WATTR[5:3]</td><td>User-defined address bits (A2, A1, A0)</td></tr><tr><td>7-6</td><td>WATTR[7:6]</td><td>I2C Write Byte Number 00: 1 byte (head byte only) 01: 2 bytes (head byte + pointer) 10: 3 bytes (head byte + pointer + 1st parameter) 11: 4 bytes (head byte + pointer + 1st parameter + 2nd parameter)</td></tr></table> 2nd Parameter: <table><tr><th>Bit</th><th>Name</th><th>Description</th></tr><tr><td>7-0</td><td>WMSB[7:0]</td><td>MSByte of write-data to external temperature sensor</td></tr></table> 3rd Parameter: <table><tr><th>Bit</th><th>Name</th><th>Description</th></tr><tr><td>7-0</td><td>WLSB[7:0]</td><td>LSByte of write-data to external temperature sensor</td></tr></table>			Bit	Name	Description	2-0	WATTR[2:0]	Pointer setting	5-3	WATTR[5:3]	User-defined address bits (A2, A1, A0)	7-6	WATTR[7:6]	I2C Write Byte Number 00: 1 byte (head byte only) 01: 2 bytes (head byte + pointer) 10: 3 bytes (head byte + pointer + 1st parameter) 11: 4 bytes (head byte + pointer + 1st parameter + 2nd parameter)	Bit	Name	Description	7-0	WMSB[7:0]	MSByte of write-data to external temperature sensor	Bit	Name	Description	7-0	WLSB[7:0]	LSByte of write-data to external temperature sensor
Bit	Name	Description																									
2-0	WATTR[2:0]	Pointer setting																									
5-3	WATTR[5:3]	User-defined address bits (A2, A1, A0)																									
7-6	WATTR[7:6]	I2C Write Byte Number 00: 1 byte (head byte only) 01: 2 bytes (head byte + pointer) 10: 3 bytes (head byte + pointer + 1st parameter) 11: 4 bytes (head byte + pointer + 1st parameter + 2nd parameter)																									
Bit	Name	Description																									
7-0	WMSB[7:0]	MSByte of write-data to external temperature sensor																									
Bit	Name	Description																									
7-0	WLSB[7:0]	LSByte of write-data to external temperature sensor																									
Restriction	This command only actives after R04H(PON)																										

R43H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
TSR	W	0	0	1	0	0	0	0	1	1	43H
1 st Parameter	R	1	RMSB[7]	RMSB[6]	RMSB[5]	RMSB[4]	RMSB[3]	RMSB[2]	RMSB[1]	RMSB[0]	-
2 nd Parameter	R	1	RLSB[7]	RLSB[6]	RLSB[5]	RLSB[4]	RLSB[3]	RLSB[2]	RLSB[1]	RLSB[0]	-

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as: This command reads the temperature sensed by the temperature sensor. 1st Parameter: <table><tr><th>Bit</th><th>Name</th><th>Description</th></tr><tr><td>7-0</td><td>RMSB[7:0]</td><td>MSByte of read-data from external temperature sensor</td></tr></table> 2nd Parameter: <table><tr><th>Bit</th><th>Name</th><th>Description</th></tr><tr><td>7-0</td><td>RLSB[7:0]</td><td>LSByte of write-data from external temperature sensor</td></tr></table> The timing diagram illustrates the sequence of signals for the R43H command. It includes SPI (Serial Peripheral Interface) with 'TSR command' and 'TSR parameters' sections, CSB (Chip Select B) as an active-low signal, SCL (Serial Clock) with two clock pulses, SDA (Serial Data) showing the data transfer, and BUSY_N (Busy Not) as an active-low signal that goes low during the data transfer period.			Bit	Name	Description	7-0	RMSB[7:0]	MSByte of read-data from external temperature sensor	Bit	Name	Description	7-0	RLSB[7:0]	LSByte of write-data from external temperature sensor
Bit	Name	Description													
7-0	RMSB[7:0]	MSByte of read-data from external temperature sensor													
Bit	Name	Description													
7-0	RLSB[7:0]	LSByte of write-data from external temperature sensor													
Restriction	This command only actives after R04H(PON)														

R50H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
CDI	W	0	0	1	0	1	0	0	0	0	50H
1 st Parameter	W	1	VBD[2]	VBD[1]	VBD[0]	DDX	CDI[3]	CDI[2]	CDI[1]	CDI[0]	97h

NOTE: "-" Don't care, can be set to VDD or GND level



Description

-The command defines as:

This command can set 2 kinds of parameters, 1.VCOM to data output interval(CDI)

:

CDI[3:0]: This command indicates the interval of VCOM and data output. When setting the vertical back porch, **the total blanking will be keep (55hsync)**.

Bit	Name	Description
3-0	CDI[3:0]	Vcom and data interval
		0000: 17 hsync
		0001:16 hsync
		0010:15 hsync
		0011:14 hsync
		0100:13 hsync
		0101:12 hsync
		0110:11 hsync
		0111:10 hsync(default)
		1000:9 hsync
		1001:8 hsync
		1010:7 hsync
		1011:6 hsync
		1100:5 hsync
		1101:4 hsync
		1110:3 hsync
		1111:2 hsync

The diagram illustrates the timing relationship between several signals during a video frame transition:

- Internal vsync:** A single pulse indicating the start of a new frame.
- Internal hsync:** A series of horizontal sync pulses.
- Internal de:** A signal that transitions from high to low at the start of the frame.
- VCOM:** A signal that transitions from low to high at the start of the frame, labeled "VCOM output location (fixed)".
- Source data Output:** A signal that transitions from low to high at the start of the frame, labeled "Frame N data".
- Frame N VCOM:** A period of time during which VCOM is high, labeled "Frame N VCOM".
- Frame N+1 VCOM:** A period of time during which VCOM is high, labeled "Frame N+1 VCOM".
- CDI setting:** A red arrow indicating the interval between the start of VCOM and the start of Source data Output, labeled "CDI setting".
- 55 hsync-CDI setting (fixed):** A label indicating the fixed interval between the start of VCOM and the start of Source data Output, labeled "55 hsync-CDI setting (fixed)".


VBD[2:0]: Border data selection. (from LUT output by IP port border_w[1:0])			
This register will make boarder pin output being mapped to a certain gray scale.			
Bit 4	Bit7-5	Description	IP setting for Border LUT select
DDX	VBD[2:0]	Gray level	
0	000	Floating	N/A
	001	Gray3	border_buf=011
	010	Gray2	border_buf=010
	011	Gray1	border_buf=001
	100	Gray0	border_buf=000
1 (default)	000	Gray0	border_buf=000
	001	Gray1	border_buf=001
	010	Gray2	border_buf=010
	011	Gray3	border_buf=011
	100	Floating	N/A
Border output voltage level: The level selection is based on mapping LUT data.			
Ex: Gray 1 waveform is mapping to 15V,without VCOM offset, the real output on Boarder pin shall be 15V.			
Boarder output will follow FOPT definition being defined in R00h.			

R51H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
LPD	W	0	0	1	0	1	0	0	0	1	51H
1 st Parameter	R	1	-	-	-	-	-	-	-	LPD	--

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as: This command indicates the input power condition. Host can read this data to understand the battery's condition. When LPD="1", system input power is normal. When LPD="0", system input power is lower (VDD<2.5v, which could be select in RE4H (LVSEL)).										
-------------	--	--	--	--	--	--	--	--	--	--	--





Restriction This command only actives when BUSY_N = "1".

R61H		Bit									
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
TRES	W	0	0	1	1	0	0	0	0	1	61H
1 st Parameter	W	1	-	-	-	-	-	-	HRES(9)	HRES(8)	00h
2 nd Parameter	W	1	HRES(7)	HRES(6)	HRES(5)	HRES(4)	HRES(3)	HRES(2)	0	0	00h
3 rd Parameter	W	1	-	-	-	-	-	-	VRES(9)	VRES(8)	00h
4 th Parameter	W	1	VRES(7)	VRES(6)	VRES(5)	VRES(4)	VRES(3)	VRES(2)	VRES(1)	VRES(0)	00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command define as follows: When using register: Horizontal display resolution(source) = HRES Vertical display resolution(gate) = VRES Note: No matter HRES[9:8],HRES[1:0],VRST[9] value being filled, it's always be 00b. Channel disable calculation: GD : First G active = G0; LAST active GD= first active +VRES[9:0] -1 SD : First active channel: =S0 ; LAST active SD= first active +HRES[9:2]*4-1 EX :176X296 GD: First G active = G0 LAST active GD= 0+296-1= 295; (G295) SD : First active channel: =S0 LAST active SD=0+44*4-1=175; (S175) Note : Only supports source 176.ch for source 160ch. above
Restriction	Horizontal resolution should be 4-multiple.

R65H		Bit									
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
GSST	W	0	0	1	1	0	0	1	0	1	65H
1 st Parameter	W	1	-	-	-	-	-	-	S_start[9]	S_start[8]	00h
2 nd Parameter	W	1	S_start[7]	S_start[6]	S_start[5]	S_start[4]	S_start[3]	S_start[2]	0	0	00h
3 rd Parameter	W	1	-	-	-	-	-	-	G_start[9]	G_start[8]	00h
4 th Parameter	W	1	G_start[7]	G_start[6]	G_start[5]	G_start[4]	G_start[3]	G_start[2]	G_start[1]	G_start[0]	00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command define as follows: Note: No matter S_start[9:8], S_start [1:0],VRST[9] value being filled, it's always be 00b. 1.S_Start [7:0] describe which source output line is the first date line 2.G_Start[8:0] describe which gate line is the first scan line
Restriction	S_Start should be the multiple of 4



R70H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
REV	W	0	0	1	1	1	0	0	0	0	70H
1 st Parameter	R	1	0	0	0	0	0	0	1	1	03h
2 nd Parameter	R	1	0	0	0	0	0	0	1	0	02h
3 rd Parameter	R	1	0	0	0	0	0	0	0	1	01h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as: 1st & 2nd & 3rd Parameter: <table><tr><th>Bit</th><th>Description</th></tr><tr><td>7-0</td><td>CHIP_REV</td></tr></table>		Bit	Description	7-0	CHIP_REV
Bit	Description					
7-0	CHIP_REV					
Restriction						

R80H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
AMV	W	0	1	0	0	0	0	0	0	0	80H
1 st Parameter	W	1	P[1]	P[0]	AMVT[1]	AMVT[0]	XON	AMVS	AMV	AMVE	00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description

-The command defines as:

This command indicates the IC status. Host can read this data to understand the IC status.

1st Parameter:

Bit	Name	Description
0	AMVE	AMVE: Auto Measure Vcom Setting 0: Auto measure VCOM disable (default) 1: Auto measure VCOM enable
1	AMV	AMV: Analog signal 0: Get Vcom value from R81h(default) 1: Get Vcom value in analog signal
2	AMVS	AMVS: setting for Source output of AMV 0: Source output 0V during Auto Measure VCOM period. (default) 1: Source output VSPL_0 during Auto Measure VCOM period.
3	XON	XON: setting for all Gate ON of AMV 0: Gate normally scan during Auto Measure VCOM period. (default) 1: All Gate ON during Auto Measure VCOM period.
5-4	AMVT[1:0]	The sensing time of VCOM detection 00: 5s (default) 01: 10s 10: 15s 11: 20s
7-6	P[1:0]	The sensing points of sampling time 00: 2 (default) 01: 4 10: 8 11: 16 Sampling time = the last quarter of sensing time (T) VCOM = average of N points. N=2,4,8,16

Source voltage

Vcom

BUSY_N

Status of Vcom controlled by sensing mode

The last quarter of sensing time

Vcom Sensing

Average of N point. N=2,4,8,16

Restriction

This command only actives when BUSY_N = "1".



R81H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
VV	W	0	1	0	0	0	0	0	0	1	81H
1 st Parameter	R	1	-	VV[6]	VV[5]	VV[4]	VV[3]	VV[2]	VV[1]	VV[0]	--

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as: This command could get the VCOM value 1 st Parameter:										
	Bit	Name	Description								
			VCOM value								
			VCOM[6:0]	Voltage(V)	VCOM[6:0]	Voltage(V)	VCOM[6:0]	Voltage(V)	VCOM[6:0]	Voltage(V)	
			0000000	00h	0	0011100	1Ch	-1.4	0111000	38h	-2.8
			0000001	01h	-0.05	0011101	1Dh	-1.45	0111001	39h	-2.85
			0000010	02h	-0.1	0011110	1Eh	-1.5	0111010	3Ah	-2.9
			0000011	03h	-0.15	0011111	1Fh	-1.55	0111011	3Bh	-2.95
			0000100	04h	-0.2	0100000	20h	-1.6	0111100	3Ch	-3
			0000101	05h	-0.25	0100001	21h	-1.65	0111101	3Dh	-3.05
			0000110	06h	-0.3	0100010	22h	-1.7	0111110	3Eh	-3.1
			0000111	07h	-0.35	0100011	23h	-1.75	0111111	3Fh	-3.15
			0001000	08h	-0.4	0100100	24h	-1.8	1000000	40h	-3.2
			0001001	09h	-0.45	0100101	25h	-1.85	1000001	41h	-3.25
			0001010	0Ah	-0.5	0100110	26h	-1.9	1000010	42h	-3.3
			0001011	0Bh	-0.55	0100111	27h	-1.95	1000011	43h	-3.35
			0001100	0Ch	-0.6	0101000	28h	-2	1000100	44h	-3.4
			0001101	0Dh	-0.65	0101001	29h	-2.05	1000101	45h	-3.45
			0001110	0Eh	-0.7	0101010	2Ah	-2.1	1000110	46h	-3.5
			0001111	0Fh	-0.75	0101011	2Bh	-2.15	1000111	47h	-3.55
			0010000	10h	-0.8	0101100	2Ch	-2.2	1001000	48h	-3.6
			0010001	11h	-0.85	0101101	2Dh	-2.25	1001001	49h	-3.65
			0010010	12h	-0.9	0101110	2Eh	-2.3	1001010	4Ah	-3.7
			0010011	13h	-0.95	0101111	2Fh	-2.35	1001011	4Bh	-3.75
			0010100	14h	-1	0110000	30h	-2.4	1001100	4Ch	-3.8
			0010101	15h	-1.05	0110001	31h	-2.45	1001101	4Dh	-3.85
			0010110	16h	-1.1	0110010	32h	-2.5	1001110	4Eh	-3.9
			0010111	17h	-1.15	0110011	33h	-2.55	1001111	4Fh	-3.95
			0011000	18h	-1.2	0110100	34h	-2.6	1010000	50h	-4
			0011001	19h	-1.25	0110101	35h	-2.65	other		-4
			0011010	1Ah	-1.3	0110110	36h	-2.7			
			0011011	1Bh	-1.35	0110111	37h	-2.75			
Restriction											

R82H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
VDCS	W	0	1	0	0	0	0	0	1	0	82H
1 st Parameter	W	1	MTP_VCM	VDCS[6]	VDCS[5]	VDCS [4]	VDCS [3]	VDCS [2]	VDCS [1]	VDCS [0]	00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command defines as: This command set the VCOM DC value. Driver will base on this value for VCM_DC. 1 st Parameter:										
	Bit	Name	Description								
			VCOM value								
			VCOM[6:0]	Voltage(V)	VCOM[6:0]	Voltage(V)	VCOM[6:0]	Voltage(V)	VCOM[6:0]	Voltage(V)	
			0000000	00h	0(default)	0011100	1Ch	-1.4	0111000	38h	-2.8
			0000001	01h	-0.05	0011101	1Dh	-1.45	0111001	39h	-2.85
			0000010	02h	-0.1	0011110	1Eh	-1.5	0111010	3Ah	-2.9



6-0	VDCS[6:0]	0000011	03h	-0.15	0011111	1Fh	-1.55	0111011	3Bh	-2.95
		0000100	04h	-0.2	0100000	20h	-1.6	0111100	3Ch	-3
		0000101	05h	-0.25	0100001	21h	-1.65	0111101	3Dh	-3.05
		0000110	06h	-0.3	0100010	22h	-1.7	0111110	3Eh	-3.1
		0000111	07h	-0.35	0100011	23h	-1.75	0111111	3Fh	-3.15
		0001000	08h	-0.4	0100100	24h	-1.8	1000000	40h	-3.2
		0001001	09h	-0.45	0100101	25h	-1.85	1000001	41h	-3.25
		0001010	0Ah	-0.5	0100110	26h	-1.9	1000010	42h	-3.3
		0001011	0Bh	-0.55	0100111	27h	-1.95	1000011	43h	-3.35
		0001100	0Ch	-0.6	0101000	28h	-2	1000100	44h	-3.4
		0001101	0Dh	-0.65	0101001	29h	-2.05	1000101	45h	-3.45
		0001110	0Eh	-0.7	0101010	2Ah	-2.1	1000110	46h	-3.5
		0001111	0Fh	-0.75	0101011	2Bh	-2.15	1000111	47h	-3.55
		0010000	10h	-0.8	0101100	2Ch	-2.2	1001000	48h	-3.6
		0010001	11h	-0.85	0101101	2Dh	-2.25	1001001	49h	-3.65
		0010010	12h	-0.9	0101110	2Eh	-2.3	1001010	4Ah	-3.7
		0010011	13h	-0.95	0101111	2Fh	-2.35	1001011	4Bh	-3.75
		0010100	14h	-1	0110000	30h	-2.4	1001100	4Ch	-3.8
		0010101	15h	-1.05	0110001	31h	-2.45	1001101	4Dh	-3.85
		0010110	16h	-1.1	0110010	32h	-2.5	1001110	4Eh	-3.9
		0010111	17h	-1.15	0110011	33h	-2.55	1001111	4Fh	-3.95
		0011000	18h	-1.2	0110100	34h	-2.6	1010000	50h	-4
		0011001	19h	-1.25	0110101	35h	-2.65	other		-4
		0011010	1Ah	-1.3	0110110	36h	-2.7			
		0011011	1Bh	-1.35	0110111	37h	-2.75			

7	MTP_VCM	Follow MTP VCOM value in MTP mode 0: From the setting of MTP (default) 1: From the setting of register
Restriction		

R83H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
PTL	W	0	1	0	0	0	0	0	1	1	83H
1 st Parameter	W	1	-	-	-	-	-	-	HRST[9]	HRST[8]	00h
2 nd Parameter	W	1	HRST[7]	HRST[6]	HRST[5]	HRST[4]	HRST[3]	HRST[2]	-	-	00h
3 rd Parameter	W	1	-	-	-	-	-	-	HRED[9]	HRED[8]	00h
4 th Parameter	W	1	HRED[7]	HRED[6]	HRED[5]	HRED[4]	HRED[3]	HRED[2]	-	-	00h
5 th Parameter	W	1	-	-	-	-	-	-	VRST[9]	VRST[8]	00h
6 th Parameter	W	1	VRST[7]	VRST[6]	VRST[5]	VRST[4]	VRST[3]	VRST[2]	VRST[1]	VRST[0]	00h
7 th Parameter	W	1	-	-	-	-	-	-	VRED[9]	VRED[8]	00h
8 th Parameter	W	1	VRED[7]	VRED[6]	VRED[5]	VRED[4]	VRED[3]	VRED[2]	VRED[1]	VRED[0]	00h
9 th Parameter	W	1	-	-	-	-	-	-	-	PMODE	00h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-This command sets partial window.												
<table border="1"> <thead> <tr> <th>Name</th><th>Description</th></tr> </thead> <tbody> <tr> <td>HRST[9:2]</td><td>Horizontal start address</td></tr> <tr> <td>HRED[9:2]</td><td>Horizontal end address. HRED must be greater than HRST.</td></tr> <tr> <td>VRST[9:0]</td><td>Vertical start address.</td></tr> <tr> <td>VRED[9:0]</td><td>Vertical end address. VRED must be greater than VRST.</td></tr> <tr> <td>PMODE</td><td>0: disable partial mode(default) 1: enable partial mode</td></tr> </tbody> </table>		Name	Description	HRST[9:2]	Horizontal start address	HRED[9:2]	Horizontal end address. HRED must be greater than HRST.	VRST[9:0]	Vertical start address.	VRED[9:0]	Vertical end address. VRED must be greater than VRST.	PMODE	0: disable partial mode(default) 1: enable partial mode
Name	Description												
HRST[9:2]	Horizontal start address												
HRED[9:2]	Horizontal end address. HRED must be greater than HRST.												
VRST[9:0]	Vertical start address.												
VRED[9:0]	Vertical end address. VRED must be greater than VRST.												
PMODE	0: disable partial mode(default) 1: enable partial mode												
Note: No matter HRST[1:0],HRST[9:8],HRED[9:8],VRST[9],VRED[9] value being filled, it's always be 00b. No matter HRED[1:0] value being filled, it's always be 11b.													
Gates scan both inside and outside of the partial window.													



R90H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
PGM	W	0	1	0	0	1	0	0	0	0	90H

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command define as follows: After this command is issued, the chip would enter the program mode. The mode would return to standby by hardware reset.										
Restriction											

R91H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
APG	W	0	1	0	0	1	0	0	0	1	91H

NOTE: "-" Don't care, can be set to VDD or GND level


Description	-The command define as follows: After this command is transmitted, the programming state machine would be activated.										
Restriction	The BUSY flag would change state from 0 to 1 while the programming is completed.										

R92H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
RMTP	W	0	1	0	0	1	0	0	1	0	92H
1 st Parameter	R	1	Dummy								-
2 nd Parameter	R	1	The data of address 0x000 in the MTP								-
3 rd Parameter	R	1	The data of address 0x001 in the MTP								-
4 th Parameter	R	1	:								-
5 th Parameter	R	1	The data of address (n-1) in the MTP								-
6 th ~(m-1) th Parameter	R	1									-
m th Parameter	R	1	The data of address (n) in the MTP								-

NOTE: "-" Don't care, can be set to VDD or GND level

Description	-The command define as follows: The command is used for reading the content of MTP for checking the data of programming. The value of (n) is depending on the amount of programmed data, the max address = 0x17FF										
-------------	--	--	--	--	--	--	--	--	--	--	--





RE4H	Bit										
Inst/Para	R/W	D/CX	D7	D6	D5	D4	D3	D2	D1	D0	Code
LVSEL	W	0	1	1	1	0	0	1	0	0	E4H
1 st Parameter	W	1	-	-	-	-	-	-	LVD_SEL[1:0]		03h

NOTE: "-" Don't care, can be set to VDD or GND level

Description	LVD_SEL[1:0]: Low Power Voltage Selection	
	LVD_SEL[1:0]	LVD value
	00	< 2.2 V
	01	< 2.3 V
	10	< 2.4 V
	11	< 2.5 V (default)
Restriction		

8. Optical Specifications

Measurements are made with that the illumination is under an angle of 45 degree, the detection is perpendicular unless otherwise specified

Symbol	Parameter	Conditions	Min	Typ.	Max	Units	Notes
R	White Reflectivity	White	30	35	-	%	8-1
CR	Contrast Ratio	Indoor	8:1		-		8-2
GN	2Grey Level	-		DS+(WS-DS)*n(m-1)			8-3
T update	Image update time	at 25 °C		26	-	sec	
Life		Topr		1000000times or 5years			

Notes: 8-1. Luminance meter: Eye-One Pro Spectrophotometer.

8-2. CR=Surface Reflectance with all white pixel/Surface Reflectance with all black pixels.

8-3. WS: White state, DS: Dark state





10. Reliability test

NO	Test items	Test condition
1	Low-Temperature Storage	T = -25°C, 240 h Test in white pattern
2	High-Temperature Storage	T=60° C, RH=35%, 240h Test in white pattern
3	High-Temperature Operation	T=40° C, RH=35%, 240h
4	Low-Temperature Operation	0° C, 240h
5	High-Temperature, High-Humidity Operation	T=40° C, RH=80%, 240h
6	High Temperature, High Humidity Storage	T=50° C, RH=90%, 240h Test in white pattern
7	Temperature Cycle	1 cycle:[-25°C 30min]→[+60°C 30 min] : 50 cycles Test in white pattern
8	UV exposure Resistance	765W/m ² for 168hrs,40 °C Test in white pattern
9	ESD Gun	Air+/-15KV;Contact+/-8KV (Test finished product shell, not display only) Air+/-8KV;Contact+/-6KV (Naked EPD display, no including IC and FPC area) Air+/-4KV;Contact+/-2KV (Naked EPD display, including IC and FPC area)

Note: Put in normal temperature for 1hour after test finished, display performance is ok.



11. Handling, Safety and Environmental Requirements

WARNING
The display glass may break when it is dropped or bumped on a hard surface. Handle with care. Should the display break, do not touch the electrophoretic material. In case of contact with electrophoretic material, wash with water and soap.

CAUTION
The display module should not be exposed to harmful gases, such as acid and alkali gases, which corrode electronic components.
Disassembling the display module can cause permanent damage and invalidate the warranty agreements.

Observe general precautions that are common to handling delicate electronic components. The glass can break and front surfaces can easily be damaged. Moreover the display is sensitive to static electricity and other rough environmental conditions.

Data sheet status	
Product specification	The data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

Product Environmental certification
RoHS



12. Matched Development Kit

Our Development Kit designed for SPI E-paper Display aims to help users to learn how to use E-paper Display more easily. It can refresh black-white E-paper Display, three-color (black, white and red/Yellow) E-paper Display and four-color (black, white, red and yellow) YOURITECH 's E-pa per Display. And it is also added the functions of USB serial port, FLASH c hip, font chip, current detection ect.


Development Kit consists of the development board and the pinboard.

Supported development platforms include STM32, ESP32, ESP8266, Arduino UNO, etc.



13. Typical Operating Sequence


13.1 Normal Operation Flow



14. Inspection method and condition

14. 1 Inspection condition

Item	Condition
Illuminance	800~1500 lux
Temperature	22℃ ± 3℃
Humidity	55 ± 10 %RH
Distance	≥30cm
Angle	Vertical fore and aft 45
Inspection method	By eyes



14. 2 Zone definition

A Zone: Active area


B Zone: Border zone


C Zone: From B zone edge to panel edge



14. 3 General inspection standards for products


14.3.1 Appearance inspection standard

Inspection item	Figure	A zone inspection standard	B/C zone	Inspection method	MAJ/ MIN
Spot defects	Diameter $D=(L+W)/2$ (L-length, W-width) Measuring method shown in the figure below  $D=(L+W)/2$ The distance between the two spots should not be less than 10mm	7.5"-13.3"Module (Not include 7.5") : $D>1\text{mm}$ $N=0$ $0.5<D\leq 0.8$ $N\leq 4$ $D\leq 0.5$ Ignore $0.8<D\leq 1$ $N\leq 2$ 4.2"-7.5"Module (Not include 4.2") : $D>0.5$ $N=0$ $0.4<D\leq 0.5$ $N\leq 2$ $D\leq 0.25$ Ignore $0.25<D\leq 0.4$ $N\leq 4$ Module below 4.2" : $D>0.5$ $N=0$ $0.4<D\leq 0.5$ $N\leq 1$ $D\leq 0.25$ Ignore $0.25<D\leq 0.4$ $N\leq 4$ $0.1\text{mm}<D\leq 0.25$ $N\leq 3/\text{cm}^2$	Foreign matter D≤1mm Pass	Check by eyes Film gauge	MIN

Inspection item	Figure	A zone inspection standard	B/C zone	Inspection method	MAJ/ MIN
Line defects	L-Length, W-Width, (W/L)<1/4 Judged by line, (W/L)≥1/4 Judged by dot  The distance between the two lines should not be less than 5mm	7.5"-13.3"Module (Not include 7.5") : $L>10\text{mm}, N=0$ $W>0.8\text{mm}, N=0$ $5\text{mm}\leq L\leq 10\text{mm}, 0.5\text{mm}\leq W\leq 0.8\text{mm}$ $N\leq 2$ $L\leq 5\text{mm}, W\leq 0.5\text{mm}$ Ignore 4.2"-7.5"Module (Not include 4.2") : $L>8\text{mm}, N=0$ $W>0.2\text{mm}, N=0$ $2\text{mm}\leq L\leq 8\text{mm}, 0.1\text{mm}\leq W\leq 0.2\text{mm}$ $N\leq 4$ $L\leq 2\text{mm}, W\leq 0.1\text{mm}$ Ignore Module below 4.2" : $L>5\text{mm}, N=0$ $W>0.2\text{mm}, N=0$ $2\text{mm}\leq L\leq 5\text{mm}, 0.1\text{mm}\leq W\leq 0.2\text{mm}$ $N\leq 4$ $L\leq 2\text{mm}, W\leq 0.1\text{mm}$ Ignore	Ignore	Check by eyes Film gauge	MIN

Inspection item	Figure	Inspection standard	Inspection method	MAJ/ MIN
Panel chipping and crack defects	X the length, Y the width, Z the chipping height, T the thickness of the panel 崩角  崩边  玻璃裂纹 	Chipping at the edge: Module over 7.5" (Include 7.5") : $X\leq 6\text{mm}, Y\leq 1\text{mm}$ $Z\leq T$ $N=3$ Allowed Module below 7.5" (Not include 7.5"): $X\leq 3\text{mm}, Y\leq 1\text{mm}$ $Z\leq T$ $N=3$ Allowed Chipping on the corner: IC side $X\leq 2\text{mm}$ $Y\leq 2\text{mm}$, Non-IC side $X\leq 1\text{mm}$ $Y\leq 1\text{mm}$. Allowed Note: Chipping should not damage the edge wiring. If it does not affect the display, allowed	Check by eyes, Film gauge	MIN
Crack		Crack at any zone of glass , Not allowed	Check by eyes, Film gauge	MIN
Burr edge		No exceed the positive and negative deviation of the outline dimensions $X+Y\leq 0.2\text{mm}$ Allowed	Calliper	MIN
Curl of panel	 Curl height	Curl height $H\leq$ Total panel length 1% Allowed	Check by eyes	MIN



Inspection item		Figure	Inspection standard	Inspection method	MAJ / MIN
PS defect	Water proof film		1. Waterproof film damage, wrinkled, open edge, not allowed 2. Exceeding the edge of module (according to the lamination drawing) Not allowed 3. Edge warped exceeds height of technical file, not allowed	Check by eyes	MIN
RTV defect	Adhesive effect		Adhesive height exceeds the display surface, not allowed 1. Overflow, exceeds the panel side edge, affecting the size, not allowed 2. No adhesive at panel edge $\leq 1\text{mm}$, no exposure of wiring, allowed 3. No adhesive at edge and corner $1*1\text{mm}$, no exposure of wiring, allowed Protection adhesive, coverage width within $W \leq 1.5\text{mm}$, no break of adhesive, allowed	Check by eyes	MIN
	Adhesive re-fill		Dispensing is uniform, without obvious concave and breaking, bubbling and swell, not higher than the upper surface of the PS, and the diameter of the adhesive re-filling is not more than 8mm, allowed	Check by eyes	MIN
EC defect	Adhesive bubble		1. Effective edge sealing area of hot melt products $\geq 1/2$ edge sealing area; 2. Bubble $a+b \geq 1/2$ effective width, $N \leq 3$, spacing $\geq 5\text{mm}$, allowed No exposure of wiring, allowed	Check by eyes	MIN

Inspection item		Figure	Inspection standard	Inspection method	MAJ/ MIN
EC defect	Adhesive effect		1. Overflow, exceeds the panel side edge, affecting the size, not allowed 2. No adhesive at panel edge $\leq 1\text{mm}$, no exposure of wiring, allowed 3. No adhesive at edge and corner $1*1\text{mm}$, no exposure of wiring, allowed 4. Adhesive height exceeds the display surface, not allowed	Visual, caliper	MIN
Silver dot adhesive defect	Silver dot adhesive		1. Single silver dot dispensing amount $\geq 1\text{mm}$, allowed 2. One of the double silver dot dispensing amount is $\geq 1\text{mm}$ and the other has adhesive (no reference to 1mm) Allowed	Visual	MIN
			Silver dot dispensing residue on the panel $\leq 0.2\text{mm}$, allowed	Film gauge	MIN
FPC defect	FPC wiring		FPC, TCP damage / gold finger peroxidation, adhesive residue, not allowed	Visual	MIJ
	FPC golden finger		The height of burr edge of TCP punching surface $\geq 0.4\text{mm}$, not allowed	Caliper	MIN
	FPC damage/crease		Damage and breaking, not allowed Crease does not affect the electrical performance display, allowed	Check by eyes	MIN



Inspection item		Figure	Inspection standard	Inspection method	MAJ/ MIN
Protective film defect	Protective film	Scratch and crease on the surface but no affect to protection function, allowed		Check by eyes	MIN
		Adhesive at edge $L \leq 5\text{mm}$, $W \leq 0.5\text{mm}$, $N=2$, no entering into viewing area		Check by eyes	MIN
Stain defect	Stain	If stain can be normally wiped clean by $> 99\%$ alcohol, allowed		Visual	MIN
Pull tab defect	Pull tab	The position and direction meet the document requirements, and ensure that the protective film can be pulled off.		Check by eyes/ Manual pulling	MIN
Shading tape defect	Shading tape	Tilt $\leq 10^\circ$, flat without warping, completely covering the IC.		Check by eyes/ Film gauge	MIN
Stiffener	Stiffener	Flat without warping, Exceeding the left and right edges of the FPC is not allowed. Left and right can be less than 0.5mm from FPC edge		Check by eyes	MIN
Label	Label/ Spraying code	The content meets the requirements of the work sheet. The attaching position meets the requirements of the technical documents.		Check by eyes	MIN



15. Precautions

- (1) Do not apply pressure to the EPD panel in order to prevent damaging it.
- (2) Do not connect or disconnect the interface connector while the EPD panel is in operation.
- (3) Do not touch IC bonding area. It may scratch TFT lead or damage IC function.
- (4) Please be mindful of moisture to avoid its penetration into the EPD panel, which may cause damage during operation.
- (5) If the EPD Panel / Module is not refreshed every 24 hours, a phenomena known as "Ghosting" or "Image Sticking" may occur. It is recommended to refreshed the ESL / EPD Tag every 24 hours in use case. It is recommended that customer ships or stores the ESL / EPD Tag with a completely white image to avoid this issue
- (6) High temperature, high humidity, sunlight or fluorescent light may degrade the EPD panel's performance. Please do not expose the unprotected EPD panel to high temperature, high humidity, sunlight, or fluorescent for long periods of time.

