

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support

Obsolescence Management

PCAP

Embedded Systems

Human Machine Interface

Touch Solutions

Software

Quality Management

Open Frame Monitors

LCD Controller

Research & Development

Firmware

EMC tests

on-site service

Optical Bonding

In-house Manufacturing

Cover glass

System solutions

OEM Solutions

Custom Display

Production Custom designs Installation

Mechanical design



Customer			
Keywords	M series, medical grade, 3.4 inch, 800*800, with configuration LUA scripts, audio, video, RTC, circular UI		
Model	ET034M8080-DC		
Signature of Customer		Signature of Engineer	
Date		Date	



1. Hardware Introduction

This section mainly introduces some appearance reference diagrams, hardware configuration diagrams and tools required for debugging of the product.

1.1 Product appearance

The following is a reference drawing of the appearance of different models of this size, as shown in Figure 1-1.

Note: There is no modification of key structural processes or major adjustments in layout, only changes and iterations in product processes or reliability, and the company will not initiate external changes, and the specific physical objects received shall prevail.




Figure1-1 4.0-inch capacitive touch reference diagram

1.2 Hardware Introduction

The following is a reference diagram of the hardware configuration of a product of this size, taking capacitive touch as an example, as shown in Figure 1-2.




Figure 1-2 Hardware configuration diagram



1.3 Debugging tool

The following is a reference diagram of the debugging tool of the product, as shown in Figure 1-3.




Figure 1-3 RS232 debugging tool diagram

◆ Development and debugging accessories (optional)	
Name	Accessory Model
Power supply	Power adapter, 5V 2A DC5.5*2.1mm Tite
Debugging the interposer	DC10P_FPC
Serial cable	Serial cable, USB to RS232 serial cable, industrial grade 9-pin serial converter, USB to serial cable, com port, male, Dieter
SD card (with card reader)	Kingston 8G



2. Product Specifications

◆ Product Parameters	
Model description	ET034M8080-DC (RS232/TTL, Capacitive touch)
Product Series	M series, medical grade
Core processor	400M SOC processor
Operating system	No operating system, power on and running
Protocol type	The default large color configuration instruction set, the host computer can be configured to run MODBUS RTU, XGUS protocol
Scripting language	Version 5.3 LUA script, the screen can run the logic, protocol and algorithm functions written by the user
Size	3.4 inch
Resolution	800*800
Installation orientation	It supports 0° , 90° , 180° and 270° rotation mounted displays
Storage space	128Mbit
Font	Built-in vector font, edge anti-aliasing, support any size ASCII, GBK, GB2312, UNICODE (global language) font library, can also customize any computer font display
Image Storage	It supports JPEG and PNG (transflective/fully transparent) compression, and supports image storage of any size. Totally, about 70 full-screen images can be stored (calculated based on the size of 150KB/piece, BMP format is not recommended). Depending on the image compression ratio, this value will fluctuate up and down
Color	65K color, 16-bit RGB
Voltage	4.5-30V
Power Consumption	Darkest backlight, No horns: 0.6W
	Darkest backlight, With horns: 1.5W
	Brightest backlight, No horns: 1.3W
	Brightest backlight, With horns: 2.2W
Communication Method	RS232/TTL(The factory default level is 232, and the short-circuit J5 is TTL level)
Communicate Baud-rate	1200~921600bps, typical baud rate: 115200bps
Communication Connector Specifications	FPC1.0-10P
USB flash drive interface	PH2.0-4P vertical type
Image Local Download	SD card, U flash drive
Firmware Local/Remote Upgrade	Insert SD card to upgrade locally / support remote serial port of user motherboard to upgrade screen firmware
Picture Remote Upgrade	Support users to remotely use their motherboard serial port to upgrade screen-related picture projects, font libraries, configuration files, etc.



Real-time clock (RTC)	Support clock, timer, countdown and other functions
Screen active display area (AA)	Length * width = 87.4mm*87.4mm
Product Size (L*W*H)	111.6mm*111.6mm*11.7mm
Supporting Host Computer Software	VisualTFT®
Audio playback	MP3 audio format (speaker 4 Ω 2W, mono), which shares storage space with pictures. If the sample rate of mp3 format is 128kbps, the storage will be 0.92MB/min
Audio connector specifications	PH2.0-2P
Video playback	MP4 video format, which shares storage space with images. If a video file with a resolution of 800 * 600, a video bitrate of 3000 Kbps, an audio bitrate of 166 Kbps, and a frame rate of 25 Hz, the storage space occupies 21.9 MB/min
Conformal coating process	None (optional)

◆ Reliability Parameters

Operating Temperature	-20~+70°C
Storage Temperature	-30~+80°C
ESD Test	IEC 61000-4-2 Air: ±10KV(No restart)
EFT Test	IEC 61000-4-4 GB 2 (Voltage: ±1KV; FREQUENCY: 100/5KHZ; TIME: 120S), no restart, no abnormal display, no abnormal touch, etc., the test function is normal
Radiation Test	EN55022 ClassB

◆ Product Core Competitiveness

Learning Cycle	30 minutes to familiarize yourself with the development environment, 3 days to complete the HMI design
Program Debugging	The host computer integrates a "TFT Simulate", which does not need to be connected to the hardware, and Keil IDE is directly bound to it for debugging
Startup Time	Run at power-on, no system load time
Configure Controls	It has a variety of configuration controls such as multi-language, button, text, drop-down menu, progress bar, slider, meter, animation, QR code, curve, historical curve, data record, circular progress bar, sprite slide control and so on
System Keyboard	Built-in virtual number, character keyboard, support Chinese and English input methods, customize keyboard
Data Logging	Supports exporting data logging control content to SD card
Layer Technology	The system has multiple built-in display layers for faster switching
Multi-Language Capabilities	Factory preset up to 15 languages of any country in the world, one-click switch of the required language, without the need for multiple sets of UI
Logical Operation Processing	The LUA script compiler is embedded in the host computer, and users can customize various complex logic relationships and protocols on the screen, meeting 99.9% of the product function requirements of customers



Remote Upgrade	Support remote serial port to upgrade screen firmware, project files, specified pictures, configuration files and font libraries
Life Cycle	It uses traditional YOURITECH processors and has been in continuous supply for many years

◆ LCD	
Display Type	IPS LCD
Backlight Tube	LED
Brightness (cd/m ²)	300
Backlight Life (h)	>20,000
Contrast Ratio	1200:1
Visual Angle (L/R/T/B)	85/85/85/85

◆ Touch Panel	
Touch Type	Capacitive touch screen
Capacitive Screen Touch Mode	Point, swipe touch
Capacitive Screen Light Transmittance	More than 90%
Capacitive Screen Touch Times	The number of capacitive screen touches is theoretically infinite, and the touch life is related to the working environment (dust, humidity)
Capacitor Cover Plate Customization	The "glass cover plate + capacitive touch" integrated lamination service can be customized according to the size of the user's drawing


◆ Customized Services	
Custom Fee	Sign a 1000PCS contract at one time, and some can be exempted from customization fees
Hardware Circuitry	Customizable PCB size, circuit thickness, add user circuit, military-grade temperature display, etc.
Software Customization	Customize special instructions or controls according to user needs to reduce user development difficulty
Art Services	Can provide picture art and product structure design services
Other	Customized on demand to meet all user needs



3. Installation Diagram

The following is the installation diagram of the product, the picture is for reference only, and the specific product shall prevail.

产品安装示意图
(PRODUCT INSTALLATION DIAGRAM)




第一步：机壳开一个洞，产品从正面放进去

(THE FIRST STEP: A HOLE IS OPENED IN THE CASE, AND THE PRODUCT IS PUT IN FROM THE FRONT)



第二步：撕开背胶

(STEP 2: TEAR OFF THE ADHESIVE)



第三步：将串口屏嵌入到客户机柜 通过3M背胶固定

(STEP 3: EMBED THE SERIAL SCREEN INTO THE CLIENT CABINET AND FIX IT WITH 3M ADHESIVE)




第四步：安装完成

(STEP 4: THE INSTALLATION IS COMPLETE.)



4. Product Size



5. Pin Definition

Number	Definition	Description	Reference Diagram
1、2、3	VCC	Power input 4.5-30V	
4	NC	Empty feet	
5	DIN	Serial port screen input, connected to the user's TXD terminal	
6	DOUT	Serial port screen output, connected to the user's RXD terminal	
7	NC	Empty feet	
8、9、10	GND	Power Ground	



6. Reliability Test

All serial port screens of YOURITECH Technology have carried out a series of process reliability tests before mass production: high and low temperature, ESD, pulse burst, radiation, touch life and other tests to ensure product quality, as shown in Figure 6-1.




Figure 6-1 Reliability Test Equipment

6.1 ESD Test

6.1.1 Execution Standards

Execution Standards

IEC 61000-4-2

6.1.2 Environment Test

Test ambient temperature: Around 25° C (indoor)

Test ambient humidity: 30-50% (indoor)

Test process: The product is placed flat on the test bench, and the air discharge is carried out on the front of the shell and the display area, as shown in Figure 6-2, and the screen is observed to see whether there are phenomena such as reset and restart, abnormal display, etc.





Figure 6-2 ESD test diagram

6.1.3 Test data

Product Model	Discharge type	Humidity	Test result
ET034M8080-DC	Air	±10KV	No restart, no abnormal display, normal function
	Air	±12KV	Occasional reset and restart, no abnormal display, normal function

Note: The current test test is the product exposure test, the actual product assembly machine, keep the screen and the machine well grounded, or the surface of the touchpad is protected by PVC or cover; the ESD performance index of the whole machine will be higher.

6.2 High and Low Temperature Aging Test

6.2.1 Test the environment

Test ambient temperature: -20~+70°C

Test ambient humidity: 60%±3%RH

Test process: Place the product in the high and low temperature test box at an angle as shown in Figure 6-3. Pass the 72H high temperature, low temperature and high and low temperature alternating change aging test. Observe whether the screen resets and restarts during the test and after the test. Abnormalities, abnormal functions, etc.





Figure 6-3 High and low temperature aging test diagram

6.2.2 Test data

Product Model	Temperature	Humidity	Test results
ET034M8080-DC	High temperature (70°C)	65%	No reboot, no abnormal display, normal function
	Low temperature (-20°C)	65%	No reboot, no abnormal display, normal function
	Alternating high and low temperature (-20~70°C)	65%	No reboot, no abnormal display, normal function

6.3 Group Pulse Test

6.3.1 Execution standards

Executive Standard	IEC 61000-4-4
--------------------	---------------

6.3.2 Test environment

Test ambient temperature: 25°C

Test ambient humidity: 50%

Test process: Place the product on the test stand, and power the screen through the power supply after the pulse group generator is coupled to the pulse group, as shown in Figure 6-4. During the test, observe whether the screen resets, displays abnormally, or touches, abnormalities and other phenomena.





Figure 6-4 Group pulse test diagram

6.3.3 Test Data

Product Model	Test Standard			Test Result
ET034M8080-DC	National standard 4			No restart, normal communication, normal function
	Voltage (KV)	Voltage (KV)	Frequency (KHZ)	
	±4.0	5	120	



7. RS232 and TTL Level Translation

Most products support RS232 and TTL level translation. As shown in Figure 8-1, when J5 is disconnected, the serial port is RS232 level; When J5 is shorted, the serial port is TTL level.

Note: TTL levels support 3.3VCMOS and 5VTTL.




Figure 8-1 Schematic diagram of RS232 and TTL conversion



8. Protocol Configuration

Most of the serial port screens launched by ShenZhen YOURITECH Technology Co., Ltd. (www.youritech.com). default to the YOURIECH configuration instruction set, and users can run MODBUS RTU, XGUS and other protocols through the host computer configuration.

Open the VisualTFT host computer software, click [Tools] in the menu bar → [Protocol and Variable Settings], as shown in Figure 9-1, enter the protocol configuration interface, and users can choose to enable the corresponding protocol according to their needs, as shown in Figure 9-2.




Figure 8-1 Protocol and variable setting




Figure 8-2 Protocol configuration interface



9. LUA Script Configuration

The serial port screens of S-type, M-type and IoT series launched by ShenZhen YOURITECH Technology Co., Ltd. (www.youritech.com). all support LUA language scripts. The serial port screen provides a wealth of LUA script API and callback interface, users can directly set and obtain the running status of all configuration controls by calling the API interface, combined with the written logic processing, the screen can complete the predetermined action without the participation of the external MCU, reducing the data communication between the MCU and the screen.

LUA is a lightweight scripting language with simpler syntax logic than C, and developers can get started directly. The LUA language comes with a well-functioning mathematical function library, string processing, JSON and other libraries, and has function support for common mathematical operations, such as square, sine cosine, and absolute value; Due to the high main frequency of the screen itself, all complex algorithms are processed by the screen, which greatly reduces the execution overhead of the user's MCU.

To write the LUA script of the project in the VisualTFT software, you can click [Tools] → [LUA Script Programming] in the menu bar to open it, as shown in Figure 10-1, and enter the LUA scripting interface, as shown in Figure 10-2.






Figure 9-1 LUA script programming





10. Packaging and Physical Dimensions

Unit weight					
Net weight (KG)	0.09				
Packaging standard and total weight					
Box model	Box size (length * width * height, unit mm)	Number of layers	Quantity (PCS)/layer	Total quantity (pieces)	Total weight (KG)
Box 1	616*523*275	1	50	50	6.25

Note: The total weight does not include the weight of the accessory; The above weight information is an estimated weight for reference only, and the actual weight is subject to the actual weight.



11. Product Architecture

The industrial serial port screen launched by ShenZhen YOURITECH Technology Co., Ltd. (www.youritech.com) is a serial display terminal integrating TFT display driver, picture font storage, GUI operation, audio playback and various configuration controls. The user microcomputer only needs to send and receive the corresponding serial port instructions to easily realize the display of text, pictures and curves.

M series serial screen processor adopts 32-bit 400M SOC processor, which integrates SDR memory and JPEG picture decoding and other functions, and the system architecture is shown in Figure 12-1.




Figure 12-1 M series serial port screen internal structure diagram

The main advantages of choosing a high-performance 32-bit dual-core processor architecture are:

1. A dedicated 32-bit 400M SOC processor optimized for picture display, with a 2D acceleration engine and JPEG picture hardware decoding, so that the display can be combined with various special effects, and the display effect is smooth and gorgeous.
2. No operating system, continuous 24*365h hours of uninterrupted power can work reliably, no garbage redundant files.



12. Develop Software

VisualTFT is a serial port screen development and debugging software independently developed by YOURITECH, integrating the first "Virtual TFT Simulator" simulator in China, which is free for life. After the user creates a new project, import the designed art pictures, and then configure the buttons and other controls in each screen, simulate correctly, and finally download the entire project to the serial port screen. The software interface is shown in Figure 12-1.




Figure 12-1 Main interface of VisualTFT

Any user only needs 3 steps to complete complex HMI design within 30 minutes.

1. Prepare art assets

Arrange for artists to design the pictures required for the product, such as the boot screen, text background, button icon, and prompt box.

2. Use the supporting VisualTFT software for screen editing, scripting, control configuration and image download.

First, using the supporting host computer VisualTFT software, the pre-designed art pictures are arranged and configured for interface, and then the "virtual serial port screen" is run for simulation, and finally the entire project can be downloaded to the internal memory of the serial port screen through SD/UART (depending on the hardware configuration of different models). PC software assigns a unique ID number to each screen, picture, and control in the project. Users can also write the required logic control and algorithms through the script editor embedded in the host computer to reduce the communication frequency between the screen and the motherboard.

3. The user's single-chip microcomputer monitors and sends the corresponding serial port command control screen display.

After the project is downloaded to the screen, once a button is pressed on the screen, the user's MCU serial port will receive the button ID information or coordinate value uploaded on the screen. By parsing the ID number, the user can obtain the screen position and functional attributes of the current button, so that the relevant peripheral device actions or screen update display can be controlled.

For non-touch products, the user micro-controller does not need to listen to the information uploaded by the button ID, but only needs to send relevant instructions for screen switching and



text picture display.

12.1 What is Virtual TFT Simulation

"Virtual TFT simulation" is the first domestic exclusive serial port screen emulator developed by ShenZhen YOURITECH Technology Co., Ltd. (www.youritech.com). After the user installs the VisualTFT software of the host computer, it can be run and used. The simulation results of the virtual serial port screen are exactly the same as the real serial port screen. Therefore, there is no need to purchase hardware during the pre-development evaluation, and it can communicate with each other through its own single-chip RS232 serial port, and click on the button will immediately upload the button control information, as shown in Figure 13-2. Once the developer has debugged it, the real hardware does not need to be debugged.



Figure 13-2 Online debugging of the serial port of the user single-chip microcomputer and the "virtual TFT simulation"

12.2 Keil is bound to debug with the virtual TFT simulation

In order to further improve the development efficiency, users can also bind Debug debugging with the "virtual TFT simulation" through the Keil development environment. When the program is single-step debugging, all running results can be presented on the "virtual TFT simulation", which greatly saves the engineer's development time, as shown in Figure 13-3. Once the project interface is changed, users no longer need to re-download pictures to the serial port screen, and all pre-project evaluations can be completed based on the PC.




Figure 12-3 The Keil development environment is bound to the virtual TFT simulation for debugging

