

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support
Obsolescence Management
Embedded Systems
Human Machine Interface
Touch Solutions
Software
Quality Management
Open Frame Monitors
Research & Development
EMC tests
on-site service
In-house Manufacturing
Cover glass
OEM Solutions
Custom Display

PCAP

Mechanical design

Production
Custom designs
Installation

System solutions



SPECIFICATION FOR LCM+CTP Module

MODULE No:	ET040WX22-KT
CUSTOMER:	

YOURITECH	INITIAL	DATE
PREPARED BY		
CHECKED BY		
APPROVED BY		

CUSTOMER	INITIAL	DATE
APPROVED BY		



Contents

1. Basic Specifications	5
1.1 TFT Features	5
1.2 CTP Features	5
1.3 Mechanical Information	6
2. Block Diagram	6
3. Outline dimension	7
4. Input terminal Pin Assignment	8
4.1 TFT PIN Define	8
4.2 CTP PIN Define	9
5. LCD Optical Characteristics	10
5.1 Optical specification	10
6. Electrical Characteristics	13
6.1 Absolute Maximum Rating	13
6.2 DC Electrical Characteristics	13
6.3 LED Backlight Characteristics	14
7. LVDS Signal Timing Characteristics	16
7.1 AC Electrical Characteristics	16
7.2 Timing Table	17
7.3 LVDS Data Input Format	18
8. CTP Specification	19
8.1 Electrical Characteristics	19
8.1.1 Absolute Maximum Rating	19
8.1.2 DC Electrical Characteristics (Ta=25℃)	19
8.1.3 AC Characteristics	20
8.2 I2C Timing	20
9. LCD Module Out-Going Quality Level	25
9.1 VISUAL & FUNCTION INSPECTION STANDARD	25
9.1.1 Inspection conditions	25
9.1.2 Definition	25
9.1.3 Sampling Plan	26
9.1.4 Criteria (Visual)	27
10. Reliability Test Result	33
11. Cautions and Handling Precautions	34
11.1 Handling and Operating the Module	34



11.2 Storage and Transportation..... 34



1.Basic Specifications

* Description

This is a color active matrix TFT (Thin Film Transistor) LCD (liquid crystal display) that uses amorphous silicon TFT as a switching device. This module is composed of a Transmissive type TFT-LCD Panel, driver circuit, capacitance touch panel, back-light unit. The resolution of a 3.95 " TFT-LCD contains 480x480 pixels, and can display up to 16.7M colors.

1.1 TFT Features

General Information Items	Specification	Unit	Note
	Main Panel		
Display area(AA)	71.86(H)*70.18(V) (3.95 inch)	mm	
Driver element	TFT active matrix	-	
Display colors	16.7M	colors	
Number of pixels	480(RGB)*480	dots	
Pixel arrangement	RGB vertical stripe	-	
Pixel pitch	0.1497(H)*0.1462(V)	mm	
Viewing angle	ALL	o'clock	
Controller IC	ST7701S	-	
LCM Interface	8BIT LVDS	-	
Display mode	Transmissive /Normally Black	-	
Operating temperature	-30~+85	°C	
Storage temperature	-40~+90	°C	
Module bonding technology	Use optical bonding between LCM and CTP	-	

1.2 CTP Features

General Information Items	Specification	Unit	Note
	Main Panel		
Resolution	480(H)*480(V)	-	
Structure	G+G	-	
Controller IC	GT911	-	
Interface	I2C	-	
Slave Address	0x5D(7bit) or 0x14(7bit)	-	
Touch mode	Five points and Gestures	-	-
Logic level	3.3	V	


Note1: For specific configuration method, please refer to section 8.2




1.3 Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal(H)	-	77	-	mm	
	Vertical(V)	-	80	-	mm	
	Depth(D)	-	4.51	-	mm	
Weight		-	59	-	g	

2. Block Diagram



3. Outline dimension



4. Input terminal Pin Assignment

4.1 TFT PIN Define

NO.	SYMBOL	DISCRIPTION	I/O
1	NC	No connected	--
2	VDD	Power supply for digital circuits	P
3	VDD		P
4	NC	No connected	--
5	NC	No connected	--
6	STBYB	Power ON/OFF PIN, Normally pulled high STBYB = "1", Power ON. STBYB = "0", Power OFF.	I
7	GND	Ground	P
8	RXIN0-	- LVDS differential data input	I/O
9	RXIN0+	+ LVDS differential data input	I/O
10	GND	Ground	P
11	RXIN1-	- LVDS differential data input	I/O
12	RXIN1+	+ LVDS differential data input	I/O
13	GND	Ground	P
14	RXIN2-	- LVDS differential data input	I/O
15	RXIN2+	+ LVDS differential data input	I/O
16	GND	Ground	P
17	RXCLKIN-	- LVDS differential clock input	I/O
18	RXCLKIN+	+ LVDS differential clock input	I/O
19	GND	Ground	P
20	RXIN3-	- LVDS differential data input	I/O
21	RXIN3+	+ LVDS differential data input	I/O
22	GND	Ground	P
23	NC	No connected	--
24	NC	No connected	--
25	GND	Ground	P
26	NC	No connected	--
27	NC	No connected	--
28	NC	No connected	--
29	NC	No connected	--



30	GND	Ground	P
31	LED-	LED Cathode	P
32	LED-	LED Cathode	P
33	NC	No connected	--
34	NC	No connected	--
35	NC	No connected	--
36	NC	No connected	--
37	NC	No connected	--
38	NC	No connected	--
39	LED+	LED anode	P
40	LED+	LED anode	P

4.2 CTP PIN Define

NO.	SYMBOL	DISCRIPTION	I/O
1	GND	Ground	P
2	NC	No Connection	
3	VDD	Supply voltage	P
4	SCL	I2C clock input	I
5	SDA	I2C data input and output	I
6	INT	External interrupt to the host	I
7	RST	External Reset, Low is active	I
8	GND	Ground	P



5. LCD Optical Characteristics

5.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit.	Note
Contrast Ratio		CR	$\Theta=0$ Normal viewing angle	800	1000	--		(1)(2)
Response time	Rising	T_R+T_F		--	25	35	msec	(1)(3)
	Falling							
Color Gamut		S(%)		50	55	--	%	
Color Filter Chromaticity	White	W_X		-0.04	0.303	+0.04		(1)(4) CA- 310
		W_Y			0.337			
	Red	R_X			0.614			
		R_Y			0.362			
	Green	G_X			0.314			
		G_Y			0.564			
	Blue	B_X			0.148			
		B_Y			0.098			
Viewing angle	Hor.	Θ_L	CR>10	70	80	--	(1)(4)	
		Θ_R		70	80	--		
	Ver.	Θ_U		70	80	--		
		Θ_D		70	80	--		
Option View Direction		ALL						(5)

*The data comes from the LCD specification.

Measuring Condition

Measuring surrounding : dark room

Ambient temperature : $25\pm 2^\circ\text{C}$


15min. warm-up time.

Measuring Equipment

FPM520 , which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.




Note (1): Definition of Viewing Angle :




Note (2): Definition of Contrast Ratio(CR) :measured at the center point of panel

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Note (3): Response Time



Note (4): Definition of optical measurement setup



6. Electrical Characteristics

6.1 Absolute Maximum Rating

Characteristics	Symbol	Min.	Max.	Unit	Note
Digital Supply Voltage	VDD	-0.3	4.6	V	Note1
Operating temperature	T _{OP}	-30	+85	°C	
Storage temperature	T _{ST}	-40	+90	°C	

NOTE1: If the absolute maximum rating of even is one of the above parameters is exceeded even momentarily, the quality of the product may be degraded. Absolute maximum ratings, therefore, specify the values exceeding which the product may be physically damaged. Be sure to use the product within the range of the absolute maximum ratings.

6.2 DC Electrical Characteristics

Characteristics		Symbol	Min.	Typ.	Max.	Unit	Note
Digital Supply Voltage		VDD	2.5	3.3	3.6	V	
Normal mode Current		IDD	--	58	116	mA	
LVDS Interface	Differential Input High Threshold Voltage	VLVTH	--	--	100	mV	
	Differential Input Low Threshold Voltage	VLVTL	-100	--	--	mV	
RGB Interface		V _{IH}	0.7*VDD	--	VDD	V	
Level input voltage		V _{IL}	GND	--	0.3* VDD	V	



6.3 LED Backlight Characteristics

The back-light system is edge-lighting type with 12 chips LED


Item	Symbol	Min.	Typ.	Max.	Unit	Note
Forward Current	I_F	--	40	--	mA	
Forward Voltage	V_F	16.8	--	20.4	V	
LCM Luminance ($I_F = 40\text{mA}$)	LV	800	900	--	cd/m ²	Note3
LED life time	Hr	50000	--	--	Hour	Note1,2
Uniformity	Avg	80	--	--	%	Note3

Note1: LED life time (Hr) can be defined as the time in which it continues to operate under the condition:


$T_a = 25 \pm 3^\circ\text{C}$, typical IL value indicated in the above table until the brightness becomes less than 50%.

Note 2: The “LED life time” is defined as the module brightness decrease to 50% original brightness at

$T_a = 25^\circ\text{C}$ and $I_L = 40\text{mA}$. The LED lifetime could be decreased if operating I_L is larger than 40mA. The constant current driving method is suggested.



Note (3) Luminance Uniformity of these 9 points is defined as below:



$$\text{Uniformity} = \frac{\text{minimum luminance in 9 points (1-9)}}{\text{maximum luminance in 9 points (1-9)}}$$


$$\text{Luminance} = \frac{\text{Total Luminance of 9 points}}{9}$$




7. LVDS Signal Timing Characteristics

7.1 AC Electrical Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit	Note
LVDS Differential input high Threshold voltage	RxVTH	--	--	+100	mV	RXVCM=1.2V
LVDS Differential input low Threshold voltage	RxVTL	-100	--	--	mV	
LVDS Differential input common mode voltage	RxVCM	0.7	--	1.6	V	
LVDDS Differential voltage	V _{ID}	200	--	600	mV	



7.2 Timing Table




Parameter	Symbol	Min.	Typ.	Max.	Unit
DCLK frequency	FCLK	--	(17)	--	MHz
Horizontal display area	HDISP	--	480	--	Clock
Horizontal Sync. Width	hpw	1	2	--	Clock
Horizontal Sync. Back Porch	hbp	1	40	-	Clock
Horizontal Sync. Front Porch	hfp	1	10	--	Clock
Vertical display area	VDISP	--	480	--	Line
Vertical Sync. Width	vs	1	2	--	Line
Vertical Sync. Back Porch	vbp	1	40	--	Line
Vertical Sync. Front Porch	vfp	1	10	--	Line
Frame-Rate		--	60	--	Hz

Note: 1. Typical value are related to the setting frame rate is 60Hz.



7.3 LVDS Data Input Format



8. CTP Specification

8.1 Electrical Characteristics

8.1.1 Absolute Maximum Rating

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	VDD	2.66	3.47	V	
Operating temperature	T _{OP}	-20	+70	°C	
Storage temperature	T _{ST}	-30	+80	°C	

8.1.2 DC Electrical Characteristics (Ta=25°C)

(Ambient temperature:25°C, VDD=2.8V, VDDIO=1.8V or VDDIO=VDD)

Item	Min.	Typ.	Max.	Unit	Note
Power Supply Voltage/VDD	2.66	3.3	3.47	V	
Normal mode operating current	--	8	14.5	mA	
Green mode operating current	--	3.3	--	mA	
Sleep mode operating current	70	--	120	uA	
Doze mode operating current	--	0.78	--	mA	
Digital Input low voltage/VIL	-0.3	--	0.25*VDD	V	
Digital Input high voltage/VIH	0.75*VDD	--	VDD+0.3	V	
Digital Output low voltage/VOL	--	--	0.15*VDD	V	
Digital Output high voltage/VOH	0.85*VDD	--	--	V	




8.1.3 AC Characteristics

(Ambient temperature:25℃, VDD=2.8V, VDDIO=1.8V)

Parameter	Min	Typ	Max	Unit	Note
OSC oscillation frequency	59	60	61	MHZ	
I/O output rise time,low to high	-	14	-	ns	
I/O output rfall time,high to low	-	14	-	ns	

8.2 I2C Timing

GT911 provides a standard I2C interface for SCL and SDA to communicate with the host. GT911 always serves as slave device in the system with all communication being initialized by the host. It is strongly recommended that transmission rate be kept at or below 400Kbps. The I2C timing is shown below:



Test condition 1: 1.8V host interface voltage, 400Kbps transmission rate, 2K pull-up resistor


Parameter	Symbol	Min.	Max.	Unit
SCL low period	t_{lo}	1.3	-	us
SCL high period	t_{hi}	0.6	-	us
SCL setup time for Start condition	t_{st1}	0.6	-	us
SCL setup time for Stop condition	t_{st3}	0.6	-	us
SCL hold time for Start condition	t_{hd1}	0.6	-	us
SDA setup time	t_{st2}	0.1	-	us
SDA hold time	t_{hd2}	0	-	us

Test condition 2: 3.3V host interface voltage, 400Kbps transmission rate, 2K pull-up resistor


Parameter	Symbol	Min.	Max.	Unit
SCL low period	t_{lo}	1.3	-	us
SCL high period	t_{hi}	0.6	-	us
SCL setup time for Start condition	t_{st1}	0.6	-	us
SCL setup time for Stop condition	t_{st3}	0.6	-	us
SCL hold time for Start condition	t_{hd1}	0.6	-	us
SDA setup time	t_{st2}	0.1	-	us
SDA hold time	t_{hd2}	0	-	us

GT911 supports two I2C slave addresses: 0xBA/0xBB and 0x28/0x29. The host can select the address by changing the status of Reset and INT pins during the power-on initialization phase. See the diagram below for configuration methods and timings:


Power-on Timing:




Timing for host resetting GT911:



Timing for setting slave address to 0x28/0x29:



Timing for setting slave address to 0xBA/0xBB:



a) Data Transmission

(For example: device address is 0xBA/0xBB)

Communication is always initiated by the host. Valid Start condition is signaled by pulling SDA line from “high” to “low” when SCL line is “high”. Data flow or address is transmitted after the Start condition.

All slave devices connected to I²C bus should detect the 8-bit address issued after Start condition and send the correct ACK. After receiving matching address, GT911 acknowledges by configuring SDA line as output port and pulling SDA line low during the ninth SCL cycle. When receiving unmatched address, namely, not 0xBA or 0xBB, GT911 will stay in an idle state.

For data bytes on SDA, each of 9 serial bits will be sent on nine SCL cycles. Each data byte consists of 8 valid data bits and one ACK or NACK bit sent by the recipient. The data transmission is valid when SCL line is “high”.

When communication is completed, the host will issue the STOP condition. Stop condition implies the transition of SDA line from “low” to “high” when SCL line is “high”.

b) Writing Data to GT911

(For example: device address is 0xBA/0xBB)



Timing for Write Operation

The diagram above displays the timing sequence of the host writing data onto GT911. First, the host issues a Start condition. Then, the host sends 0xBA (address bits and R/W bit; R/W bit as 0 indicates Write operation) to the slave device.


After receiving ACK, the host sends the 16-bit register address (where writing starts) and the 8-bit data bytes (to be written onto the register).

The location of the register address pointer will automatically add 1 after every Write Operation. Therefore, when the host needs to perform Write Operations on a group of registers of continuous addresses, it is able to write continuously. The Write Operation is terminated when the host issues the Stop condition.



c) Reading Data from GT911

(For example: device address is 0xBA/0xBB)



Timing for Read Operation

The diagram above is the timing sequence of the host reading data from GT911. First, the host issues a Start condition and sends 0xBA (address bits and R/W bit; R/W bit as 0 indicates Write operation) to the slave device.

After receiving ACK, the host sends the 16-bit register address (where reading starts) to the slave device. Then the host sets register addresses which need to be read.

Also after receiving ACK, the host issues the Start condition once again and sends 0xBB (Read Operation). After receiving ACK, the host starts to read data.

GT911 also supports continuous Read Operation and, by default, reads data continuously. Whenever receiving a byte of data, the host sends an ACK signal indicating successful reception. After receiving the last byte of data, the host sends a NACK signal followed by a STOP condition which terminates communication.



9. LCD Module Out-Going Quality Level

9.1 VISUAL & FUNCTION INSPECTION STANDARD

9.1.1 Inspection conditions

Inspection performed under the following conditions is recommended.


Temperature : $25\pm 5^{\circ}\text{C}$

Humidity : $65\%\pm 10\%\text{RH}$


Viewing Angle : Normal viewing Angle.

Illumination: Single fluorescent lamp (300 to 700Lux)

Viewing distance:30-50cm



9.1.2 Definition



Zone A : Effective Viewing Area(Character or Digit can be seen)

Zone B : Viewing Area except Zone A

Zone C : Outside (Zone A+Zone B) which can not be seen after assembly by customer

Zone D : IC Bonding Area

Note:As a general rule ,visual defects in Zone C can be ignored when it doesn't effect product function or appearance after assembly by customer



9.1.3 Sampling Plan

According to GB/T 2828-2003 ; , normal inspection, Class II

AQL:

Major defect	Minor defect
0.65	1.5

LCD: Liquid Crystal Display , LCM: Liquid Crystal Module, CTP: Capacitive Touch Panel




No	Items to be inspected	Criteria	Classification of defects
1	Functional defects	1) No display, Open or miss line 2) Display abnormally, Short 3) Backlight no lighting, abnormal lighting. etc	Major
2	Missing	Missing components and etc	
3	Outline dimension	Overall outline dimension beyond the drawing is not allowed, deformation and etc	
4	Color tone	Color unevenness, refer to limited sample	Minor
5	Spot/Line defect	Light dot, Dim spot, (Note1) Polarizer Air Bubble, Polarizer accidented spot and etc.	
6	Soldering appearance	Good soldering , Peeling off is not allowed and etc.	
7	LCD/Polarizer/CTP	Black/White spot/line, scratch, crack, etc.	

Note1: a) Light dot: Dots appear bright and unchanged in size in which LCD panel is displaying under black pattern.

b) Dim dot: Dots appear dark and unchanged in size in which LCD panel is displaying under pure red, green, blue picture.



9.1.4 Criteria (Visual)

Number	Items	Criteria(mm)						
1.0 LCD Crack/Broken NOTE: X: Length Y: Width Z: Height L: Length of IT O, T: Height of LCD	(1) The edge of LCD broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td><Inner border line of the seal</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	<Inner border line of the seal	≤T
	X	Y	Z					
	≤3.0mm	<Inner border line of the seal	≤T					
(2)LCD corner broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td>≤L</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	≤L	≤T	
X	Y	Z						
≤3.0mm	≤L	≤T						
(3) LCD crack	 Crack Not allowed							



Spot defect

2.0

Y

X

Φ=(X+Y)/2

① light dot (black/white spot , pinhole, stain, etc.)

Zone Size (mm)	Acceptable Qty		
	A	B	C
Φ≤0.15	Ignore	Ignore	
0.15<Φ≤0.25	3(distance ≥ 10mm)		
0.25<Φ≤0.4	2(distance ≥ 10mm)		
Φ>0.4	0		

② Dim spot (light leakage、dent、dark spot, etc)

Zone Size (mm)	Acceptable Qty		
	A	B	C
Φ≤0.15	Ignore	Ignore	
0.15<Φ≤0.25	3(distance ≥ 10mm)		
0.25<Φ≤0.4	2(distance ≥ 10mm)		
Φ>0.4	0		



③ Polarizer accidented spot

Zone Size (mm)	Acceptable Qty		
	A	B	C
Φ≤0.2	Ignore		Ignore
0.2<Φ≤0.5	2(distance ≥ 10mm)		
Φ>0.5	0		


④Polarizer Bubble

Zone Size (mm)	Acceptable Qty		
	A	B	C
Φ≤0.2	Ignore		Ignore
0.2<Φ≤0.4	3(distance ≥ 10mm)		
Φ>0.4	0		




3.0	LCD Pixel defect	Pixel bad points																							
		<table> <tr> <th>Item</th><th>Zone A</th><th>Acceptable Qt</th></tr> <tr> <td rowspan="3">Bright dot</td><td>Random</td><td>$N \leq 2$</td></tr> <tr> <td>2 dots adjacent</td><td>$N \leq 0$</td></tr> <tr> <td>3 dots adjacent</td><td>$N \leq 0$</td></tr> <tr> <td rowspan="3">Dark dot</td><td>Random</td><td>$N \leq 2$</td></tr> <tr> <td>2 dots adjacent</td><td>$N \leq 0$</td></tr> <tr> <td>3 dots adjacent</td><td>$N \leq 0$</td></tr> <tr> <td>Distance</td><td> 1. Minimum Distance Between Bright dots. 2. Minimum Distance Between dark dots 3. Minimum Distance Between dark and bright dot. </td><td>5mm</td></tr> <tr> <td colspan="2">Total bright and dark dot</td><td>$N \leq 4$</td></tr> </table> Note: A) Bright dot: Dots appear bright and unchanged in size in which LCD panel is displaying under black pattern. B) Dark dot: Dots appear dark and unchanged in size in which LCD panel is displaying under pure red, green, blue picture. C) 2 dot adjacent = 1 pair = 2 dots Picture:     2 dot adjacent 2 dot adjacent 2 dot adjacent (vertical) 2 dot adjacent (slant)	Item	Zone A	Acceptable Qt	Bright dot	Random	$N \leq 2$	2 dots adjacent	$N \leq 0$	3 dots adjacent	$N \leq 0$	Dark dot	Random	$N \leq 2$	2 dots adjacent	$N \leq 0$	3 dots adjacent	$N \leq 0$	Distance	1. Minimum Distance Between Bright dots. 2. Minimum Distance Between dark dots 3. Minimum Distance Between dark and bright dot.	5mm	Total bright and dark dot		$N \leq 4$
Item	Zone A	Acceptable Qt																							
Bright dot	Random	$N \leq 2$																							
	2 dots adjacent	$N \leq 0$																							
	3 dots adjacent	$N \leq 0$																							
Dark dot	Random	$N \leq 2$																							
	2 dots adjacent	$N \leq 0$																							
	3 dots adjacent	$N \leq 0$																							
Distance	1. Minimum Distance Between Bright dots. 2. Minimum Distance Between dark dots 3. Minimum Distance Between dark and bright dot.	5mm																							
Total bright and dark dot		$N \leq 4$																							



4.0	Line defect (LCD /Polarizer backlight black/white line, scratch, stain)  W: width, L: length N : Count	Width(mm)	Length(m)	Acceptable Qty		
				A	B	C
		$\Phi \leq 0.05$	Ignore	Ignore		Ignore
		$0.05 < W \leq 0.06$	$L \leq 4.0$	$N \leq 3$		
		$0.06 < W \leq 0.08$	$L \leq 3.0$	$N \leq 2$		
$W > 0.08$	Define as spot defect					
5.0	Electronic Components SMT.	Not allow missing parts, solderless connection, cold solder joint, mismatch, The positive and negative polarity opposite				
6.0	Display color& Brightness.	1. Color: Measuring the color coordinates, The measurement standard according to the datasheet or samples. 2. Brightness: Measuring the brightness of White screen, The measurement standard according to the datasheet or Samples.				
7.0	LCD Mura/Waving/ Hot spot	Not visible through 5% ND filter in 50% gray or judge by limit sample if necessary.				


8.0	CTP Related	CTP Cover sensor acc identified black/white spot	Size Φ (mm)	Acceptable Qty		
			A	B	C	
			$\Phi \leq 0.1$	Ignore		Ignore
			$0.1 < \Phi \leq 0.2$	3 (distance $\geq 10\text{mm}$)		
			$0.20 < \Phi \leq 0.25$	2 (distance $\geq 10\text{mm}$)		
			$\Phi > 0.25$	0		



		CTP Cover scratch	<table><tr><th rowspan="2">Width(mm)</th><th rowspan="2">Ignore (mm)</th><th colspan="3">Acceptable Qty</th></tr><tr><th>A</th><th>B</th><th>C</th></tr><tr><td>$\Phi \leq 0.05$</td><td>Ignore</td><td colspan="3">Ignore</td></tr><tr><td>$0.05 < W \leq 0.06$</td><td>$L \leq 4.0$</td><td colspan="3">$N \leq 3$</td></tr><tr><td>$0.06 < W \leq 0.08$</td><td>$L \leq 3.0$</td><td colspan="3">$N \leq 2$</td></tr><tr><td>$0.08 < W$</td><td colspan="4">Define as spot defect</td></tr></table>	Width(mm)	Ignore (mm)	Acceptable Qty			A	B	C	$\Phi \leq 0.05$	Ignore	Ignore			$0.05 < W \leq 0.06$	$L \leq 4.0$	$N \leq 3$			$0.06 < W \leq 0.08$	$L \leq 3.0$	$N \leq 2$			$0.08 < W$	Define as spot defect				
			Width(mm)			Ignore (mm)	Acceptable Qty																									
				A	B		C																									
			$\Phi \leq 0.05$	Ignore	Ignore																											
			$0.05 < W \leq 0.06$	$L \leq 4.0$	$N \leq 3$																											
		$0.06 < W \leq 0.08$	$L \leq 3.0$	$N \leq 2$																												
		$0.08 < W$	Define as spot defect																													
		CTP Cover Pinhole/ Lack of ink	<table><tr><th rowspan="2">Zone Size (mm)</th><th>Acceptable Qty</th></tr><tr><th>C</th></tr><tr><td>$\Phi \leq 0.1$</td><td>Ignore</td></tr><tr><td>$0.1 < \Phi \leq 0.25$</td><td>3(distance $\geq 10\text{mm}$)</td></tr><tr><td>$0.25 < \Phi \leq 0.3$</td><td>2(distance $\geq 10\text{mm}$)</td></tr><tr><td>$\Phi > 0.3$</td><td>0</td></tr></table>	Zone Size (mm)	Acceptable Qty	C	$\Phi \leq 0.1$	Ignore	$0.1 < \Phi \leq 0.25$	3(distance $\geq 10\text{mm}$)	$0.25 < \Phi \leq 0.3$	2(distance $\geq 10\text{mm}$)	$\Phi > 0.3$	0																		
			Zone Size (mm)		Acceptable Qty																											
				C																												
$\Phi \leq 0.1$	Ignore																															
$0.1 < \Phi \leq 0.25$	3(distance $\geq 10\text{mm}$)																															
$0.25 < \Phi \leq 0.3$	2(distance $\geq 10\text{mm}$)																															
$\Phi > 0.3$	0																															
CTP Bondi ng bubble/ accident ed spot	<table><tr><th rowspan="2">Size $\Phi(\text{mm})$</th><th colspan="2">Acceptable Qty</th></tr><tr><th>A</th><th>B</th></tr><tr><td>$\Phi \leq 0.1$</td><td colspan="2">Ignore</td></tr><tr><td>$0.1 < \Phi \leq 0.2$</td><td colspan="2">3(distance $\geq 10\text{mm}$)</td></tr><tr><td>$0.2 < \Phi \leq 0.25$</td><td colspan="2">2(distance $\geq 10\text{mm}$)</td></tr><tr><td>$\Phi > 0.25$</td><td colspan="2">0</td></tr></table>	Size $\Phi(\text{mm})$	Acceptable Qty		A	B	$\Phi \leq 0.1$	Ignore		$0.1 < \Phi \leq 0.2$	3(distance $\geq 10\text{mm}$)		$0.2 < \Phi \leq 0.25$	2(distance $\geq 10\text{mm}$)		$\Phi > 0.25$	0															
	Size $\Phi(\text{mm})$		Acceptable Qty																													
		A	B																													
	$\Phi \leq 0.1$	Ignore																														
	$0.1 < \Phi \leq 0.2$	3(distance $\geq 10\text{mm}$)																														
	$0.2 < \Phi \leq 0.25$	2(distance $\geq 10\text{mm}$)																														
$\Phi > 0.25$	0																															
Assembly deflection	beyond the edge of backlight $\leq 0.2\text{mm}$																															
CTP cover broken X : length Y : width Z : height	<table><tr><th>X</th><th>Y</th><th>Z</th></tr><tr><td>$X \leq 0.5\text{mm}$</td><td>$Y \leq 0.5\text{mm}$</td><td>$Z < \text{cover thickness}$</td></tr></table>	X	Y	Z	$X \leq 0.5\text{mm}$	$Y \leq 0.5\text{mm}$	$Z < \text{cover thickness}$																									
	X	Y	Z																													
$X \leq 0.5\text{mm}$	$Y \leq 0.5\text{mm}$	$Z < \text{cover thickness}$																														
Circuitry broken is not allowed.																																



			X	Y	Z	
		CTP cover broken	$X \leq 0.3\text{mm}$	$Y \leq 0.3\text{mm}$	$Z < \text{cover thickness}$	
		X : length	* Circuitry broken is not allowed.			
		Y : width				
		Z : height				



Criteria (functional items)

Number	Items	Criteria (mm)
1	No display	Not allowed
2	Missing segment	Not allowed
3	Short	Not allowed
4	Backlight no lighting	Not allowed
5	CTP no function	Not allowed



10. Reliability Test Result

Item	Condition	Inspection after test
High Temperature Operating	85°C,96H	Inspection after 2~4hours storage at room temperature, the sample shall be free from defects: 1.Air bubble in the LCD; 2.Non-display; 3.Missing segments/line; 4.Glass crack; 5.Current IDD is twice higher than initial value.
Low Temperature Operating	-30°C, 96HR	
High Temperature Storage	90°C, 96HR	
Low Temperature Storage	-40°C, 96HR	
High Temperature & High Humidity Operating	+60°C, 90% RH ,96 hours.	
Thermal Shock (Non-operation)	-10°C,30 min ↔ +60°C,30 min, Change time:5min 20CYC.	
ESD test	C=150pF, R=330,5points/panel Air:±8KV, 5times; Contact:±6KV, 5 times; (Environment: 15°C~35°C, 30%~60%).	
Vibration (Non-operation)	Frequency range:10~55Hz, Stroke:1.5mm Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z. (6 hours for total) (Package condition).	
Box Drop Test	1 Corner 3 Edges 6 faces,80 _{cm} (MEDIUM BOX)	

Remark:

- 1.The test samples should be applied to only one test item.
- 2.Sample size for each test item is 5~10pcs.
- 3.For Damp Proof Test, Pure water(Resistance > 10MΩ) should be used.
- 4.In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part.
- 5.Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.
6. The color fading mura of polarizing filter should not care.



11. Cautions and Handling Precautions

11.1 Handling and Operating the Module

- (1) When the module is assembled, it should be attached to the system firmly.
Do not warp or twist the module during assembly work.
- (2) Protect the module from physical shock or any force. In addition to damage, this may cause improper operation or damage to the module and back-light unit.
- (3) Note that polarizer is very fragile and could be easily damaged. Do not press or scratch the surface.
- (4) Do not allow drops of water or chemicals to remain on the display surface.
If you have the droplets for a long time, staining and discoloration may occur.
- (5) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
- (6) The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane.
Do not use ketene type materials (ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (7) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs, or clothes, it must be washed away thoroughly with soap.
- (8) Protect the module from static; it may cause damage to the CMOS ICs.
- (9) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (10) Do not disassemble the module.
- (11) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (12) Pins of I/F connector shall not be touched directly with bare hands.
- (13) Do not connect, disconnect the module in the "Power ON" condition.
- (14) Power supply should always be turned on/off by the item 6.1 Power On Sequence & 6.2 Power Off Sequence

11.2 Storage and Transportation.

- (1) Do not leave the panel in high temperature, and high humidity for a long time.
It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%
- (2) Do not store the TFT-LCD module in direct sunlight.
- (3) The module shall be stored in a dark place. When storing the modules for a long time, be sure to adopt effective measures for protecting the modules from strong ultraviolet radiation, sunlight, or fluorescent light.
- (4) It is recommended that the modules should be stored under a condition where no condensation is allowed. Formation of dewdrops may cause an abnormal operation or a failure of the module.
In particular, the greatest possible care should be taken to prevent any module from being operated where condensation has occurred inside.
- (5) This panel has its circuitry FPC on the bottom side and should be handled carefully in order not to be stressed.