

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support

Obsolescence Management

PCAP

Embedded Systems

Human Machine Interface

Touch Solutions

Software

Quality Management

Open Frame Monitors

LCD Controller

Research & Development

Firmware

EMC tests

on-site service

Optical Bonding

In-house Manufacturing

Cover glass

System solutions

OEM Solutions

Custom Display

Production Custom designs Installation

Mechanical design



SPECIFICATION FOR LCM Module

MODULE No:	ET043WQ01-K
CUSTOMER:	

YOURITECH	INITIAL	DATE
PREPARED BY		
CHECKED BY		
APPROVED BY		

CUSTOMER	INITIAL	DATE
APPROVED BY		



Contents

1. Block Diagram	5
2. Outline dimension	6
3. Input terminal Pin Assignment	7
4. LCD Optical Characteristics	9
4.1 Optical specification	9
5. Electrical Characteristics	12
5.1 Absolute Maximum Rating	12
5.2 DC Electrical Characteristics	12
5.3 LED Backlight Characteristics	13
6. AC Characteristic	15
6.1 System Bus Timing for RGB Interface	15
6.2 RGB Interface	16
6.2.1 SYNC Mode	16
6.2.2 SYNC-DE Mode	17
6.2.3 DE Mode	18
6.3 RGB Input Timing Table	19
6.3.1 Parallel 24-bit RGB Timing Table	19
6.3.2 Series 8-bit RGB Timing Table	19
7. POWER ON/OFF SEQUENCE	20
7.1 Power On Sequence	20
7.2 Power Off Sequence	21
8. LCD Module Out-Going Quality Level	22
8.1 VISUAL & FUNCTION INSPECTION STANDARD	22
8.1.1 Inspection conditions	22
8.1.2 Definition	22
8.1.3 Sampling Plan	23
8.1.4 Criteria (Visual)	24
9. Reliability Test Result	28
10. Cautions and Handling Precautions	29
10.1 Handling and Operating the Module	29
10.2 Storage and Transportation	29
11. Packing	30



* Description

This is a color active matrix TFT (Thin Film Transistor) LCD (liquid crystal display) that uses amorphous silicon TFT as a switching device. This module is composed of a Transmissive type TFT-LCD Panel, driver circuit, back-light unit. The resolution of a 4.3" TFT-LCD contains 480X272 pixels, and can display up to 65K/262K/16.7M colors.

* Features


General Information Items	Specification	Unit	Note
	Main Panel		
Display area(AA)	95.04(H)*53.86(V) (4.3inch)	mm	
Driver element	TFT active matrix	-	
Display colors	65K/262K/16.7M	colors	
Number of pixels	480(RGB)*272	dots	
Pixel arrangement	RGB vertical stripe	-	
Pixel pitch	0.198(H)*0.198(V)	mm	
Viewing angle	FREE	o'clock	
Controller IC	ILI6485	-	
LCM Interface	24/8 BIT RGB	-	
Display mode	Transmissive /Normally black	-	
Operating temperature	-30~+80	°C	
Storage temperature	-30~+80	°C	

* Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal(H)	-	105.4	-	mm	
	Vertical(V)	-	67.15	-	mm	
	Depth(D)	-	2.85	-	mm	
Weight		-	40	-	g	



1. Block Diagram



p
 e
 c
 if₄

22	C	B1	i-	B2
23				B2

a
 ti
 on




3. Input terminal Pin Assignment

NO.	SYMBOL	DISCRIPTION	I/O
1	VLED-	Cathode pin of backlight	P
2	VLED+	Anode pin of backlight	P
3	GND	Ground.	P
4	VDD	Supply voltage(3.3V).	P
5-12	R0-R7	8-bit digital Red data input	I
13-20	G0-G7	8-bit digital Green data input. Serial 8-bit RGB interface and input through DG[7:0].	I
21-28	B0-B7	8-bit digital Blue data input	I
29	GND	Ground.	P
30	PCLK	Clock signal; latching data at the falling edge	I
31	DISP	Display control / standby mode selection. DISP = "Low" : Standby; DISP = "High" : Normal display (Default)	I
32	HSYNC	Horizontal sync signal; negative polarity	I
33	VSYNC	Vertical sync signal; negative polarity	I
34	DE	Data input enable. Active High to enable the data input When not used in SYNC mode, user should connect it to "Low".	I
35	NC	--	--
36	GND	Ground.	P
37	XR(NC)	--	--
38	YD(NC)	--	--
39	XL(NC)	--	--
40	YU(NC)	--	--



FPC Interface set in



Note:

default setting is 24bit RGB interface, it needs to change registers location if it is for 8bit serial RGB interface.

R10	R11	Interface type
OR	NC	24BIT RGB interface
NC	OR	8BIT RGB interface, G0-G7



4. LCD Optical Characteristics

4.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit.	Note
Contrast Ratio		CR	$\Theta=0$ Normal viewing angle	1000	1200	--		(1)(2)
Response time	Rising	T_R+T_F		--	30	35	msec	(1)(3)
	Falling							
Color Gamut		S(%)		40	45.5	--	%	C-light
Color Filter Chromaticity	White	W_X		-0.04	0.278	+0.04	--	(1)(4) CA-310
		W_Y			0.292			
	Red	R_X			0.549			
		R_Y			0.314			
	Green	G_X			0.341			
		G_Y			0.562			
	Blue	B_X			0.153			
		B_Y			0.094			
Viewing angle	Hor.	Θ_L	CR>10	80	85	--	--	(1)(4)
		Θ_R		80	85	--		
	Ver.	Θ_U		80	85	--		
		Θ_D		80	85	--		
Option View Direction		FREE						

*The data comes from the LCD specification.

Measuring Condition

Measuring surrounding : dark room

Ambient temperature : $25\pm 2^\circ\text{C}$


15min. warm-up time.

Measuring Equipment

FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.




Note (1): Definition of Viewing Angle :




Note (2): Definition of Contrast Ratio(CR) :measured at the center point of panel

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Note (3): Response Time



Note (4): Definition of optical measurement setup



5. Electrical Characteristics

5.1 Absolute Maximum Rating

Characteristics	Symbol	Min.	Max.	Unit	Note
Digital Supply Voltage	VDD	-0.3	4.6	V	Note1
Operating temperature	T _{OP}	-30	+80	°C	
Storage temperature	T _{ST}	-30	+80	°C	

NOTE1: If the absolute maximum rating of even is one of the above parameters is exceeded even momentarily, the quality of the product may be degraded. Absolute maximum ratings, therefore, specify the values exceeding which the product may be physically damaged. Be sure to use the product within the range of the absolute maximum ratings.

5.2 DC Electrical Characteristics

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Digital Supply Voltage	VDD	3.0	3.3	3.6	V	
Normal mode Current	IDD	--	20	40	mA	
Level input voltage	V _{IH}	0.7VDD	--	VDD	V	
	V _{IL}	GND	--	0.3VDD	V	
Level output voltage	V _{OH}	VDD-0.4	--	--	V	
	V _{OL}	GND	--	GND+0.4	V	



5.3 LED Backlight Characteristics

The back-light system is edge-lighting type with 9 chips LED

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Forward Current	I_F	--	20	--	mA	
Forward Voltage	V_F	24.3	25.6	29.7	V	
LCM Luminance ($I_F=20\text{mA}$)	LV	550	600	--	cd/m ²	Note3
LED life time	Hr	50000		--	Hour	Note1,2
Uniformity	Avg	80	--	--	%	Note3

Note1: LED life time (Hr) can be defined as the time in which it continues to operate under the condition:

$T_a=25\pm3\text{ }^{\circ}\text{C}$, typical IL value indicated in the above table until the brightness becomes less than 50%.

Note 2: The "LED life time" is defined as the module brightness decrease to 50% original brightness at


$T_a=25^{\circ}\text{C}$ and $I_L=20\text{ mA}$. The LED lifetime could be decreased if operating I_L is larger than 20mA. The constant current driving method is suggested.



B/L Circuit



Note (3) Luminance Uniformity of these 9 points is defined as below:




$$\text{Uniformity} = \frac{\text{minimum luminance in 9 points (1-9)}}{\text{maximum luminance in 9 points (1-9)}}$$

$$\text{Luminance} = \frac{\text{Total Luminance of 9 points}}{9}$$



6. AC Characteristic

6.1 System Bus Timing for RGB Interface




Item	Symbol	Min.	Typ.	Max.	Unit	Conditions
CLK Pulse Duty	Tcw	40	50	60	%	
HSYNC Width	Thw	2	-	-	DCLK	
HSYNC Period	Th	55	60	65	us	
VSYNC Setup Time	Tvst	12	-	-	ns	
VSYNC Hold Time	Tvhd	12	-	-	ns	
HSYNC Setup Time	Thst	12	-	-	ns	
HSYNC Hold Time	Thhd	12	-	-	ns	
Data Setup Time	Tdsu	12	-	-	ns	
Data Hold Time	Tdhd	12	-	-	ns	
DE Setup Time	Tdest	12	-	-	ns	
DE Hold Time	Tdehd	12	-	-	ns	




6.2 RGB Interface


6.2.1 SYNC Mode



6.2.2 SYNC-DE Mode



6.2.3 DE Mode



RGB Mode Selection Table	DCLK	HSYNC	VSYNC	DE
SYNC - DE Mode	Input	Input	Input	Input
SYNC Mode	Input	Input	Input	GND
DE Mode	Input	GND	GND	Input

Note: "Input" means these signals are driven by host side.



6.3 RGB Input Timing Table

6.3.1 Parallel 24-bit RGB Timing Table

RGB input timing table (VCIP=VCI=VDDI= 3.3V, VSSA= 0V, TA=25°C).

480RGB X 272 Resolution Timing Table						
Item	Symbol	Min.	Typ.	Max.	Unit	Remark
DCLK Frequency	Fclk	8	9	12	MHz	
DCLK Period	Tclk	125	111	83	ns	
HSYNC	Period Time	Th	487	531	598	DCLK
	Display Period	Thdisp	-	480	-	DCLK
	Back Porch	Thbp	3	43	43	DCLK
	Front Porch	Thfp	4	8	75	DCLK
	Pulse Width	Thw	2	4	75	DCLK
VSYNC	Period Time	Tv	276	292	321	H
	Display Period	Tvdisp	-	272	-	H
	Back Porch	Tvbp	2	12	12	H
	Front Porch	Tvfp	2	8	37	H
	Pulse Width	Tvw	2	4	37	H

Note: 1.It is necessary to keep Tvbp =12 and Thbp =43 in sync mode. DE mode is unnecessary to keep it.

2.Thbp+Thfp >=7

6.3.2 Series 8-bit RGB Timing Table

480RGB X 272 Resolution Timing Table						
Item	Symbol	Min.	Typ.	Max.	Unit	Remark
DCLK Frequency	Fclk	24	27	30	MHz	
DCLK Period	Tclk	42	37	33	ns	
HSYNC	Period Time	Th	1461	1491	1558	DCLK
	Display Period	Thdisp	-	1440	-	DCLK
	Back Porch	Thbp	3	43	43	DCLK
	Front Porch	Thfp	18	8	75	DCLK
	Pulse Width	Thw	2	4	75	DCLK
VSYNC	Period Time	Tv	276	292	321	H
	Display Period	Tvdisp	-	272	-	H
	Back Porch	Tvbp	2	12	12	H
	Front Porch	Tvfp	2	8	37	H
	Pulse Width	Tvw	2	4	37	H


Note:1. It is necessary to keep Tvbp =12 and Thbp =43 in sync mode. DE mode is unnecessary to keep it.

2.Thbp+Thfp >=21



7. POWER ON/OFF SEQUENCE


7.1 Power On Sequence



Symbol	Description	Min. Time	Unit
T0	System power stability to GRB RESET signal	0	ms
T1	GRB RESET= "High" to DISP="High"	10	ms
T2	Display Signal output to Backlight Power on	250	ms



7.2 Power Off Sequence



Symbol	Description	Min. Time	Unit
T0	Backlight Power off to DISP="Low"	5	ms
T1	DISP="Low" to IC internal voltage discharge complete	80	ms



8. LCD Module Out-Going Quality Level

8.1 VISUAL & FUNCTION INSPECTION STANDARD

8.1.1 Inspection conditions

Inspection performed under the following conditions is recommended.


Temperature : $25\pm 5^{\circ}\text{C}$

Humidity : $65\%\pm 10\%\text{RH}$


Viewing Angle : Normal viewing Angle.

Illumination: Single fluorescent lamp (300 to 700Lux)

Viewing distance:30-50cm



8.1.2 Definition



Zone A : Effective Viewing Area(Character or Digit can be seen)

Zone B : Viewing Area except Zone A

Zone C : Outside (Zone A+Zone B) which can not be seen after assembly by customer

Zone D : IC Bonding Area

Note:As a general rule ,visual defects in Zone C can be ignored when it doesn't effect product function or appearance after assembly by customer



8.1.3 Sampling Plan

According to GB/T 2828-2012 ; , normal inspection, Class II

AQL:

Major defect	Minor defect
0.65	1.5

LCD: Liquid Crystal Display , LCM: Liquid Crystal Module,




No	Items to be inspected	Criteria	Classification of defects
1	Functional defects	1) No display, Open or miss line 2) Display abnormally, Short 3) Backlight no lighting, abnormal lighting. etc...	Major
2	Missing	Missing components and etc...	
3	Outline dimension	Overall outline dimension beyond the drawing is not allowed, deformation and etc...	
4	Color tone	Color unevenness, refer to limited sample	Minor
5	Spot/Line defect	Light dot, Dim spot, (Note1) Polarizer Air Bubble, Polarizer accidented spot and etc.	
6	Soldering appearance	Good soldering , Peeling off is not allowed and etc.	
7	LCD/Polarizer	Black/White spot/line, scratch, crack, etc.	

Note1: a) Light dot: Dots appear bright and unchanged in size in which LCD panel is displaying under black pattern.

b) Dim dot: Dots appear dark and unchanged in size in which LCD panel is displaying under pure red, green, blue picture.



8.1.4 Criteria (Visual)

Number	Items	Criteria(mm)						
1.0 LCD Crack/Broken NOTE: X: Length Y: Width Z: Height L: Length of IT O, T: Height of LCD	(1) The edge of LCD broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td><Inner border line of the seal</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	<Inner border line of the seal	≤T
	X	Y	Z					
	≤3.0mm	<Inner border line of the seal	≤T					
(2)LCD corner broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td>≤L</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	≤L	≤T	
X	Y	Z						
≤3.0mm	≤L	≤T						
(3) LCD crack	 Crack Not allowed							



Spot defect

$\Phi=(X+Y)/2$

① light dot (black/white spot , pinhole, stain, etc.)

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.15$	Ignore	Ignore	
$0.15<\Phi\leq0.25$	3(distance $\geq 10\text{mm}$)		
$0.25<\Phi\leq0.4$	2(distance $\geq 10\text{mm}$)		
$\Phi>0.4$	0		

② Dim spot (light leakage、dent、dark spot, etc)

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.15$	Ignore	Ignore	
$0.15<\Phi\leq0.25$	3(distance $\geq 10\text{mm}$)		
$0.25<\Phi\leq0.4$	2(distance $\geq 10\text{mm}$)		
$\Phi>0.4$	0		




③ Polarizer accidented spot

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.2$	Ignore		Ignore
$0.2<\Phi\leq0.5$	2(distance $\geq 10\text{mm}$)		
$\Phi>0.5$	0		

④Polarizer Bubble

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.2$	Ignore		Ignore
$0.2<\Phi\leq0.4$	3(distance $\geq 10\text{mm}$)		
$\Phi>0.4$	0		



3.0	LCD Pixel defect	Pixel bad points <table border="1" data-bbox="539 309 1497 1059"> <thead> <tr> <th data-bbox="539 309 730 365">Item</th><th data-bbox="730 309 1246 365">Zone A</th><th data-bbox="1246 309 1497 365">Acceptable Qt</th></tr> </thead> <tbody> <tr> <td data-bbox="539 365 730 521" rowspan="3">Bright dot</td><td data-bbox="730 365 1246 421">Random</td><td data-bbox="1246 365 1497 421">$N \leq 2$</td></tr> <tr> <td data-bbox="730 421 1246 477">2 dots adjacent</td><td data-bbox="1246 421 1497 477">$N \leq 0$</td></tr> <tr> <td data-bbox="730 477 1246 521">3 dots adjacent</td><td data-bbox="1246 477 1497 521">$N \leq 0$</td></tr> <tr> <td data-bbox="539 521 730 689" rowspan="3">Dark dot</td><td data-bbox="730 521 1246 577">Random</td><td data-bbox="1246 521 1497 577">$N \leq 2$</td></tr> <tr> <td data-bbox="730 577 1246 633">2 dots adjacent</td><td data-bbox="1246 577 1497 633">$N \leq 0$</td></tr> <tr> <td data-bbox="730 633 1246 689">3 dots adjacent</td><td data-bbox="1246 633 1497 689">$N \leq 0$</td></tr> <tr> <td data-bbox="539 689 730 1003">Distance</td><td data-bbox="730 689 1246 1003"> 1. Minimum Distance Between Bright dots. 2. Minimum Distance Between dark dots 3. Minimum Distance Between dark and bright dot. </td><td data-bbox="1246 689 1497 1003">5mm</td></tr> <tr> <td colspan="2" data-bbox="539 1003 1246 1059">Total bright and dark dot</td><td data-bbox="1246 1003 1497 1059">$N \leq 4$</td></tr> </tbody> </table> Note: A) Bright dot: Dots appear bright and unchanged in size in which LCD panel is displaying under black pattern. B) Dark dot: Dots appear dark and unchanged in size in which LCD panel is displaying under pure red, green, blue picture. C) 2 dot adjacent = 1 pair = 2 dots Picture:  2 dot adjacent  2 dot adjacent (vertical)  2 dot adjacent  2 dot adjacent (slant)	Item	Zone A	Acceptable Qt	Bright dot	Random	$N \leq 2$	2 dots adjacent	$N \leq 0$	3 dots adjacent	$N \leq 0$	Dark dot	Random	$N \leq 2$	2 dots adjacent	$N \leq 0$	3 dots adjacent	$N \leq 0$	Distance	1. Minimum Distance Between Bright dots. 2. Minimum Distance Between dark dots 3. Minimum Distance Between dark and bright dot.	5mm	Total bright and dark dot		$N \leq 4$
Item	Zone A	Acceptable Qt																							
Bright dot	Random	$N \leq 2$																							
	2 dots adjacent	$N \leq 0$																							
	3 dots adjacent	$N \leq 0$																							
Dark dot	Random	$N \leq 2$																							
	2 dots adjacent	$N \leq 0$																							
	3 dots adjacent	$N \leq 0$																							
Distance	1. Minimum Distance Between Bright dots. 2. Minimum Distance Between dark dots 3. Minimum Distance Between dark and bright dot.	5mm																							
Total bright and dark dot		$N \leq 4$																							



4.0	Line defect (LCD /Polarizer backlight black/white line, scratch, stain)  W: width, L : length N : Count	Width(mm)	Length(m m)	Acceptable Qty		
				A	B	C
		$\Phi \leq 0.05$	Ignore	Ignore		Ignore
		$0.05 < W \leq 0.06$	$L \leq 4.0$	$N \leq 3$		
		$0.06 < W \leq 0.08$	$L \leq 3.0$	$N \leq 2$		
		$W > 0.08$	Define as spot defect			
5.0	Electronic Components SMT.	Not allow missing parts, solderless connection, cold solder joint, mismatch, The positive and negative polarity opposite				
6.0	Display color& Brightness.	1. Color: Measuring the color coordinates, The measurement standard according to the datasheet or samples. 2. Brightness: Measuring the brightness of White screen, The measurement standard according to the datasheet or Samples.				
7.0	LCD Mura/Waving/ Hot spot	Not visible through 5% ND filter in 50% gray or judge by limit sample if necessary.				

Criteria (functional items)

Number	Items	Criteria (mm)
1	No display	Not allowed
2	Missing segment	Not allowed
3	Short	Not allowed
4	Backlight no lighting	Not allowed



9. Reliability Test Result

Item	Condition	Inspection after test
High Temperature Operating	80°C,96H	Inspection after 2~4hours storage at room temperature, the sample shall be free from defects: 1.Air bubble in the LCD; 2.Non-display; 3.Missing segments/line; 4.Glass crack; 5.Current IDD is twice higher than initial value.
Low Temperature Operating	-30°C, 96HR	
High Temperature Storage	80°C, 96HR	
Low Temperature Storage	-30°C, 96HR	
High Temperature & High Humidity Operating	+60°C, 90% RH ,96 hours.	
Thermal Shock (Non-operation)	-10°C,30 min ↔ +60°C,30 min, Change time:5min 20CYC.	
ESD test	C=150pF, R=330,5points/panel Air:±8KV, 5times; Contact:±6KV, 5 times; (Environment: 15°C~35°C, 30%~60%).	
Vibration (Non-operation)	Frequency range:10~55Hz, Stroke:1.5mm Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z. (6 hours for total) (Package condition).	
Box Drop Test	1 Corner 3 Edges 6 faces,80cm(MEDIUM BOX)	

Remark:

- 1.The test samples should be applied to only one test item.
- 2.Sample size for each test item is 5~10pcs.
- 3.For Damp Proof Test, Pure water(Resistance > 10MΩ) should be used.
- 4.In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part.
- 5.Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.
6. The color fading mura of polarizing filter should not care.



10. Cautions and Handling Precautions

10.1 Handling and Operating the Module

(1) When the module is assembled, it should be attached to the system firmly.

Do not warp or twist the module during assembly work.

(2) Protect the module from physical shock or any force. In addition to damage, this may cause improper operation or damage to the module and back-light unit.

(3) Note that polarizer is very fragile and could be easily damaged. Do not press or scratch the surface.

(4) Do not allow drops of water or chemicals to remain on the display surface.

If you have the droplets for a long time, staining and discoloration may occur.

(5) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.

(6) The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane.

Do not use ketene type materials (ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.

(7) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs, or clothes, it must be washed away thoroughly with soap.

(8) Protect the module from static; it may cause damage to the CMOS ICs.

(9) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.

(10) Do not disassemble the module.

(11) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.

(12) Pins of I/F connector shall not be touched directly with bare hands.

(13) Do not connect, disconnect the module in the "Power ON" condition.

(14) Power supply should always be turned on/off by the item 6.1 Power On Sequence & 6.2 Power Off Sequence

10.2 Storage and Transportation.

(1) Do not leave the panel in high temperature, and high humidity for a long time.

It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%

(2) Do not store the TFT-LCD module in direct sunlight.

(3) The module shall be stored in a dark place. When storing the modules for a long time, be sure to adopt effective measures for protecting the modules from strong ultraviolet radiation, sunlight, or fluorescent light.

(4) It is recommended that the modules should be stored under a condition where no condensation is allowed. Formation of dewdrops may cause an abnormal operation or a failure of the module.

In particular, the greatest possible care should be taken to prevent any module from being operated where condensation has occurred inside.

(5) This panel has its circuitry FPC on the bottom side and should be handled carefully in order not to be stressed.



11. Packing

