

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support

Obsolescence Management

PCAP

Embedded Systems

Human Machine Interface

Touch Solutions

Software

Quality Management

Open Frame Monitors

LCD Controller

Research & Development

Firmware

EMC tests

on-site service

Optical Bonding

In-house Manufacturing

Cover glass

System solutions

OEM Solutions

Custom Display

Production Custom designs Installation

Mechanical design



MODEL NO : ET043WV01-K**MODEL VERSION: 01****SPEC VERSION : 1.0****ISSUED DATE: 2018-02-05**

- ☒ Preliminary Specification
☐ Final Product Specification

Customer : _____

Approved by	Notes

Table of Contents

Record of Revision.....	3
1 General Specifications	4
2 Input/Output Terminals	5
3 Absolute Maximum Ratings	6
4 Electrical Characteristics.....	6
5 Timing Chart.....	8
6 Optical Characteristics	14
7 Environmental / Reliability Test	17
9 Packing Drawing	19
10 Precautions for Use of LCD Modules	19

Record of Revision

[illegible]

1 General Specifications

Feature		Spec
Display Spec.	Size	4.3 inch
	Resolution	480(RGB)*800
	Technology Type	a-Si
	Pixel Configuration	RGB Vertical Stripe
	Pixel pitch(mm)	0.117(H)*0.117(V)
	Display Mode	Transmissive/Normally Black
	Viewing Direction	ALL
Mechanical Characteristics	MODEL (W x H x D) (mm)	62.5 (W)*105.5(H)*2,5(D)
	Active Area(mm)	56.16(H)*93.60(V)
	With /Without TSP	Without TSP
	Driver IC	ILI9806E
	Weight (g)	TBD
Electrical Characteristics	LCD Interface	2 Lane MIPI
	Color Depth	16.7M

Note 1: Viewing direction for best image quality is different from TFT definition. There is a 180 degree shift.

Note 2: Requirements on Environmental Protection: Q/S0002

Note 3: LCM weight tolerance: $\pm 5\%$

2 Input/Output Terminals

2.1 LCM Interface

NO.	SYMBOL	DISCRIPTION	I/O
1	NC		
2	LEDK	Cathode pin of backlight.	P
3	NC		
4	LEDA	Anode pin of backlight.	P
5	NC		
6	VCI	Supply Voltage (3.3V).	P
7	IOVCC	I/O power supply voltage.	P
8	TE	-Tearing effect output Leave the pin to open when not in use.	O
9	RESET	- The external reset input. Initializes the chip with a low input. Be sure to execute a power-on reset after supplying power.	I
10	GND	Ground.	P
11	MIPI_D1P	MIPI DSI differential data pair (DSI-Dn+/-). If MIPI are not used, they should be connected to DGND	I/O
12	MIPI_D1N		I/O
13	GND	Ground.	P
14	MIPI_CLP	MIPI DSI differential clock pair (DSI-CLK+/-). If MIPI are not used, they should be connected to DGND.	I
15	MIPI_CLN		I
16	GND	Ground.	P
17	MIPI_D0P	MIPI DSI differential data pair (DSI-Dn+/-). If MIPI are not used, they should be connected to DGND	I/O
18	MIPI_D0N		I/O
19	GND	Ground.	P
20	GND	Ground.	P

3 Absolute Maximum Ratings

Characteristics	Symbol	Min.	Max.	Unit
Digital Supply Voltage	V _{CI}	-0.3	4.6	V
Digital interface supply Voltage	IOVCC	-0.3	4.6	V
Operating temperature	T _{OP}	-20	+70	°C
Storage temperature	T _{ST}	-30	+80	°C

NOTE: If the absolute maximum rating of even is one of the above parameters is exceeded even momentarily, the quality of the product may be degraded. Absolute maximum ratings, therefore, specify the values exceeding which the product may be physically damaged. Be sure to use the product within the range of the absolute maximum ratings.

4 Electrical Characteristics

4.1 Driving TFT LCD Panel


Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Digital Supply Voltage	V _{CI}	2.5	2.8/3.3	3.6	V	--
Digital interface supply Voltage	IOVCC	1.62	1.8	3.6	V	--
Normal mode Current consumption	IDD	--	25	--	mA	--
Level input voltage	V _{IH}	0.7 IOVCC	--	IOVCC	V	--
	V _{IL}	-0.3	--	0.3 IOVCC	V	--
Level output voltage	V _{OH}	0.8* IOVCC	--	IOVCC	V	--
	V _{OL}	GND	--	0.2 IOVCC	V	--

4.2 Backlight Unit

The backlight system is an edge-lighting type with 8 LED. The characteristics of the LED are shown in the following tables.

Item	Symbol	MIN	TYP	MAX	Unit	Remark
Backlight forward voltage	V_F	-	12.8	-	V	8 LEDs
Backlight forward current	I_F	--	40	--	mA	
LED life time	--	50000	--	--	Hrs	

Note 1: LED life time (Hr) can be defined as the time in which it continues to operate under the condition: $T_a=25\pm3\text{ }^{\circ}\text{C}$, typical IL value indicated in the above table and the $f_L=50\text{k Hz}$ until the brightness becomes less than 50%.



LED(B/L) CIRCUIT

5 Timing Chart

5.1 MIPI Interface Characteristics

High Speed Mode – Clock Channel Timing




Figure 114 DSI Clock Channel Timing

Table 45 DSI Clock Channel Timing

Signal	Symbol	Parameter	Min	Max	Unit
DSI-CLK+/-	$2xUI_{INST}$	Double UI instantaneous	4	25	ns
DSI-CLK+/-	UI_{INSTA}, UI_{INSTB}	UI instantaneous Half	2	12.5	ns

Note: $UI = UI_{INSTA} = UI_{INSTB}$

High Speed Mode – Data Clock Channel Timing




Figure 115 DSI Data to Clock Channel Timings

Table 46 DSI Data to Clock Channel Timings

Signal	Symbol	Parameter	Min	Max
DSI-Dn+/- , n=0 and 1	t_{DS}	Data to Clock Setup time	$0.15xUI$	-
	t_{DH}	Clock to Data Hold Time	$0.15xUI$	-

Figure 116 Rise and Fall Timings on Clock and Data Channels

Table 47 Rise and Fall Timings on Clock and Data Channels

Parameter	Symbol	Condition	Specification			Unit
			Min	Typ	Max	
Differential Rise Time for Clock	t _{ORTCLK}	DSI-CLK+/-	-	-	150 (Note)	ps
Differential Rise Time for Data	t _{ORTDATA}	DSI-Dn+/- n=0 and 1	-	-	150 (Note)	ps
Differential Fall Time for Clock	t _{FTCLK}	DSI-CLK+/-	-	-	150 (Note)	ps
Differential Fall Time for Data	t _{FTDATA}	DSI-Dn+/- n=0 and 1	-	-	150 (Note)	ps

1

Lower Power Mode and its State Periods are illustrated for reference purposes on the Bus Turnaround (BTA) from the MPU to the Display Module (ILI9806E) sequence below.



Figure 117 BTA from the MPU to the Display Module

The information contained herein is the exclusive property of Shenzhen Youri Technology Co.,Ltd,and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of Shenzhen Youri Technology Co.,Ltd

Lower Power Mode and its State Periods are illustrated for reference purposes on the Bus Turnaround (BTA) from the Display Module (ILI9806E) to the MPU sequence below.




Figure 118 BTA from the Display Module to the MPU

Table 48 Low Power State Period Timings – A

Signal	Symbol	Description	Min	Max	Unit
DSI-D0+/-	T_{LPXM}	Length of LP-00, LP-01, LP-10 or LP-11 periods MPU → Display Module (ILI9806E)	50	75	ns
DSI-D0+/-	T_{LPXD}	Length of LP-00, LP-01, LP-10 or LP-11 periods Display Module (ILI9806E) → MPU	50	75	ns
DSI-D0+/-	T_{TA-00D}	Time-out before the Display Module (ILI9806E) starts driving	T_{LPXD}	$2 \times T_{LPXD}$	ns

Table 49 Low Power State Period Timings – B

Signal	Symbol	Description	Time	Unit
DSI-D0+/-	$T_{TA-GETD}$	Time to drive LP-00 by Display Module (ILI9806E)	$5 \times T_{LPXD}$	ns
DSI-D0+/-	T_{TA-00D}	Time to drive LP-00 after turnaround request – MPU	$4 \times T_{LPXD}$	ns




Figure 119 Data Lanes – Low Power Mode to High Speed Mode Timings

Table 50 Data Lanes – Low Power Mode to High Speed Mode Timings

Signal	Symbol	Description	Min	Max	Unit
DSI-Dn+/-, n=0 and 1	T_{LPX}	Length of any Low Power State Period	50	-	ns
DSI-Dn+/-, n=0 and 1	$T_{HS-PREPARE}$	Time to drive LP-00 to prepare for HS Transmission	40+4xUI	85+6xUI	ns
DSI-Dn+/-, n=0 and 1	$T_{HS-TERM-EN}$	Time to enable Data Lane Receiver line termination measured from when Dn crosses V_{ILMAX}	-	35+4xUI	ns




Figure 120 Data Lanes – High Speed Mode to Low Power Mode Timings

Table 51 Data Lanes – High Speed Mode to Low Power Mode Timings

Signal	Symbol	Description	Min	Max	Unit
DSI-Dn+/-, n=0 and 1	$T_{HS-SKIP}$	Time-Out at Display Module (ILI9806E) to ignore transition period of EoT	40	55+4xUI	ns
DSI-Dn+/-, n=0 and 1	$T_{HS-EXIT}$	Time to driver LP-11 after HS burst	100	-	ns




Figure 121 Clock Lanes – High Speed Mode to/from Low Power Mode Timings

Table 52 Clock Lanes – High Speed Mode to/from Low Power Mode Timings

Signal	Symbol	Description	Min	Max	Unit
DSI-CLK+/-	$T_{CLK-POST}$	Time that the MPU shall continue sending HS clock after the last associated Data Lanes has transitioned to LP mode	$60+52 \times UI$	-	ns
DSI-CLK+/-	$T_{CLK-TRAIL}$	Time to drive HS differential state after last payload clock bit of a HS transmission burst	60	-	ns
DSI-CLK+/-	$T_{HS-EXIT}$	Time to drive LP-11 after HS burst	100	-	ns
DSI-CLK+/-	$T_{CLK-PREPARE}$	Time to drive LP-00 to prepare for HS transmission	38	95	ns
DSI-CLK+/-	$T_{CLK-TERM-EN}$	Time-out at Clock Lane to enable HS termination	-	38	ns
DSI-CLK+/-	$T_{CLK-PREPARE}$	Minimum lead HS-0 drive period before starting Clock	300	-	ns
DSI-CLK+/-	$T_{CLK-PRE}$	Time that the HS clock shall be driven prior to any associated Data Lane beginning the transition from LP to HS mode	$8 \times UI$	-	ns

5.2 Reset input timing




Figure 102 Reset Timing

Table 41 Reset Timing

Signal	Symbol	Parameter	Min	Max	Unit
RESX	tRW	Reset pulse duration	10		us
	tRT	Reset cancel		5(note 1,5) 120 (note 1,6,7)	ms

Note:

1. The reset cancel includes also required time for loading ID bytes, VCOM setting and other settings from OTP to registers. This loading is done every time when there is H/W reset cancel time (tRT) within 5 ms after a rising edge of RESX.
2. Spike due to an electrostatic discharge on RESX line does not cause irregular system reset according to the Table 43.

Table 42 Reset Descript

RESX Pulse	Action
Shorter than 5us	Reset Rejected
Longer than 9us	Reset
Between 5us and 9us	Reset starts

3. During the Resetting period, the display will be blanked (The display is entering blanking sequence, which maximum time is 120 ms, when Reset Starts in Sleep Out mode. The display remains the blank state in Sleep In mode.) and then return to Default condition for Hardware Reset.
4. Spike Rejection also applies during a valid reset pulse as shown below:




Figure 103 Positive Noise Pulse during Reset Low

5. When Reset applied during Sleep In Mode.
6. When Reset applied during Sleep Out Mode.
7. It is necessary to wait 5msec after releasing RESX before sending commands. Also Sleep Out command cannot be sent for 120msec.

6 Optical Characteristics


Item		Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles		θT	CR≧10	-	80	-	Degree	Note2,3
		θB		-	80	-		
		θL		-	80	-		
		θR		-	80	-		
Contrast Ratio		CR	θ=0°	-	800	-		Note 3
Response Time		T _{ON}	25℃	-	35	-	ms	Note 4
		T _{OFF}						
Chromaticity	White	x	Backlight is on	0.26	0.31	0.36		Note 1,5
		y		0.28	0.33	0.38		
	Red	x						Note 1,5
		y						
	Green	x						Note 1,5
		y						
	Blue	x						Note 1,5
		y						
Uniformity		U		75	80	--	%	Note 6
Luminance		L		400	450	-	cd/m ²	Note 7

Test Conditions:

1. $I_F = 20$ mA, and the ambient temperature is 25℃.
2. The test systems refer to Note 1 and Note 2.


Note 1: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 Minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Note 2: Definition of viewing angle range and measurement system.

viewing angle is measured at the center point of the LCD.



Note 3: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD is on the "White" state}}{\text{Luminance measured when LCD is on the "Black" state}}$$


"White state ": The state is that the LCD should drive by V_{white} .

"Black state": The state is that the LCD should drive by V_{black} .

V_{white} : To be determined V_{black} : To be determined.

Note 4: Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)


Color coordinates measured at center point of LCD.

Note 6: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity (U)} = L_{\min} / L_{\max}$$

L-----Active area length W----- Active area width



$L_{\max}$: The measured Maximum luminance of all measurement position.

$L_{\min}$: The measured Minimum luminance of all measurement position.

Note 7: Definition of Luminance:

Measure the luminance of white state at center point.

7 Environmental / Reliability Test

No	Test Item	Condition	Remarks
1	High Temperature Operation	70℃, 120Hours	IEC60068-2-1:2007 GB2423.2-2008
2	Low Temperature Operation	-20℃, 120Hours	IEC60068-2-1:2007 GB2423.1-2008
3	High Temperature Storage	80℃, 120Hours	IEC60068-2-1:2007 GB2423.2-2008
4	Low Temperature Storage	-30℃, 120Hours	IEC60068-2-1:2007 GB2423.1-2008
5	Storage at High Temperature and Humidity	60℃, 90%RH, 120Hours	IEC60068-2-78 :2001 GB/T2423.3—2006
6	Thermal Shock (non-operation)	-20℃ ↔ 70℃, ON/OFF, 20CYC	Start with cold temperature, End with high temperature, IEC60068-2-14:1984,G B2423.22-2002
7	ESD	Voltage:±8KV R:330 ohm,C:150pF Air discharge,10 times	IEC61000-4-2:2001 GB/T17626.2-2006
8	Vibration Test	10 => 55 =>10 => 55 => 10 Hz, within 1 minute;Amplitude:1.5mm. 15 minutes for each Direction (X,Y,Z)	IEC60068-2-6:1982 GB/T2423.10—1995
10	Package Drop Test	Packed, 66CM free fall 6 sides, 1 corner, 3edges	IEC60068-2-32:1990 GB/T2423.8—1995


Note1: Ts is the temperature of panel's surface.

Note2: Ta is the ambient temperature of sample.

Note3: Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

Note 4: In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

8. Outline Dimension



9 Packing Drawing

TBD

10 Precautions for Use of LCD Modules

a) Handling Precautions

- i. The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.
- ii. If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.
- iii. Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.
- iv. The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.
- v. If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:
 - Isopropyl alcohol
 - Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
 - Ketone
 - Aromatic solvents
- vi. Do not attempt to disassemble the LCD Module.
 - vii. If the logic circuit power is off, do not apply the input signals.
 - viii. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

10.1.8.1 Be sure to ground the body when handling the LCD Modules.

10.1.8.2 Tools required for assembly, such as soldering irons, must be properly ground.

10.1.8.3 To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

10.1.8.4 The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

b) Storage precautions

The information contained herein is the exclusive property of Shenzhen Youri Technology Co.,Ltd, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of Shenzhen Youri Technology Co.,Ltd

i. When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

ii. The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0℃ ~ 40℃ Relatively humidity: ≤80%

iii. The LCD modules should be stored in the room without acid, alkali and harmful gas.

c) Transportation Precautions

i. The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.