

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support

Obsolescence Management

PCAP

Embedded Systems

Human Machine Interface

Touch Solutions

Software

Quality Management

Open Frame Monitors

LCD Controller

Research & Development

Firmware

EMC tests

on-site service

In-house Manufacturing

Optical Bonding

Cover glass

System solutions

OEM Solutions

Custom Display

Production
Custom designs
Installation

Mechanical design



PRODUCT SPECIFICATION

Customer	
Project	
Part No.	ET081CR01-ZT
Remarks	☐ APPOVAL FOR SPECIFICATION ONLY ☒ APPOVAL FOR SPECIFICATION AND SAMPLE

CUSTOMER			YOURITECH		
Approved By	Checked By	Prepared By	Approved By	Checked By	Prepared By



Revision Record

Rev. No.	Date	Description
V1.0	2025-09-17	Preliminary Specification Release.

Contents

1. General Specifications	3
2. Interface Definition Description	4
3. Mechanical Drawing	5
4. Electrical Specifications	8
5. Delivery Inspection	11
6. Reliability Test	14
7. Precautions	15
8. Storage	17



1. General Specifications

No.	Item	Specification	Unit
1	Display Size (Diagonal)	8.18	inch
2	Display Resolution	1080 (H) × RGB × 1080 (V)	pixels
3	Pixel Pitch	192.6 (H) × 192.6 (V)	um
4	LCD Module Dimension (Without FPC)	219.3 (W) ×224.02 (H) ×4.0 (T)	mm
5	Touch Display Dimension (Without FPC)	241.16 (W) ×241.16 (H) ×5.3 (T)	mm
6	LCD Active Area	208.01 (W) ×208.01 (H)	mm
7	View Direction (Gray Inversion)	FULL VIEW	-
8	LCM Driver IC	FT8201S	-
9	Pixel Arrangement	RGB-Stripe	-
10	Display Mode	Normal Black	-
11	FPC Version	Z82001-P40 V1	-
12	TFT Display Interface	MIPI	-
13	TP Interface	I2C	-
14	PCAP Multi Touch	(10)	point
15	Touch Screen Report Rate	(120)	Hz
16	Operating Temperature	-20°C~ 60°C	-
17	Storage Temperature	-30°C~ 70°C	-
18	Backlight Arrangement	LED/7 Series 8 Parallel (56 lights in total)	-
19	Display+Touch Luminance	Typ.: 250	nit
20	Weight	TBD	kg




2. Interface Definition Description

PIN NO.	PIN SYMBOL	FUNCTION DESC.
1-2	AVDD	POWER SUPPLY(6.0V)
3	NC	No Connection
4-5	AVEE	POWER SUPPLY(-6.0V)
6	NC	No Connection
7-8	IOVCC 1.8V	I/O POWER SUPPLY(1.8V)
9	RESET 1.8V	LCM RESET PIN
10-11	GND	Ground
12	MIPI0N	Negative MIPI differential data input
13	MIPI0P	Positive MIPI differential data input
14	GND	Ground
15	MIPI1N	Negative MIPI differential data input
16	MIPI1P	Positive MIPI differential data input
17	GND	Ground
18	MIPICKN	Negative MIPI differential CLOCK input
19	MIPICKP	Positive MIPI differential CLOCK input
20	GND	Ground
21	MIPI2N	Negative MIPI differential data input
22	MIPI2P	Positive MIPI differential data input
23	GND	Ground
24	MIPI3N	Negative MIPI differential data input
25	MIPI3P	Positive MIPI differential data input
26	GND	Ground
27	ID0	LCM ID PIN
28	ID1	LCM ID PIN
29	GND	Ground
30	TP-SDA(1.8V)	TP I2C data (SDA) data input (MOSI)
31	TP-SCL(1.8V)	TP I2C clock (SCL) clock (SCLK)
32	TP-INT(1.8V)	TP Interrupt PIN(1.8V)
33	TP-RST(1.8V)	TP Reset PIN
34	GND	Ground
35	NC	No Connection
36-37	LED-	POWER SUPPLY- FOR BACKLIGHT CATHODE
38	NC	No Connection
39-40	LED+	POWER SUPPLY- FOR BACKLIGHT ANODE

RESET voltage should be consistent with VDDI voltage, or there probably is black screen fault when power on.







4. Electrical Specifications

4.1. LCD Optical Characteristics

Item		Symbol	Conditions	Specification			Unit	Note
				Min.	Typ.	Max.		
Transmittance (With PL)		T(%)	Viewing normal angle $x = y = 0$	--	--	-	%	-
Contrast Ratio		CR		800	1000	-	-	-
Response Time		TR+TF		-	-	35	ms	-
Viewing Angle	Hor.	Θ_{x+}	$CR \geq 10$ at 25°C	80	85	-	deg.	-
		Θ_{x-}		80	85	-		
	Ver.	Θ_{y+}		80	85	-		
		Θ_{y-}		80	85	-		

4.2. Electrical Characteristics

Item	Symbol	Specification			Unit
		Min.	Typ.	Max.	
Power For Analog Circuit	AVDD	-	-	-	V
TFT Gate On Voltage	VGH	-	-	-	V
TFT Gate Off Voltage	VGL	-	-	-	V
TFT Common Electrode Voltage	Vcom	-	-	-	V

4.3. Typical Operating Conditions

Item	Symbol	Min.	Typ.	Max.	Unit
Analog Supply Voltage	AVDD	5.8	6.0	6.1	V
Analog Supply Voltage	AVEE	-6.1	-6.0	-5.8	
I/O Supply Voltage	IOVCC	1.65	1.8	2.0	V



4.4. Backlight Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Current	I _B	-	160	-	mA	-
Voltage	V _f	18.9	21	23.8	V	-
LCM Uniformity	-	75	-	-	%	If=20mA/LED
Life Time	-	-	20000	-	Hr.	
Power Consumption	PBL	-	3360	-	mW	
LCM Chromaticity Coordinate	Red	R _x	-	-	-	Average the brightness EV at 9 points, Optical Instrument BM-7
		R _y	-	-	-	
	Green	G _x	-	-	-	
		G _y	-	-	-	
	Blue	B _x	-	-	-	
		B _y	-	-	-	
	White	W _x	0.31	-	-	
		W _y	0.32	-	-	

4.5. LCD Power Consumption


Mode	Symbol	Typ.	Max.	Unit
Normal Mode	VCC+IOVCC	-	-	mA
Test Condition: VCC=2.8V.				
Interface Drive Type: row flipping or column flipping.				
IPS Type LCD Panel => All Black Pattern.				
TN Type LCD Panel => All White Pattern.				
Temperature: 25°C.				
Mode	Symbol	Typ.	Max.	Unit
Sleep Mode	VCC+IOVCC	-	-	μA
Test Condition: VCC=2.8V.				



DC/DC converter is enabled. Internal oscillator is started and panel scanning is started.
Except for the IC internal crystal oscillator and panel scanning, other functions are suspended.
Temperature: 25°C.


4.6. Measuring System

4.6.1. LCM Viewing Angle



Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface.

4.6.2. Response Time



Response time is the time required for the display to transition from white to black (Rising time, T_r) and from black to white (Falling time, T_f) for additional information.

4.6.3. Contrast Ratio (CR)



Contrast Ratio (CR) is defined mathematically as:

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

Surface luminance is the center point across the LCD surface 500mm from the surface with all pixels displaying white.



4.7. Power On / Power Off




5. Inspection Criterion



5.1. Quality Inspection Environmental Conditions

- 5.1.1. Viewing distance: the normal viewing distance between the screen and the inspector is $30\pm 5\text{cm}$; Inspection Angle: $90^\circ\pm 45^\circ$ (90° indicates that the inspector's perspective is perpendicular to the product to be inspected).
- 5.1.2. Visual inspection illumination: $1000\pm 200\text{LUX}$;Electrical inspection illumination: $200\pm 100\text{LUX}$;Ambient temperature $25\pm 5^\circ\text{C}$, ambient humidity $55\pm 15\%\text{RH}$.



5.2. Quality Inspection Standard

No.	Defect	Standard		Defect Grade	Result
1	Spot Defect (including bright spot / color spot / bubble / dark spot, etc.)	< 7 inches	$\Phi \leq 0.10\text{mm}$	Ignore	OK
			$0.10\text{mm} < \Phi \leq 0.20\text{mm}$ $DS \geq 10\text{mm}$	Minor Defect	OK
			$\Phi > 0.20\text{mm}$	Serious Defect	NG
		$\cong 7$ inches	$\Phi \leq 0.15\text{mm}$	Ignore	OK
			$0.15\text{mm} < \Phi \leq 0.25\text{mm}$ $DS \geq 10\text{mm}$	Minor Defect	OK
			$\Phi > 0.25\text{mm}$	Serious Defect	NG
		Φ : defect diameter. DS: spacing.			
2	Linear Defect (scratches, filaments, etc.)	< 7 inches	$W \leq 0.02\text{mm}$, L: unlimited	Ignore	OK
			$0.02\text{mm} < W \leq 0.03\text{mm}$	Minor Defect	OK



		≥ 7 inches	$L \leq 5\text{mm}$			
			$W > 0.03\text{mm}$		Serious Defect	NG
			$W \leq 0.03\text{mm}$ L: unlimited		Ignore	OK
			$0.03\text{mm} < W \leq 0.05\text{mm}$ $L \leq 5\text{mm}$		Minor Defect	OK
			$W > 0.05\text{mm}$		Serious Defect	NG
		W: defect width. L: defect length. DS: spacing.				
3	Polarizer Bubble	Display Area	Judge by Spot Defect			
		Black Edge Area	The distance from the edge of the display area is greater than 0.5mm.		Minor defect	OK
			The distance from the edge of the display area is less than 0.5mm.		Judge by Spot Defect	
4	Polarizer Bump (Mark)	Display Area / Black Edge Area	Invisible when the touch screen or cover plate is assembled.		Minor Defect	OK
5	Color and Luminance	Item	Method	Instrument	Median	Tolerance Range
		Color	x, y Color Coordinate	Optical Instrument BM-7	According to the actual test on the sample confirmed by the customer.	± 0.04
		Luminance	Average the brightness EV at 9 points	Optical Instrument BM-7	According to the actual test on the sample confirmed by the customer.	$\pm 20\%$
6	Other Standards	Subject to the negotiation by both parties.				
7	Warranty Period	One year after sale.				



8	Guarantee	ROHS、REACH
9	Websites	

6. Reliability Test

Item	Condition	Result Determination
High-Temperature Storage	70°C 96H	After the test, leave the LCD samples indoors at normal temperature and humidity for 2H for function and appearance inspection. The sample should meet the requirements on electrical performance, but be free from the following defects: 1. Air bubble in the module, 2. No display, 3. Glass crack.
Low-Temperature Storage	-30°C 96H	
High-Temperature Operation	60°C 96H	
Low-Temperature Operation	-20°C 96H	
High-Temperature and High-Humidity	50°C 90%RH 96H	
Thermal shock	-20°C/0.5H ~ +60°C/0.5H 50 cycles in total	
Vibration Test	Frequency: 10Hz ~ 55Hz ~ 10Hz Amplitude: 0.75mm Cycle once a minute, 30 cycles in total (Packing Condition)	
ESD Test	±4kV Human Body Mode 150pF/330Ω ±8kV Air Mode 150pF/330Ω	

Note:

- 1) Each module under test can only be used for one of the test items.
- 2) The quantity of samples for each test item is 2.



- 3) Fault Judgment Criterion: Basic Specifications, Electrical Specifications, Mechanical Specifications, Optical Specifications.

7. Precautions

- 7.1. The display screen consists of glass and polarizer. Since the glass is fragile, the user must pay special attention to the edge area, and protect it from falling, vibration, or mechanical impact.
- 7.2. If the display screen is damaged and the liquid crystal material leaks, be sure not to get any in the mouth. If the liquid crystal material contacts the skin or clothes, flush off with soap and water.
- 7.3. Do not apply excessive force to the display screen or the joint part, or the color will change. Do not touch the display screen with bare hands, which will stain the display area and degraded insulation between terminals (some of the appearance is determined by the polarizer).
- 7.4. The polarizer covering the display panel of the LCD module is soft and easy to be scratched, be sure to handle carefully. Do not touch, impact, press, or rub the exposed polarizers with anything harder than an HB pencil lead (e.g.: glass, tweezers, etc.). Do not place or attach anything onto the display area to avoid leaving marks. The condensed material on the surface or terminals due to cold will damage or stain the polarizer. After the test in low temperature environment, the product must be warmed up in a container before put into the room temperature environment.
- 7.5. If the display panel is stained, blow warm air onto the surface and gently wipe it with a soft and dry cloth. If it is seriously contaminated, wipe it with a wet cloth dipped in one of the following solvents:
- glycerol
 - ethyl Alcohol
- Do not scrub, and avoid damaging the display panel.
- 7.6. Solvents other than those mentioned above may damage the polarizer. In particular, never use any of the following solvents:
- water
 - ketone
 - arene
- Wipe off saliva or water drop immediately, the contact with water over a long period of time may cause deformation or color fading. Avoid contact with oil or grease.
- 7.7. Special note: minimize electrode corrosion. Because electrode corrosion can be accelerated by water droplets, condensation of humidity, or electrification in a high humidity environment.
- 7.8. Assemble the LCD Module by the mounting holes. Make sure the LCD module make sure there is no



bending, distortion, or deformation. Do not forcibly pull or bend the transmission wire or the backlight wire.

- 7.9. Do not disassemble the LCD module.
- 7.10. NC terminal should be disconnected. Do not connect any device.
- 7.11. If the logic circuit power supply is off, do not send the input signal.
- 7.12. Since the LCD module is integrated with CMOS, pay special attention to the modules. To prevent electrostatic damage, be careful to maintain a suitable work environment.
 - Make sure the module has the same potential as the human body before take the LCD module out of the packing box for assembly. The reliable grounding is necessary during module processing.
 - The required tool, such as the electric soldering iron, must be reliably grounded. Make sure it is connected to AC power supply, and no electric leakage. When fixing the module with electric screwdriver, it must be grounded, to reduce the electromagnetic wave generated by the electric commutator spark as much as possible.
 - Do not assemble or operate under dry condition to reduce the static electricity. To reduce static electricity, the workplace must not be too dry. The recommended relative humidity is 50 - 60%. Keep your work clothes and work table grounded as much as possible
 - The LCD module is coated with a film to protect the display surface. Be careful when peeling off the film to reduce the generated static electricity.
- 7.13. Since the LCD module has high precision assembly and regulation, try to avoid excessive impact on the module or making any changes:
 - Do not change the shape of the tab on the metal frame.
 - Do not drill any extra hole, modify the shape, or change the position of component on the printed circuit board.
 - Do not change or damage the pattern on the printed circuit board.
 - Never modify the zebra strip (conductive rubber) or heat seal connector.
 - Do not make any change with the electric soldering iron except for the joint.
 - Do not throw, bend or twist.



8. Storage

8.1. Storage Method

Store in an ambient temperature of $23\pm5^{\circ}\text{C}$, and in a relative humidity of $60\pm15\%$. The storage period should not exceed 12 months. Do not expose to the sun for a long period of time.

8.1.1. Store in clean environment, free from dust, active gas, or solvent.

8.1.2. Store in anti-static environment.

