

INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support

Obsolescence Management

PCAP

Embedded Systems

Human Machine Interface

Touch Solutions

Software

Quality Management

Open Frame Monitors

LCD Controller

Research & Development

Firmware

EMC tests

on-site service

Optical Bonding

In-house Manufacturing

Cover glass

System solutions

OEM Solutions

Custom Display

Production Custom designs Installation

Mechanical design



Project No. 项目编号	ET101WU15-TT
Customer 客户名称	
Module No. 客户型号	
Product type 产品内容	Standard LCD Module TFT: 1920*RGBx1200Dots 10.1" TFT LCD+CTP

客户确认Customer Approval

项目负责人Project Manager	
品质主管Director of Quality	
采购工程师Purchasing Engineer	

PREPARED BY	CHECKED BY	APPROVED BY



1. Introduction

1.1 Scope of application

This specification applies to the LCD module that is supplied by YOURITECH Technology CO., LTD.

LCD specification: Dots 1920xRGBx1200

As to basic specification of the driver IC, refer to the IC (TBD) specification and data book.

All material & processing of the LCD module should be Lead Free.

1.2 TFT features:

Structure: TFT PANNEL+IC +FPC+BL+CTP;

ALL Viewing Type LCD

1920 dot-segment and 1200 dot-common outputs;

16.7M Color can be selected by software;

White LED back light;

LVDS(two port) interface



2. LCM General specification

ITEM	Standard value	Unit
LCD Type	Normally Black	--
Drive element	TFT active matrix	--
Number of pixels	1920*3RGB(H)X1200(V)	Dots
Pixel arrangement	RGB Vertical Stripe	--
Pixel Pitch (W*H)	0.11292(H) X 0.11292(V)	mm
Active area	216.81(H) x135.50(V)	mm
Viewing direction	ALL O'CLOCK	-
TFT Driver IC	TBD	
TFT interface	LVDS(two port) interface	-
Approx. Weight	TBD	g
LCM Size(W*H*T)	229.10(W) ×148.90(H) ×4.25(T)	mm
LCM+CTP Size(W*H*T)	247.56(W) ×166.20(H) ×6.36(T)	mm
Touch structure	G+G	
Touch Driver IC	GT9271	-
Touch Interface	I2C	





3.Absolute Maximum Rating

Characteristics	Symbol	Min.	Max.	Unit
LCM Operating Temperature	T _{OPR}	-20	+70	°C
LCM Storage Temperature	T _{STG}	-30	+80	°C
TP Operating Temperature & Humidity (20% ~ 90%RH)	T _{OPR}	-20	+70	°C
TP SStorage Temperature & Humidity (20% ~ 90%RH)	T _{STG}	-30	+80	°C
Humidity	RH	-	90	%

4.Electrical Characteristics

4.1 TFT DC Characteristics

Characteristics	Symbol	Min.	Typ.	Max.	Unit
Supply Voltage for(DC/DC)	VDD	3.0	3.3	3.3	V

4.2 Back-Light Unit Characeristics


The back-light system is an edge-lighting type with 36 white LEDs. The characteristics of the back-light are shown in the following tables.

Characteristics	Symbol	Min.	Type	Max.	Unit	Notes
Forward Voltage	V _F	16.8	--	19.2	V	-
Forward current	I _F	--	300	--	mA	-
Luminance(With LCD+CTP)	L _v	--	1000	--	cd/m ²	-
LED life time	N/A	----	30,000	--	Hr	Note 1

Note:

- (1) The “LED life time” is defined as the module brightness decrease to 50% of original brightness at I_L=20mA/LED. The LED life time could be decreased if operating I_L is larger than 25mA/LED.

Backlight circuit diagram shown in below:



5. Module Function Description

LCM Functional

Pin No.	Symbol	Description	I/O
1	VLED-	LED Cathode	P
2	VLED-	LED Cathode	P
3	VLED+	LED Anode	P
4	VLED+	LED Anode	P
5	NC	NC	-
6	GND	GROUND	P
7	ELV3P	EVEN LVDS Positive data signal (+)	I
8	ELV3N	EVEN LVDS Negative data signal (-)	I
9	GND	GROUND	P
10	ELV2P	EVEN LVDS Positive data signal (+)	I
11	ELV2N	EVEN LVDS Negative data signal (-)	I
12	GND	GROUND	P
13	ELVCLKP	EVEN LVDS Positive CLK signal (+)	I
14	ELVCLKN	EVEN LVDS Negative CLK signal (-)	I
15	GND	GROUND	P
16	ELV1P	EVEN LVDS Positive data signal (+)	I
17	ELV1N	EVEN LVDS Negative data signal (-)	I
18	GND	GROUND	P
19	ELV0P	EVEN LVDS Positive data signal (+)	I
20	ELV0N	EVEN LVDS Negative data signal (-)	I



Pin No.	Symbol	Description	I/O
21	GND	GROUND	P
22	OLV3P	Odd LVDS Positive data signal (+)	I
23	OLV3N	Odd LVDS Negative data signal (-)	I
24	GND	GROUND	P
25	OLV2P	Odd LVDS Positive data signal (+)	I
26	OLV2N	Odd LVDS Negative data signal (-)	I
27	GND	GROUND	P
28	OLVCLKP	Odd LVDS Positive CLK signal (+)	I
29	OLVCLKN	Odd LVDS Negative CLK signal (-)	I
30	GND	GROUND	P
31	OLV1P	Odd LVDS Positive data signal (+)	I
32	OLV1N	Odd LVDS Negative data signal (-)	I
33	GND	GROUND	P
34	OLV0P	Odd LVDS Positive data signal (+)	I
35	OLV0N	Odd LVDS Negative data signal (-)	I
36	GND	GROUND	P
37	I2C_SDA	Reserved for LCD manufacturer' s use , not connection	I
38	I2C_SCL		I
39	VDD_OTP		P
40	EEPEN	Not Connection	I
41	VDDIN	Power supply VDDIN=3.3V (Typ.)	P
42	VDDIN		P
43	VDDIN		P
44	VDDIN		P
45	VDDIN		P

CTP PIN Description:

Pin No.	Symbol	CTP Functional	Notes
1	GND	Power Ground	
2	CTP_INT 3.3V	Interrupt signal	
3	CTP_VCC 3.3V	Touch panel Power supply	
4	CTP_SCL 3.3V	Touch panel I2C clock	
5	CTP_SDA 3.3V	Touch panel I2C data	
6	CTP_RST 3.3V	Touch panel reset	



6. Timing Characteristics

6.1 8Bit LVDS input




Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK Frequency	Fdclk	74.5	77.56	85	MHz
Horizontal display area	Thd	960			DCLK
HSYNC period time	Th	989	1040	1248	DCLK
Horizontal Blank	THB	29	80	288	DCLK
HSYNC pulse width	Thp	2	10	255	DCLK
HSYNC back porch	thbp	3	6	255	DCLK
HSYNC Front porch	thfp	24	64	260	DCLK
Vertical display area	Tvd	1200			H
VSYNC period time	Tv	1243	1243	1560	H
Vertical Blank	TVB	43	43	360	H
VSYNC Pluse width	Tvp	4	4	20	H
VSYNC back porch	Tvbp	20	20	255	H
VSYNC front porch	Tvfp	19	19	260	H
Frequency	fV	-	60	-	Hz




6.2 Interface Timing

Item	Symbol	Condition	MIN	TYP	MAX	Unit
Differential input high Threshold voltage	Vth	Vcm=1.2V	-	-	+0.1	V
Differential input low Threshold voltage	Vtl	-	-0.1	-	-	V
Differential input common Threshold voltage	Vcm	-	1	1.2	1.7- Vid /2	V
LVDS input voltage	Vinlv	-	0.7	-	1.7	V
Differential input voltage	Vid	-	0.35	-	0.6	V
Differential input leakage voltage	Ilvleak	-	-10	-	+10	uA

Differential:
LVCLKP(R)-LVCLKN(R)
LVD[3:0]P(R)-
LVD[3:0]N(R)




6.3 Power On/Off Sequence



< Table8. Sequence Table >

Parameter	Values			Units
	Min	Typ	Max	
T1	0	-	10	ms
T2	0	-	50	ms
T3	200	-	-	ms
T4	500	-	-	ms
T5	0	-	50	ms
T6	0	-	10	ms
T7	500	-	-	ms



7. Optical Characteristics


7.1 Optical Specification

Item	Symbol	Condition	Min	Typ.	Max	Unit	Note
Transmittance (center)			-	5.5	-	%	
整机BLU brightness	Lv		-	-	-	nit	
Viewing Angle	θ_L	$Cr \geq 10$	75	80	--	deg	Note 1
	θ_R		75	80	--		
	ψ_T		75	80	--		
	ψ_B		75	80	--		
Contrast Ratio	Cr	$\theta = 0^\circ$ FF = 0°	800	1000	--	-	Note 2
Response Time	Tr+Tf		-	30	35	ms	Note 3
Color Coordinate of CIE1931	Rx	$\theta = 0^\circ$	-	-	-	-	Note 4
	Ry		-	-	-		
	Gx		-	-	-		
	Gy		-	-	-		
	Bx		-	-	-		
	By		-	-	-		
	Wx		-	-	-		
	Wy		-	-	-		
NTSC Ratio	NTSC	CIE1931	67	72	--	%	Note 5
Gamma Scale			2.0	2.2	2.4		



Note 1: The definition of Viewing Angle

Refer to the graph below marked by θ and ϕ .




Note 2: The definition of Contrast Ratio (Test LCM using CS2000 or similar equipments):

$$\text{Contrast Ratio (CR)} = \frac{\text{Luminance When LCD is at "White" state}}{\text{Luminance When LCD is at "Black" state}}$$

(Contrast Ratio is measured in optimum common electrode voltage)

Note 3: Definition of Response time. (Test LCD using DMS501 or similar equipments):

The output signal also photo detector are measured when the input signal also are changed from "black" to "white" (Voltage falling time) and from "white" to "black" (Voltage rising time), respectively. The response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figures below.



Measured Response Time	0	10	20	47	60	70	80	100	120	140	160	170	180	200	220	240	260
Start	0	10	20	47	60	70	80	100	120	140	160	170	180	200	220	240	260

Response time of gray to gray:

Response time T_g is the average time required for display transition by switching the input signal as below table and is based on Frame rate $f_v = 60\text{Hz}$ to optimize. Each time in below table is defined as Figure 2 and shall be measured by switching the signals for "any level of gray (bright)" and any level of gray (dark).

5. The output signals of photodetector are measured when the input signals are changed from "Lx" to "Ly", $x, y = [0, 7]$. The response time is defined as the time interval between the 10% and 90% of amplitudes. The result of the test can be noted as below:



Note 4: Color Coordinates of CIE 1931


The test condition is at ILED=100mA and measured on the surface of LCD module at 25°C.

Measurement equipment: CS2000 or similar equipments

The Color Coordinate (CIE 1931) is the measurement of the center of the display shown in below figure.

Note 5: Definition of Color of CIE Coordinate and NTSC Ratio.

$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$



8. Reliability Test Item

No.	Test Item	Test Condition	Notes
1	High Temp. Storage	+80°C / 96H	1. Functional test isOK. Missing Segment,short, unclear segment non-display,display abnormally and liquid crystal leakare un-allowed. 2. No low temperature bubbles,end seal loose andfall, frame rainbow.
2	Low Temp. Storage	-30°C / 96H	
3	High Tempe. Operating	+70°C / 96H	
4	Low Tempe. Operating	-20°C / 96H	
5	High Temperature /Humidity storage	60°C x 90%RH /96H	
6	Thermal and cold shock	Static state, -20°C (30min) ~70°C (30min), 10 cycles	

9. Packing Method----TBD

- END -

