


# INDUSTRIAL STRENGTH... Start Your Application From YOURITECH

Integration support  
Obsolescence Management  
Embedded Systems  
Human Machine Interface  
Touch Solutions  
Software  
Quality Management  
Open Frame Monitors  
Research & Development  
EMC tests  
on-site service  
In-house Manufacturing  
Cover glass  
OEM Solutions  
Custom Display  
Firmware  
LCD Controller  
Mechanical design  
PCAP  
Production Custom designs Installation





FOR MESSRS : \_\_\_\_\_

DATE : Mar. 1<sup>st</sup>, 2023

## CUSTOMER'S ACCEPTANCE SPECIFICATIONS

### TX20D200VM2BVA

#### Contents

| No. | ITEM                       | SHEET No.                    | PAGE       |
|-----|----------------------------|------------------------------|------------|
| 1   | COVER                      | 7B64PS 2701-TX20D200VM2BVA-2 | 1-1/1      |
| 2   | RECORD OF REVISION         | 7B64PS 2702-TX20D200VM2BVA-2 | 2-1/1      |
| 3   | GENERAL DATA               | 7B64PS 2703-TX20D200VM2BVA-2 | 3-1/1      |
| 4   | ABSOLUTE MAXIMUM RATINGS   | 7B64PS 2704-TX20D200VM2BVA-2 | 4-1/1      |
| 5   | ELECTRICAL CHARACTERISTICS | 7B64PS 2705-TX20D200VM2BVA-2 | 5-1/2~2/2  |
| 6   | OPTICAL CHARACTERISTICS    | 7B64PS 2706-TX20D200VM2BVA-2 | 6-1/2~2/2  |
| 7   | BLOCK DIAGRAM              | 7B64PS 2707-TX20D200VM2BVA-2 | 7-1/1      |
| 8   | RELIABILITY TESTS          | 7B64PS 2708-TX20D200VM2BVA-2 | 8-1/1      |
| 9   | LCD INTERFACE              | 7B64PS 2709-TX20D200VM2BVA-2 | 9-1/7~7/7  |
| 10  | OUTLINE DIMENSIONS         | 7B64PS 2710-TX20D200VM2BVA-2 | 10-1/2~2/2 |
| 11  | TOUCH PANEL                | 7B64PS 2711-TX20D200VM2BVA-2 | 11-1/1     |
| 12  | APPEARANCE STANDARD        | 7B64PS 2712-TX20D200VM2BVA-2 | 12-1/4~4/4 |
| 13  | PRECAUTIONS                | 7B64PS 2713-TX20D200VM2BVA-2 | 13-1/2~2/2 |
| 14  | DESIGNATION OF LOT MARK    | 7B64PS 2714-TX20D200VM2BVA-2 | 14-1/1     |

ACCEPTED BY: \_\_\_\_\_

PROPOSED BY: Oblack Tsai

|                                  |           |                              |      |       |
|----------------------------------|-----------|------------------------------|------|-------|
| JDI Taiwan Inc. Kaohsiung Branch | SHEET NO. | 7B64PS 2701-TX20D200VM2BVA-2 | PAGE | 1-1/1 |
|----------------------------------|-----------|------------------------------|------|-------|

## 2. RECORD OF REVISION

| DATE       | SHEET No.                                   | SUMMARY                                                                                                                                                                                           |
|------------|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mar.01,'23 | 7B64PS 2701-TX20D200VM2BVA-2<br>Page 1-1/1  | Company logo changed :<br> →  |
|            | 7B64PS 2714-TX20D200VM2BVA-2<br>Page 14-1/1 |                                                                                                                                                                                                   |
|            | All page                                    | Company name changed:<br>From "JDI Taiwan Inc. Kaohsiung Branch"<br>to "JDI Taiwan Inc. Kaohsiung Branch"                                                                                         |
|            |                                             |                                                                                                                                                                                                   |

## 3. GENERAL DATA

### 3.1 DISPLAY FEATURES

This module is a 8.0" WVGA of 16:9 format amorphous silicon TFT. The pixel format is vertical stripe and sub pixels are arranged as R(red), G(green), B(blue) sequentially. This display is RoHS compliant, and COG (chip on glass) technology and LED backlight are applied on this display.

|                         |                                                                                                          |
|-------------------------|----------------------------------------------------------------------------------------------------------|
| Part Name               | TX20D200VM2BVA                                                                                           |
| Module Dimensions       | 200.0(W) mm x 124.0(H) mm x 13.08 (D) mm                                                                 |
| LCD Active Area         | 174.0(W) mm x104.4(H) mm                                                                                 |
| Pixel Pitch             | 0.2175(W) mm x 0.2175 (H) mm                                                                             |
| Resolution              | 800 x 3(RGB)(W) x 480(H) Dots                                                                            |
| Color Pixel Arrangement | R, G, B Vertical Stripe                                                                                  |
| LCD Type                | Transmissive Color TFT; Normally White                                                                   |
| Display Type            | Active Matrix                                                                                            |
| Number of Colors        | 262k Colors (6-bit RGB)                                                                                  |
| Backlight               | Light Emitting Diode (LED)                                                                               |
| Weight                  | 352 g                                                                                                    |
| Interface               | LVDS; 20 pins                                                                                            |
| Power Supply Voltage    | 3.3V for LCD; 12.0V for backlight.                                                                       |
| Power Consumption       | 0.89W for LCD; 4.92W for backlight.                                                                      |
| Viewing Direction       | 12 O'clock (without image inversion and least brightness change)<br>6 O'clock (contrast peak located at) |
| Touch Panel             | Projected Capacitive type ; Cover Glass on ITO Film                                                      |

## 4. ABSOLUTE MAXIMUM RATINGS

| Item                    | Symbol           | Min. | Max. | Unit | Remarks |
|-------------------------|------------------|------|------|------|---------|
| Supply Voltage          | V <sub>DD</sub>  | -0.5 | 5.0  | V    | -       |
| Input Voltage of Logic  | V <sub>I</sub>   | -0.5 | 5.0  | V    | Note 1  |
| Operating Temperature   | T <sub>op</sub>  | -30  | 80   | °C   | Note 2  |
| Storage Temperature     | T <sub>st</sub>  | -30  | 80   | °C   | Note 2  |
| Backlight Input Voltage | V <sub>LED</sub> | -    | 15   | V    | -       |

Note 1: The rating is defined for the signal voltages of the interface such as CLK and pixel data pairs.

Note 2: The maximum rating is defined as above based on the chamber temperature, which might be different from ambient temperature after assembling the panel into the application. Moreover, some temperature-related phenomenon as below needed to be noticed:

- Background color, contrast and response time would be different in temperatures other than 25°C.
- Operating under high temperature will shorten LED lifetime.


## 5. ELECTRICAL CHARACTERISTICS

### 5.1 LCD CHARACTERISTICS

$T_a = 25\text{ }^{\circ}\text{C}$ ,  $V_{SS} = 0\text{V}$

| Item                                                   | Symbol      | Condition                     | Min. | Typ. | Max. | Unit | Remarks  |
|--------------------------------------------------------|-------------|-------------------------------|------|------|------|------|----------|
| Power Supply Voltage                                   | $V_{DD}$    | -                             | 3.0  | 3.3  | 3.6  | V    | -        |
| Differential Input Voltage for LVDS Receiver Threshold | $V_I$       | $V_{IH}$                      | -    | -    | +100 | mV   | Note 1   |
|                                                        |             | $V_{IL}$                      | -100 | -    | -    |      |          |
| Power Supply Current                                   | $I_{DD}$    | $V_{DD}-V_{SS} = 3.3\text{V}$ | -    | 270  | 377  | mA   | Note 2,3 |
| Frame Frequency                                        | $f_{Frame}$ | -                             | -    | 60   | 66   | Hz   | -        |
| CLK Frequency                                          | $f_{CLK}$   | -                             | 25   | 33.3 | 40   | MHz  |          |

Note 1: VCM 1.2V is common mode voltage of LVDS transmitter and receiver. The input terminal of LVDS receiver is terminated with  $100\Omega$ .



Note 2: An all black check pattern is used when measuring  $I_{DD}$ .  $f_{Frame}$  is set to 60Hz.

Note 3: 0.63A fuse is applied in the module for  $I_{DD}$ . For display activation and protection purpose, power supply is recommended larger than 1.6A to start the display and break fuse once any short circuit occurred.

## 5.2 BACKLIGHT CHARACTERISTICS

$T_a = 25\text{ }^{\circ}\text{C}$

| Item                | Symbol    | Condition               | Min. | Typ. | Max. | Unit | Remarks |
|---------------------|-----------|-------------------------|------|------|------|------|---------|
| LED Input Voltage   | $V_{LED}$ | -                       | 11.0 | 12.0 | 13.0 | V    | Note1   |
| LED Forward Current | $I_{LED}$ | 0V; 0% duty             | 360  | 410  | 460  | mA   | Note 2  |
|                     |           | 3.3VDC; 100% duty       | 30   | 40   | 50   |      |         |
| LED lifetime        | -         | $I_{LED}=410\text{ mA}$ | -    | 70K  | -    | hrs  | Note 3  |

Note 1: As Fig. 5.1 shown, LED current is constant, 410 mA, controlled by the LED driver when applying 12V  $V_{LED}$ .

Note 2: Dimming function can be obtained by applying DC voltage or PWM signal from the display interface CN1. The recommended PWM signal is 1K ~ 10K Hz with 3.3V amplitude.

Note 3: The estimated lifetime is specified as the time to reduce 50% brightness by applying 410 mA at 25°C.




Fig 5.1

## 6. OPTICAL CHARACTERISTICS

The optical characteristics are measured based on the conditions as below:

- Supplying the signals and voltages defined in the section of electrical characteristics.
- The ambient temperature is 25 °C .
- In the dark room less than 100 lx, the equipment has been set for the measurements as shown in Fig 6.1.

$T_a = 25\text{ }^{\circ}\text{C}$ ,  $f_{Frame} = 60\text{ Hz}$ ,  $V_{DD} = 3.3\text{ V}$

| Item                                |       | Symbol        | Condition                                                           | Min. | Typ. | Max. | Unit            | Remarks |
|-------------------------------------|-------|---------------|---------------------------------------------------------------------|------|------|------|-----------------|---------|
| Brightness of White                 |       | -             | $I_{LED} = 410\text{ mA}$<br>$\phi = 0^{\circ}, \theta = 0^{\circ}$ | 1000 | 1300 | -    | $\text{cd/m}^2$ | Note 1  |
| Brightness Uniformity               |       | -             |                                                                     | 70   | -    | -    | %               | Note 2  |
| Contrast Ratio                      |       | CR            |                                                                     | 400  | 800  | -    | -               | Note 3  |
| Response Time<br>(Rising + Falling) |       | $T_r + T_f$   | $\phi = 0^{\circ}, \theta = 0^{\circ}$                              | -    | 20   | -    | ms              | Note 4  |
| NTSC Ratio                          |       | -             | $\phi = 0^{\circ}, \theta = 0^{\circ}$                              | -    | 60   | -    | %               | -       |
| Viewing Angle                       |       | $\theta_x$    | $\phi = 0^{\circ}, CR \geq 10$                                      | 60   | 80   | -    | Degree          | Note 5  |
|                                     |       | $\theta_{x'}$ | $\phi = 180^{\circ}, CR \geq 10$                                    | 60   | 80   | -    |                 |         |
|                                     |       | $\theta_y$    | $\phi = 90^{\circ}, CR \geq 10$                                     | 50   | 60   | -    |                 |         |
|                                     |       | $\theta_{y'}$ | $\phi = 270^{\circ}, CR \geq 10$                                    | 70   | 80   | -    |                 |         |
| Color Chromaticity                  | Red   | X             | $\phi = 0^{\circ}, \theta = 0^{\circ}$                              | 0.59 | 0.64 | 0.69 | -               | Note 6  |
|                                     |       | Y             |                                                                     | 0.29 | 0.34 | 0.39 |                 |         |
|                                     | Green | X             |                                                                     | 0.31 | 0.36 | 0.41 |                 |         |
|                                     |       | Y             |                                                                     | 0.53 | 0.58 | 0.63 |                 |         |
|                                     | Blue  | X             |                                                                     | 0.09 | 0.14 | 0.19 |                 |         |
|                                     |       | Y             |                                                                     | 0.05 | 0.10 | 0.15 |                 |         |
|                                     | White | X             |                                                                     | 0.26 | 0.31 | 0.36 |                 |         |
|                                     |       | Y             |                                                                     | 0.29 | 0.34 | 0.39 |                 |         |

Note 1: The brightness is measured from 9 point average value of the panel, P5 in Fig. 6.2, for the typical value.

Note 2: The brightness uniformity is calculated by the equation as below:

$$\text{Brightness uniformity} = \frac{\text{Min. Brightness}}{\text{Max. Brightness}} \times 100\%$$

which is based on the brightness values of the 9 points measured by BM-5 as shown in Fig. 6.2.




Fig. 6.1




Fig. 6.2

Note 3: The Contrast ratio is measured from the center point of the panel, P5, and defined as the following equation:

$$CR = \frac{\text{Brightness of White}}{\text{Brightness of Black}}$$

Note 4: The definition of response time is shown in Fig. 6.3. The rising time is the period from 90% brightness to 10% brightness when the data is from white to black. Oppositely, falling time is the period from 10% brightness rising to 90% brightness.




Fig 6.3

Note 5: The definition of viewing angle is shown in Fig. 6.4. Angle  $\phi$  is used to represent viewing directions, for instance,  $\phi = 270^\circ$  means 6 o'clock, and  $\phi = 0^\circ$  means 3 o'clock. Moreover, angle  $\theta$  is used to represent viewing angles from axis Z toward plane XY.

The display is super wide viewing angle version, so that the best optical performance can be obtained from every viewing direction.





Fig 6.4

Note 6: The color chromaticity is measured from the center point of the panel, P5, as shown in Fig. 6.2.

## 7. BLOCK DIAGRAM



Note : Signals are CLK and pixel data pairs.

## 8. RELIABILITY TESTS

| Test Item                   | Condition                                                                                                                 |                                                            |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|
| High Temperature            | 1) Operating<br>2) 80 °C                                                                                                  | 240 hrs                                                    |
| Low Temperature             | 1) Operating<br>2) -30 °C                                                                                                 | 240 hrs                                                    |
| High Temperature            | 1) Storage<br>2) 80 °C                                                                                                    | 240 hrs                                                    |
| Low Temperature             | 1) Storage<br>2) -30 °C                                                                                                   | 240 hrs                                                    |
| Heat Cycle                  | 1) Operating<br>2) -20 °C ~70 °C<br>3) 3hrs~1hr~3hrs                                                                      | 240 hrs                                                    |
| Thermal Shock               | 1) Non-Operating<br>2) -35 °C ↔ 85 °C<br>3) 0.5 hr ↔ 0.5 hr                                                               | 240 hrs                                                    |
| High Temperature & Humidity | 1) Operating<br>2) 40 °C & 85%RH<br>3) Without condensation                                                               | 240 hrs<br>(Note 3)                                        |
| Vibration                   | 1) Non-Operating<br>2) 20~200 Hz<br>3) 2G<br>4) X, Y, and Z directions                                                    | 1 hr for each direction                                    |
| Mechanical Shock            | 1) Non-Operating<br>2) 10 ms<br>3) 50G<br>4) ±X, ±Y and ±Z directions                                                     | Once for each direction                                    |
| ESD                         | 1) Operating<br>2) Tip: 150 pF, 330 Ω<br>3) Air discharge for glass: ± 8KV<br>4) Contact discharge for metal frame: ± 8KV | 1) Glass: 9 points<br>2) Metal frame: 8 points<br>(Note 4) |

Note 1: Display functionalities are inspected under the conditions defined in the specification after the reliability tests.

Note 2: The display is not guaranteed for use in corrosive gas environments.

Note 3: Under the condition of high temperature & humidity, if the temperature is higher than 40°C, the humidity needs to be reduced as Fig. 8.1 shown.




Fig. 8.1

Note 4: All pins of LCD interface (CN1) have been tested by ± 100V contact discharge of ESD under non-operating condition.

## 9. LCD INTERFACE

### 9.1 INTERFACE PIN CONNECTIONS

The display interface connector CN1 is FI-SEB20P-HF13E made by JAE and pin assignment is as below:

| Pin No. | Signal          | Signal                 | Pin No. | Signal          | Signal        |
|---------|-----------------|------------------------|---------|-----------------|---------------|
| 1       | V <sub>DD</sub> | Power Supply for Logic | 11      | IN2-            | B2~B5, DE     |
| 2       | V <sub>DD</sub> |                        | 12      | IN2+            |               |
| 3       | V <sub>SS</sub> | GND                    | 13      | V <sub>SS</sub> | GND           |
| 4       | V <sub>SS</sub> |                        | 14      | CLK IN-         | Pixel Clock   |
| 5       | IN0-            | R0~R5, G0              | 15      | CLK IN+         |               |
| 6       | IN0+            |                        | 16      | V <sub>SS</sub> | GND           |
| 7       | V <sub>SS</sub> | GND                    | 17      | NC              | No Connection |
| 8       | IN1-            | G1~G5, B0~B1           | 18      | NC              | No Connection |
| 9       | IN1+            |                        | 19      | NC              | No Connection |
| 10      | V <sub>SS</sub> | GND                    | 20      | DIM             | Note 2        |

Note 1: IN n- and IN n+ (n=0, 1, 2), CLK IN- and CLK IN+ should be wired by twist-pairs or side-by-side FPC patterns, respectively.

Note 2: Normal brightness: 0V or 0% PWM duty; Brightness control: 0V to 3.3V DC or 0% to 100% PWM duty.

The backlight interface connector CN2 is SM02(8.0)B-BHS-1-TB made by JST, and pin assignment is as below:


| Pin No. | Signal            | Level | Function             |
|---------|-------------------|-------|----------------------|
| 1       | V <sub>LED+</sub> | -     | Power Supply for LED |
| 2       | V <sub>LED-</sub> | -     | GND                  |

The capacitive touch panel interface FPC : Pitch 0.5mm 6pins

Pin assignment is as below :

| Pin No. | Signal          | Function                                         |
|---------|-----------------|--------------------------------------------------|
| 1       | V <sub>CC</sub> | Power Supply for PCAP                            |
| 2       | SCL             | Serial Clock Input                               |
| 3       | SDA             | Serial Data Input / Output                       |
| 4       | INT             | Inform Host to Get Finger Information Low Active |
| 5       | GND             | GND                                              |

## 9.2 LVDS INTERFACE




Note 1: LVDS cable impedance should be 100 ohms per signal line when each 2-lines (+, -) is used in differential mode.

Note 2: The recommended transmitter, THC63LVDM83R, is made by Thine or equivalent, which is not contained in the module.

Note 3: The receiver built-in the module is THC63LVDF84B .

## 9.3 LVDS DATA FORMAT



DE: Display Enable

NA: Not Available

## 9.4 TIMING CHART




Fig. 9.1 Horizontal Timing




Fig. 9.2 Vertical Timing




Fig. 9.3 Setup & Hold Time

## 9.5 TIMING TABLE

The column of timing sets including minimum, typical, and maximum as below are based on the best optical performance, frame frequency (Vsync) = 60 Hz to define. If 60 Hz is not the aim to set, less than 66 Hz for Vsync is recommended to apply for better performance by other parameter combination as the definitions in section 5.1.


### A. Horizontal and Vertical Timing

| Item       |               | Symbol | Min. | Typ. | Max. | Unit |
|------------|---------------|--------|------|------|------|------|
| Horizontal | CLK Frequency | fclk   | 25   | 33.3 | 40   | M Hz |
|            | Display Data  | thd    | 800  |      |      | CLK  |
|            | Cycle Time    | th     | 841  | 1056 | 1088 |      |
| Vertical   | Display Data  | tvd    | 480  |      |      | H    |
|            | Cycle Time    | tv     | 495  | 525  | 610  |      |

### B. Setup and Hold Time

| Item |            | Symbol | Min. | Typ. | Max. | Unit |
|------|------------|--------|------|------|------|------|
| CLK  | Duty       | Tcwh   | 40   | 50   | 60   | %    |
|      | Cycle Time | Tcph   | -    | 30   | -    | ns   |
| Data | Setup Time | Tdsu   | 5    | -    | -    |      |
|      | Hold Time  | Tdhd   | 5    | -    | -    |      |
| DE   | Setup Time | Tesu   | 5    | -    | -    |      |
|      | Hold Time  | Tehd   | 5    | -    | -    |      |

## 9.6 LVDS RECEIVER TIMING




$$R_{inX} = (R_{inX+}) - (R_{inX-}) \quad (X=0, 1, 2)$$

|                            | Item              | Symbol      | Min.                   | Typ.            | Max.                   | Unit |
|----------------------------|-------------------|-------------|------------------------|-----------------|------------------------|------|
| CLK                        | Cycle frequency   | $1/t_{CLK}$ | 25                     | 33.3            | 40                     | MHz  |
| $R_{inX}$<br>( $X=0,1,2$ ) | 0 data position   | $t_{RP0}$   | $1/7 * t_{CLK} - 0.49$ | $1/7 * t_{CLK}$ | $1/7 * t_{CLK} + 0.49$ | ns   |
|                            | 1st data position | $t_{RP1}$   | -0.49                  | 0               | +0.49                  |      |
|                            | 2nd data position | $t_{RP2}$   | $6/7 * t_{CLK} - 0.49$ | $6/7 * t_{CLK}$ | $6/7 * t_{CLK} + 0.49$ |      |
|                            | 3rd data position | $t_{RP3}$   | $5/7 * t_{CLK} - 0.49$ | $5/7 * t_{CLK}$ | $5/7 * t_{CLK} + 0.49$ |      |
|                            | 4th data position | $t_{RP4}$   | $4/7 * t_{CLK} - 0.49$ | $4/7 * t_{CLK}$ | $4/7 * t_{CLK} + 0.49$ |      |
|                            | 5th data position | $t_{RP5}$   | $3/7 * t_{CLK} - 0.49$ | $3/7 * t_{CLK}$ | $3/7 * t_{CLK} + 0.49$ |      |
|                            | 6th data position | $t_{RP6}$   | $2/7 * t_{CLK} - 0.49$ | $2/7 * t_{CLK}$ | $2/7 * t_{CLK} + 0.49$ |      |

## 9.7 DATA INPUT for DISPLAY COLOR

| Input color |            | Red Data |    |    |    |    |     | Green Data |    |    |    |    |     | Blue Data |    |    |    |    |     |
|-------------|------------|----------|----|----|----|----|-----|------------|----|----|----|----|-----|-----------|----|----|----|----|-----|
|             |            | R5       | R4 | R3 | R2 | R1 | R0  | G5         | G4 | G3 | G2 | G1 | G0  | B5        | B4 | B3 | B2 | B1 | B0  |
|             |            | MSB      |    |    |    |    | LSB | MSB        |    |    |    |    | LSB | MSB       |    |    |    |    | LSB |
| Basic Color | Black      | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Red(63)    | 1        | 1  | 1  | 1  | 1  | 1   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Green(63)  | 0        | 0  | 0  | 0  | 0  | 0   | 1          | 1  | 1  | 1  | 1  | 1   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Blue(63)   | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 1         | 1  | 1  | 1  | 1  | 1   |
|             | Cyan       | 0        | 0  | 0  | 0  | 0  | 0   | 1          | 1  | 1  | 1  | 1  | 1   | 1         | 1  | 1  | 1  | 1  | 1   |
|             | Magenta    | 1        | 1  | 1  | 1  | 1  | 1   | 0          | 0  | 0  | 0  | 0  | 0   | 1         | 1  | 1  | 1  | 1  | 1   |
|             | Yellow     | 1        | 1  | 1  | 1  | 1  | 1   | 1          | 1  | 1  | 1  | 1  | 1   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | White      | 1        | 1  | 1  | 1  | 1  | 1   | 1          | 1  | 1  | 1  | 1  | 1   | 1         | 1  | 1  | 1  | 1  | 1   |
| Red         | Black      | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Red (1)    | 0        | 0  | 0  | 0  | 0  | 1   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Red (2)    | 0        | 0  | 0  | 0  | 1  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | :          | :        | :  | :  | :  | :  | :   | :          | :  | :  | :  | :  | :   | :         | :  | :  | :  | :  | :   |
|             | :          | :        | :  | :  | :  | :  | :   | :          | :  | :  | :  | :  | :   | :         | :  | :  | :  | :  | :   |
|             | Red (62)   | 1        | 1  | 1  | 1  | 1  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Red (63)   | 1        | 1  | 1  | 1  | 1  | 1   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
| Green       | Black      | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Green (1)  | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 1   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Green (2)  | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 1  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | :          | :        | :  | :  | :  | :  | :   | :          | :  | :  | :  | :  | :   | :         | :  | :  | :  | :  | :   |
|             | :          | :        | :  | :  | :  | :  | :   | :          | :  | :  | :  | :  | :   | :         | :  | :  | :  | :  | :   |
|             | Green (62) | 0        | 0  | 0  | 0  | 0  | 0   | 1          | 1  | 1  | 1  | 1  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Green (63) | 0        | 0  | 0  | 0  | 0  | 0   | 1          | 1  | 1  | 1  | 1  | 1   | 0         | 0  | 0  | 0  | 0  | 0   |
| Blue        | Black      | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 0   |
|             | Blue (1)   | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 0  | 1   |
|             | Blue (2)   | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 0         | 0  | 0  | 0  | 1  | 0   |
|             | :          | :        | :  | :  | :  | :  | :   | :          | :  | :  | :  | :  | :   | :         | :  | :  | :  | :  | :   |
|             | :          | :        | :  | :  | :  | :  | :   | :          | :  | :  | :  | :  | :   | :         | :  | :  | :  | :  | :   |
|             | Blue (62)  | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 1         | 1  | 1  | 1  | 1  | 0   |
|             | Blue (63)  | 0        | 0  | 0  | 0  | 0  | 0   | 0          | 0  | 0  | 0  | 0  | 0   | 1         | 1  | 1  | 1  | 1  | 1   |

## 9.8 POWER SEQUENCE




Note 1: In order to avoid any damages,  $V_{DD}$  has to be applied before all other signals. The opposite is true for power off where  $V_{DD}$  has to be remained on until all other signals have been switch off. The recommended time period is 1 second. Hot plugging might cause display damage due to incorrect power sequence, please pay attention on interface connecting before power on.

Note 2: In order to avoid showing uncompleted patterns in transient state. It is recommended that switching the backlight on is delayed for 1 second after the signals have been applied. The opposite is true for power off where the backlight has to be switched off 1 second before the signals are removed.

10. OUTLINE DIMENSIONS


10.1 FRONT VIEW



|   |     |
|---|-----|
| 1 | VCC |
| 2 | SCL |
| 3 | SDA |
| 4 | INT |
| 5 | GND |

General Tolerance:  $\pm 0.5$ mm  
Scale : NTS  
Unit : mm

### 10.2 REAR VIEW



General Tolerance:  $\pm 0.5\text{mm}$   
Scale : NTS  
Unit : mm

## 11. TOUCH PANEL

The type of touch panel used on this display is capacitive touch panel film, and more characteristics are shown as below:

### 11.1 MECHANICAL CHARACTERISTICS

| Item              | Specification                      | Remarks               |
|-------------------|------------------------------------|-----------------------|
| Thickness         | $t = 2.2 \pm 0.2\text{mm}$         | -                     |
| Cover Glass       | $t = 1.8 \pm 0.3\text{mm}$         | Strengthened Glass    |
| Surface Hardness  | 7H                                 | -                     |
| Input Method      | Through a special stylus or finger | -                     |
| FPC Peeling Force | 700g                               | Peeling upward by 90° |
| Touch Panel       | 10 points                          | -                     |

### 11.2 ELECTRICAL CHARACTERISTICS

| Item                                      | Symbol       | Symbol                       | Value        |      |      | Unit | Remarks |
|-------------------------------------------|--------------|------------------------------|--------------|------|------|------|---------|
|                                           |              |                              | Min.         | Typ. | Max. |      |         |
| Power supply voltage                      | $V_{DD}$     | $V_{DD-GND}$                 | 3.0          | 3.3  | 3.6  | V    | -       |
| Power supply voltage for I <sup>2</sup> C | $V_{I^2C}$   | $V_{I^2C-GND}$               | -            | 3.3  | 5    | V    | -       |
| Operation Current                         | $I_{DD}$     | $V_{DD}=3.3V$                | -            | -    | 100  | mA   | -       |
| Idle Mode Current                         | $I_{idid}$   | $GND=0V$<br>$T_a=25^\circ C$ | -            | -    | 100  | mA   | -       |
| Input High Level Voltage                  | $V_{IH}$     | -                            | $V_{DD}-0.8$ | -    | -    | V    | -       |
| Input Low Level Voltage                   | $V_{IL}$     | -                            | -            | -    | 0.8  | V    | -       |
| Operating Frequency                       | $1/t_{clcl}$ | -                            | -            | 12   | -    | MHz  | -       |
| Operating High Level Voltage              | $V_{OH}$     | $I=2mA$                      | $V_{DD}-0.4$ | -    | -    | V    | -       |
| Operating Low Level Voltage               | $V_{OL}$     |                              | -            | -    | 0.4  | V    | -       |

### 11.3 CONTROLLER CHARACTERISTICS

The Capacitive Touch Panel features as below:

- Controller IC is EXC3146,
- Interface : I<sup>2</sup>C
- OS : Win7, Win8, Ubuntu Fedora Android(Version 2.3~)
- Firmware information:

Mode Name: SIRIUS\_4277

Type Name: PCAP3146I SERIES

Version: 00\_T1

## 12. APPEARANCE STANDARD

The appearance inspection is performed in a room around 500~1000 lx based on the conditions as below:

- The distance between inspector's eyes and display is 30 cm.
- The viewing zone is defined with angle  $\theta$  shown in Fig. 12.1 The inspection should be performed within  $45^\circ$  when display is shut down. The inspection should be performed within  $5^\circ$  when display is power on.




Fig. 12.1

### 12.1 THE DEFINITION OF LCD ZONE

LCD panel is divided into 2 areas as shown in Fig.12.2 for appearance specification in next section. A zone is the LCD active area (dot area); B zone is the area between A zone and metal frame.

In terms of housing design, B zone is the recommended window area customers' housing should be located in.




Fig. 12.2

## 12.2 LCD APPEARANCE SPECIFICATION

The specification as below is defined as the amount of unexpected phenomenon or material in different zones of LCD panel. The definitions of length, width and average diameter using in the table are shown in Fig. 12.4 and Fig. 12.5.

| Item                                              | Criteria                              |                |                |                | Applied zone |
|---------------------------------------------------|---------------------------------------|----------------|----------------|----------------|--------------|
| Scratches                                         | Length (mm)                           | Width (mm)     | Maximum number | Minimum space  | A            |
|                                                   | L ≤ 15                                | W ≤ 0.02       | Ignored        | -              |              |
|                                                   | L ≤ 15                                | 0.02 < W ≤ 0.1 | 5              | -              |              |
|                                                   | L > 15                                | 0.1 < W        | 0              | -              |              |
| Dent                                              | Serious one is not allowed            |                |                |                | A            |
| Wrinkles in polarizer                             | Serious one is not allowed            |                |                |                | A            |
| Bubbles on polarizer                              | Average diameter (mm)                 |                | Maximum number |                | A            |
|                                                   | D ≤ 0.3                               |                | Ignored        |                |              |
|                                                   | 0.3 < D ≤ 0.6                         |                | 4              |                |              |
|                                                   | 0.6 < D                               |                | 0              |                |              |
| 1) Stains<br>2) Foreign Materials<br>3) Dark Spot | Filamentous (Line shape)              |                |                |                | A            |
|                                                   | Length (mm)                           | Width (mm)     | Maximum number |                |              |
|                                                   | L ≤ 2.0                               | W ≤ 1.5        | 5              |                |              |
|                                                   | L > 2.0                               | 1.5 < W        | 0              |                |              |
|                                                   | Round (Dot shape)                     |                |                |                | A            |
|                                                   | Average diameter (mm)                 | Maximum number | Minimum Space  |                |              |
|                                                   | D ≤ 0.2                               | Ignored        | -              |                |              |
|                                                   | 0.2 < D ≤ 0.6                         | 4              | -              |                |              |
|                                                   | 0.6 < D                               | 0              | -              |                |              |
|                                                   | Those wiped out easily are acceptable |                |                |                |              |
| Dot-Defect<br>(Note 1,2)                          |                                       | Area①          | Area②          | Maximum number | A            |
|                                                   | Bright dot-defect                     | 1 dot          | 2 dot          | 3 dot          |              |
|                                                   | Dark dot-defect                       | 2 dot          | 3 dot          | 4 dot          |              |
|                                                   | Bright + Dark point                   | 3 dot          | 4 dot          | 5 dot          |              |

Note 1: The Dot-Defect inspection within A zone (active area) would be divided into area ①, ② as Fig. 12.3 shown.




Fig. 12.3




Fig 12.4




Fig 12.5

Note 2: The definitions of dot defect are as below:

- The defect area of the dot must be bigger than half of a dot.
- For bright dot-defect, showing black pattern, the dot's brightness must be over 30% brighter than others.
- For dark dot-defect, showing white pattern, the dot's brightness must be under 70% darker than others.

### 12.3 TOUCH PANEL APPEARANCE SPECIFICATION

The specification as below is defined by the amount of unexpected material in different zones of touch panel.

| Item                       | Criteria                 |             |                               | Applied zone |
|----------------------------|--------------------------|-------------|-------------------------------|--------------|
| Scratches                  | Width (mm)               | Length (mm) | Maximum number                | A            |
|                            | $W \leq 0.05$            | -           | Ignored                       |              |
|                            | $0.05 < W \leq 0.10$     | $L \leq 5$  | 3; 2-defect distance $> 5$ mm |              |
|                            | $0.10 < W$               | $L > 5$     | Not allowed                   |              |
| Foreign materials and spot | Round (Dot shape)        |             |                               | A            |
|                            | $D \leq 0.2$             |             | Ignored                       |              |
|                            | $0.2 < D \leq 0.4$       |             | 3; 2-defect distance $> 5$ mm |              |
|                            | $0.4 < D$                |             | Not allowed                   |              |
|                            | Filamentous (Line shape) |             |                               |              |
|                            | Width (mm)               | Length (mm) | Maximum number                |              |
|                            | $W \leq 0.03$            | -           | Ignored                       |              |
|                            | $0.03 < W \leq 0.10$     | $L \leq 4$  | 3; 2-defect distance $> 5$ mm |              |
|                            | $0.10 < W$               | $L > 4$     | Not allowed                   |              |
| Bubble                     | Round (Dot shape)        |             |                               | A            |
|                            | Average diameter (mm)    |             | Maximum number                |              |
|                            | $D \leq 0.15$            |             | Ignored                       |              |
|                            | $0.15 < D \leq 0.40$     |             | 3; 2-defect distance $> 5$ mm |              |
|                            | $0.40 < D$               |             | Not allowed                   |              |
| Pin hole on printing area  | $D \leq 0.2$             |             | Acceptable                    | B            |
|                            | $D > 0.2$                |             | Unacceptable                  |              |

The limitation of glass flaw occurred on touch panel is defined in the table as below.

| Item             | Specifications |                                                                                      |
|------------------|----------------|--------------------------------------------------------------------------------------|
| Edge flaw        |                | $X \leq 0.3 \text{ mm}$<br>$Y \leq 0.3 \text{ mm}$<br>$Z \leq 1/2 \text{ Thickness}$ |
| Corner flaw      |                | $X \leq 0.3 \text{ mm}$<br>$Y \leq 0.3 \text{ mm}$<br>$Z \leq 1/2 \text{ Thickness}$ |
| Progressive flaw |                | Not allowed                                                                          |

## 13. PRECAUTIONS

### 13.1 PRECAUTIONS of ESD

- 1) Before handling the display, please ensure your body has been connected to ground to avoid any damages by ESD. Also, do not touch display's interface directly when assembling.
- 2) Please remove the protection film very slowly before turning on the display to avoid generating ESD.

### 13.2 PRECAUTIONS of HANDLING

- 1) In order to keep the appearance of display in good condition; please do not rub any surfaces of the displays by sharp tools harder than 3H, especially touch panel, metal frame and polarizer.
- 2) Please do not pile the displays in order to avoid any scars leaving on the display. In order to avoid any injuries, please pay more attention for the edges of glasses and metal frame, and wear finger cots to protect yourself and the display before working on it.
- 3) Touching the display area or the terminal pins with bare hand is prohibited. This is because it will stain the display area and cause poor insulation between terminal pins, and might affect display's electrical characteristics furthermore.
- 4) Do not use any harmful chemicals such as acetone, toluene, and isopropyl alcohol to clean display's surfaces.
- 5) Please use soft cloth or absorbent cotton with ethanol to clean the display by gently wiping. Moreover, when wiping the display, please wipe it by horizontal or vertical direction instead of circling to prevent leaving scars on the display's surface, especially polarizer.
- 6) Please wipe any unknown liquids immediately such as saliva, water or dew on the display to avoid color fading or any permanently damages.
- 7) Maximum pressure to the surface of the display must be less than  $1.96 \times 10^4$  Pa. If the area of adding pressure is less than  $1 \text{ cm}^2$ , the maximum pressure must be less than 1.96N.

### 13.3 PRECAUTIONS OF OPERATING

- 1) Please input signals and voltages to the displays according to the values defined in the section of electrical characteristics to obtain the best performance. Any voltages over than absolute maximum rating will cause permanent damages to this display. Also, any timing of the signals out of this specification would cause unexpected performance.
- 2) When the display is operating at significant low temperature, the response time will be slower than it at  $25^\circ\text{C}$ . In high temperature, the color will be slightly dark and blue compared to original pattern. However, these are temperature-related phenomenon of LCD and it will not cause permanent damages to the display when used within the operating temperature.
- 3) The use of screen saver or sleep mode is recommended when static images are likely for long periods of time. This is to avoid the possibility of image sticking.
- 4) Spike noise can cause malfunction of the circuit. The recommended limitation of spike noise is no bigger than  $\pm 100 \text{ mV}$ .

|                                  |              |                              |      |        |
|----------------------------------|--------------|------------------------------|------|--------|
| JDI Taiwan Inc. Kaohsiung Branch | SHEET<br>NO. | 7B64PS 2713-TX20D200VM2BVA-2 | PAGE | 13-1/2 |
|----------------------------------|--------------|------------------------------|------|--------|

### 13.4 PRECAUTIONS of STORAGE

If the displays are going to be stored for years, please be aware the following notices.

- 1) Please store the displays in a dark room to avoid any damages from sunlight and other sources of UV light.
- 2) The recommended long-term storage temperature is between 10C°~35C° and 55%~75% humidity to avoid causing bubbles between polarizer and LCD glasses, and polarizer peeling from LCD glasses.
- 3) It would be better to keep the displays in the container, which is shipped from JDI, and do not unpack it.
- 4) Please do not stick any labels on the display surface for a long time, especially on the polarizer.

## 14. DESIGNATION of LOT MARK

- 1) The lot mark is showing in Fig.14.1. First 4 digits are used to represent production lot, T represented made in Taiwan, and the last 6 digits are the serial number.




Fig. 14.1

- 2) The tables as below are showing what the first 4 digits of lot mark are shorted for.

| Year | Lot Mark | Month | Lot Mark | Month | Lot Mark | Week       | Lot Mark |
|------|----------|-------|----------|-------|----------|------------|----------|
| 2019 | 9        | Jan.  | 01       | Jul.  | 07       | 1~7 days   | 1        |
| 2020 | 0        | Feb.  | 02       | Aug.  | 08       | 8~14 days  | 2        |
| 2021 | 1        | Mar.  | 03       | Sep.  | 09       | 15~21 days | 3        |
| 2022 | 2        | Apr.  | 04       | Oct.  | 10       | 22~28 days | 4        |
| 2023 | 3        | May   | 05       | Nov.  | 11       | 29~31 days | 5        |
|      |          | Jun.  | 06       | Dec.  | 12       |            |          |

- 3) Except letters I and O, revision number will be shown on lot mark and following letters A to Z.

- 4) The location of the lot mark is on the back of the display shown in Fig. 14.2.

Label example :



Fig. 14.2